



Standard Classification of Peat Samples by Laboratory Testing¹

This standard is issued under the fixed designation D4427; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope*

1.1 This classification is a system for subdividing and assigning nomenclature to peat samples through laboratory tests.

1.2 *This standard does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D1997 Test Method for Laboratory Determination of the Fiber Content of Peat Samples by Dry Mass

D2974 Test Methods for Moisture, Ash, and Organic Matter of Peat and Other Organic Soils

D2976 Test Method for pH of Peat Materials (Withdrawn 2013)³

D2980 Test Method for Volume Mass, Moisture-Holding Capacity, and Porosity of Saturated Peat Materials

D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction

3. Terminology

3.1 **Definitions**—For definitions of common technical terms in this standard, refer to Terminology **D653**.

3.2 **Definitions of Terms Specific to This Standard:**

¹ This classification is under the jurisdiction of ASTM Committee **D18** on Soil and Rock and is the direct responsibility of Subcommittee **D18.07** on Identification and Classification of Soils.

Current edition approved July 1, 2013. Published July 2013. Originally approved in 1984. Last previous edition approved in 2007 as D4427 – 07. DOI: 10.1520/D4427-13.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

3.2.1 **absorbency**—the amount of water by mass that can be held by the peat. This amount is expressed in terms of the water-holding capacity as measured using Test Method **D2980**.

3.2.2 **acidity**—expressed as the pH of the peat in water as measured using Test Method **D2976**.

3.2.3 **ash content**—the percentage by dry mass of material remaining after the oven dry peat is burned, using the methods described in Test Methods **D2974**.

3.2.4 **botanical composition**—the dominant plant genus, genera, or informal plant group identified by visual observation as comprising a portion of the fiber in the peat.

3.2.5 **fiber content**—the dry mass of fibers remaining after wet sieving over a No. 100 (150-μm) sieve. Fiber content is expressed as a percentage of the original dry mass, using the method described in Test Method **D1997**.

4. Significance and Use

4.1 The purpose of this classification is to standardize the naming of peat materials so that the peat-producer can better identify the product and the peat-consumer can better select peat materials to meet requirements. This system may also be used for peat resource evaluations, environmental impact reports, and preliminary engineering studies. The parameters selected for use in this classification are ones which have been determined to relate to the agricultural/horticultural, geotechnical, and energy uses of peats.

NOTE 1—The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice **D3740** are generally considered capable of competent and objective testing. Users of this standard are cautioned that compliance with Practice **D3740** does not in itself assure reliable results. Reliable results depend on many factors; Practice **D3740** provides a means of evaluating some of those factors.

5. Sampling

5.1 Representative samples of the peat should be used. The size and type of sample needed is dependent on the tests to be performed and the coarseness and moisture content of the peat. When taking the sample, it should be accurately identified and placed in a sealed container to prevent moisture loss.

*A Summary of Changes section appears at the end of this standard

6. Basis for Classification

6.1 Fiber Content:

- 6.1.1 *Fibric*—Peat with greater than 67 % fibers.
- 6.1.2 *Hemic*—Peat with between 33 % and 67 % fibers.
- 6.1.3 *Sapric*—Peat with less than 33 % fibers.

NOTE 2—These fiber content categories may be related to the widely used field assessment of the degree of humification (H) developed by Von Post.⁴ Fibric corresponds approximately to $H_1 - H_3$, hemic to $H_4 - H_6$, and sapric to $H_7 - H_{10}$.

6.2 Ash Content—As measured by Test Methods D2974:

- 6.2.1 *Low Ash*—Peat with less than 5 % ash.
- 6.2.2 *Medium Ash*—Peat with between 5 and 15 % ash.
- 6.2.3 *High Ash*—Peat with more than 15 % ash.

6.3 Acidity—As measured by Test Method D2976:

- 6.3.1 *Highly Acidic*—Peat with a pH less than 4.5.
- 6.3.2 *Moderately Acidic*—Peat with a pH between 4.5 and 5.5.
- 6.3.3 *Slightly Acidic*—Peat with a pH greater than 5.5 and less than 7.

6.3.4 Basic—Peat with a pH equal to or greater than 7.

6.4 Absorbency—As measured by Test Method D2980:

- 6.4.1 *Extremely Absorbent*—Peat with a water-holding capacity greater than 1500 %.
- 6.4.2 *Highly Absorbent*—Peat with a water-holding capacity between 800 and 1500 %.
- 6.4.3 *Moderately Absorbent*—Peat with a water-holding capacity greater than 300 and less than 800 %.
- 6.4.4 *Slightly Absorbent*—Peat with a water-holding capacity less than or equal to 300 %.

6.5 *Botanical Composition*—If a botanical designation is necessary, the following rules of naming should be applied:

6.5.1 If a single botanical name or other botanical designation is used, for example, *Sphagnum* Peat, *Taxodium* Peat, Moss Peat, Herbaceous Peat, or Woody Peat, it is necessary that at least 75 % of the fiber content of that peat should be derived from the designated type of plant material.

6.5.2 If two or more botanical designations are used in naming the peat, for example, Reed-Sedge Peat, Bay-Gum

Peat, *Myrica-Persea-Salix* Peat, Spruce-Moss-Sedge Peat, it is necessary that at least 75 % of the fiber content of that peat be composed of these types of plants as a group. Furthermore, the order of the plant types in the group name should indicate the relative quantity of each type in the peat with the dominant component appearing last.

NOTE 3—For peats with less than 33 % fiber (that is, Sapric) it would be advisable to refrain from using a botanical designation unless a significant portion of the non-fiber can be identified (for example, algal peat).

7. Use of This System

7.1 The order of classification should be as follows: fiber content, ash content, acidity, absorbency, and botanical designation, if necessary.

7.2 For example, a peat sample with a fiber content of 55 %, an ash content of 8 %, a pH of 4.7, a water-holding capacity of 1200 %, and with 70 % of its fibers derived from *Sphagnum* and 20 % from *Carex* would be designated a Hemic, Medium Ash, Moderately Acidic, Highly Absorbent, *Carex-Sphagnum* Peat.

8. Precision and Bias

8.1 *Precision*—Test data on precision is not presented due to the nature of the materials tested by this standard. It is either not feasible or too costly at this time to have ten or more laboratories participate in a round-robin testing program. In addition, it is either not feasible or too costly to produce multiple specimens that have uniform physical properties. Any variation observed in the data is just as likely to be due to specimen variation as to operator or laboratory testing variation.

8.1.1 Subcommittee D18.07 is seeking any data from the users of this classification that might be used to make a limited statement on precision.

8.2 *Bias*—There is no accepted reference value for this test method, therefore, bias cannot be determined.

9. Keywords

9.1 absorbency; acidity; ash content; botanical composition; classification; fiber content; laboratory testing; nomenclature; peat

⁴ Korpilaakko, E. O., and Woolnough, D. F., "Peatland Survey and Inventory", *Muskeg and the Northern Environment in Canada*, University of Toronto Press, 1977.

SUMMARY OF CHANGES

Committee D18 has identified the location of selected changes to this standard since the last issue (D4427 – 07) that may impact the use of this standard. (Approved July 1, 2013.)

- | | |
|---|---|
| <p>(1) Removed jargon and superlative wording and replaced with acceptable language.</p> <p>(2) Replaced “weight” with “mass” throughout.</p> <p>(3) Removed from Section 3 the definition of peat since it is already in Terminology D653.</p> | <p>(4) Reworded 3.2.5.</p> <p>(5) Renamed Section 5.</p> <p>(6) Renamed Section 7.</p> <p>(7) Added 7.1 and renumbered former 7.1 to 7.2.</p> |
|---|---|

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the ASTM website (www.astm.org/COPYRIGHT/).

Copyright ASTM International