



Standard Test Method for Assay of Peroxy Esters—Catalyzed Iodometric Procedure¹

This standard is issued under the fixed designation E 1228; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers the assay of organic peroxides of the peroxy ester type.

NOTE 1—Other test methods for the assay of organic peroxides are given in Test Methods E 298, E 475, and E 755.

1.2 Review the current material safety data sheets (MSDS) for detailed information concerning toxicity, first aid procedures, and safety precautions.

1.3 The values stated in SI units are to be regarded as the standard. No other units of measurement are included in this test method.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* Specific hazards statements are given in Section 9.

2. Referenced Documents

2.1 ASTM Standards:²

D 1193 Specification for Reagent Water

E 180 Practice for Determining the Precision of ASTM Methods for Analysis and Testing of Industrial and Specialty Chemicals

E 200 Practice for Preparation, Standardization, and Storage of Standard and Reagent Solutions for Chemical Analysis

E 298 Test Methods for Assay of Organic Peroxides

E 475 Test Method for Assay of Di-*tert*-Butyl Peroxide Using Gas Chromatography

¹ This test method is under the jurisdiction of ASTM Committee E15 on Industrial and Specialty Chemicals and is the direct responsibility of Subcommittee E15.01 on General Standards.

Current edition approved April 1, 2009. Published April 2009. Originally approved in 1988. Last previous edition approved in 2003 as E 1228 - 94(2003)^{e1}.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.

E 755 Test Method for Dicumyl Peroxide, Assay (Liquid Chromatography)

3. Terminology

3.1 Definitions:

3.1.1 *active oxygen*—the oxidizing power present in organic peroxides expressed as oxygen (equivalent weight 8.00).

4. Summary of Test Method

4.1 A sample is dissolved in a mixture of isopropyl alcohol, acetic acid, and cupric chloride. A solution of potassium iodide is added and the mixture is briefly heated, then allowed to react in the dark at room temperature for 30 min. The cupric ion catalyzes the reduction of the peroxide and the liberated iodine is titrated with standard sodium thiosulfate solution.

5. Significance and Use

5.1 Peroxy esters are widely used as chemical intermediates, catalysts, and initiators. This test method provides a procedure for assaying peroxy esters to determine if they are suitable for their intended use.

6. Interferences

6.1 Conjugated diolefins interfere under the conditions of analysis by absorbing iodine.

7. Apparatus

7.1 *Iodine Flasks*, 250-mL capacity, with stoppers.

NOTE 2—All glassware should be cleaned thoroughly with dichromate cleaning solution before use.

7.2 *Beakers*, 1-mL capacity, glass or PTFE.

7.3 *Buret*, 50-mL capacity, graduated in 0.1-mL subdivisions.

7.4 *Water Bath*, maintained at 60°C.

8. Reagents

8.1 *Purity of Reagents*—Reagent grade chemicals shall be used in all tests. Unless otherwise indicated, it is intended that all reagents shall conform to the Specifications of the Committee on Analytical Reagents of the American Chemical

*A Summary of Changes section appears at the end of this standard.

Society, where such specifications are available.³ Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

8.2 *Purity of Water*—Unless otherwise indicated, references to water shall be understood to mean Type II or III reagent water conforming to Specification D 1193.

8.3 *Acetic Acid*, glacial.

8.4 *Isopropyl Alcohol*.

8.5 *Hydrochloric Acid*, (1:100)—Dilute 1.0 mL of concentrated hydrochloric acid (HCl) to 100 mL with water.

8.6 *Cupric Chloride Solution*, 1 %—Dilute 1.0 g of anhydrous cupric chloride (CuCl₂) to 100 mL with water. Add 1.0 mL of 1:100 HCl and mix. The solution should be clear.

8.7 *Potassium Iodide Solution*, 50 %—Dissolve 25 g of potassium iodide (KI) in 25 mL of de-aerated water. This reagent should be freshly prepared just prior to use.

8.8 *Sodium Thiosulfate Standard Solution*, (0.1 meq/mL)—Prepare and standardize in accordance with the appropriate sections of Practice E 200.

8.9 *Nitrogen Gas*, oxygen-free.


9. Hazards

9.1 Organic peroxides are strong oxidizing agents and present potential fire and explosion hazards. Avoid contact with reducing agents and sources of heat, sparks, or open flames. Reactivity varies widely and some compounds may explode when shocked. Organic peroxides are irritating to the skin, eyes, and mucous membranes. Avoid bodily contact and handle only in a well-ventilated area.

10. Procedure

10.1 Add 50 mL of isopropyl alcohol and 15 mL of acetic acid to a 250-mL iodine flask. A graduate can be used for these additions.

10.2 Pipet 1.00 mL of 1 % cupric chloride solution into the flask. (**Warning**—The quantity of the cupric chloride catalyst solution must be carefully measured in order to obtain reproducible results as the reagent also reacts with iodide to liberate iodine according to the following Eq 1:



The blank titration should be approximately 1.0 mL. The results should be discarded and the analysis repeated if a significantly higher blank value is obtained.)

10.3 Sparge the solution with a rapid flow of nitrogen for 2 min, then stopper the flask and reserve.

10.4 Accurately weigh a sample containing 3 to 4 meq of active oxygen in a 1-mL beaker. Transfer the beaker containing the sample to the prepared flask and immediately restopper and mix. The approximate sample weight may be calculated as follows:

$$\text{Sample mass, g} = \frac{3.5 M}{2C \times 1000} \quad (2)$$

where:

M = molecular weight of compound, and

C = number of peroxide groups in the molecule.

NOTE 3—Volatile liquid peroxides may be diluted to a known volume with isopropyl alcohol and aliquots taken for analysis.

10.5 While maintaining a flow of nitrogen over the solution, add 5 mL (graduate) of freshly prepared 50 % KI solution, and then immediately restopper and swirl to mix.

10.6 Place the flask in a water bath maintained at 60°C for 20 s while gently swirling. The level of water in the bath should be above the level of solution in the flask.

NOTE 4—The reaction is temperature sensitive. If the temperature of the solution is above 25°C, a 30-min reaction time is generally sufficient for most peresters. If the temperature of the solution is less than 25°C, a longer reaction period may be required. By preheating the solution for 20 s at 60°C, the solution temperature is high enough to obtain complete reaction in 30 min with minor variation in the ambient laboratory temperature.

10.7 Remove the flask from the bath and allow to stand in a dark location at room temperature for 30 min.

10.8 Add 50-mL of de-aerated water and titrate the solution with 0.1 meq/mL Na₂S₂O₃ solution to the colorless end point. Record the number of millilitres required for the sample titration.

10.9 Subtract the number of millilitres required for titration of a blank carried simultaneously through the entire procedure and calculate the assay value of the sample. (See Warning note in 10.2.)

11. Calculation

11.1 Calculate the assay as follows:

$$\text{assay, as \% compound} = \frac{[(A - B) \times N \times M \times 100]}{(W \times 2C \times 1000)} \quad (3)$$

where:

A = Na₂S₂O₃ solution required for titration of the sample, mL,

B = Na₂S₂O₃ solution required for titration of the blank, mL,

N = meq/mL, normality of the Na₂S₂O₃ solution,

C = number of peroxide groups in the molecule,

M = molecular weight of the ground, and

W = sample used, g.

11.2 Calculate the percent of active oxygen in the compound as follows:

$$\text{active oxygen, \%} = \frac{[(A - B) \times N \times 0.008] \times 100}{W} \quad (4)$$

NOTE 5—This assay is based on the determination of active oxygen under specified conditions. If other organic peroxides are present as impurities and release equivalent amounts of active oxygen under the same conditions, their concentrations must be determined by appropriate HPLC or GC procedures and the results corrected accordingly.

12. Report

12.1 Report the assay value of the compound to the nearest 0.1 %.

³ *Reagent Chemicals, American Chemical Society Specifications*, American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see *Analar Standards for Laboratory Chemicals*, BDH Ltd., Poole, Dorset, U.K., and the *United States Pharmacopeia and National Formulary*, U.S. Pharmacopeial Convention, Inc. (USPC), Rockville, MD.

13. Precision and Bias ⁴

13.1 *Precision*—The following criteria should be used for judging the acceptability of results: (see **Note 6**).

13.1.1 *Repeatability (Single Analyst)*—The standard deviation for a single determination has been estimated to be 0.135 % at 14 DF. The 95 % limit for the difference between two such runs is 0.4 %.

13.1.2 *Laboratory Precision*—The standard deviation of results (each the average of duplicates), obtained by the same analyst on different days, has been estimated to be 0.141 % absolute at 6 DF. The 95 % limit for the difference between two such averages is 0.4 % absolute.

⁴ Supporting data are available from ASTM Headquarters. Request RR: E15-1036.

13.1.3 *Reproducibility (Multilaboratory)*—The standard deviation of results (each the average of duplicates), obtained by analysts in different laboratories, has been estimated to be 0.236 % absolute at 3 DF. The 95 % limit for the difference between two such averages is 0.7 %.

13.2 *Bias*—The bias of this test method cannot be determined due to the unavailability of suitable reference materials.

NOTE 6—The above precision estimates are based upon an interlaboratory study performed in 1987 on samples of *t*-butyl perbenzoate and *t*-butyl peracetate with manufacturer's assays of 98.3 % and 51.0 %, respectively. One analyst in each of four laboratories performed duplicate determinations and repeated one day later, for a total of 32 determinations. Practice E 180 was used in developing these precision estimates.

14. Keywords

14.1 active oxygen; iodometric; peroxides; peroxyesters

SUMMARY OF CHANGES

Committee E15 has identified the location of selected changes to this standard since the last issue (E 1228 - 94(2003)^{e1}) that may impact the use of this standard. (April 1, 2009)

- | | |
|---|--|
| <p>(1) Updated units of measure to comply with the International System of Units (SI).</p> <p>(2) Added paragraph in Scope stating that the SI units are to be considered standard.</p> | <p>(3) Added Summary of Changes section.</p> |
|---|--|

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).