



Standard Specification for PB Exterior Insulation and Finish Systems¹

This standard is issued under the fixed designation E 2568; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers PB Exterior Insulation and Finish Systems (EIFS) defined as an exterior, non-bearing wall covering providing a weather-resistant exterior wall envelope on walls required to be combustible or noncombustible, fire-resistance-rated or nonfire-resistance-rated. Further, PB EIFS is a system described as being applied over insulation board, an adhesive or mechanical attachment of the insulation board to a substrate, or both, glass fiber reinforcing mesh, a base coat on the face of the insulation board, and a textured protective finish coat.

1.2 This specification does not cover Class PB EIFS with drainage.

1.3 This specification qualifies EIFS products for use in normal service conditions and is not for evaluating in service EIFS installations.

1.4 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

- B 117** Practice for Operating Salt Spray (Fog) Apparatus
- C 297/C 297M** Test Method for Flatwise Tensile Strength of Sandwich Constructions
- C 578** Specification for Rigid, Cellular Polystyrene Thermal Insulation
- D 2247** Practice for Testing Water Resistance of Coatings in 100 % Relative Humidity
- E 84** Test Method for Surface Burning Characteristics of Building Materials

E 119 Test Methods for Fire Tests of Building Construction and Materials

E 330 Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference

E 331 Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference

E 631 Terminology of Building Constructions

E 2098 Test Method for Determining Tensile Breaking Strength of Glass Fiber Reinforcing Mesh for Use in Class PB Exterior Insulation and Finish Systems (EIFS), after Exposure to a Sodium Hydroxide Solution

E 2110 Terminology for Exterior Insulation and Finish Systems (EIFS)

E 2134 Test Method for Evaluating the Tensile-Adhesion Performance of an Exterior Insulation and Finish System (EIFS)

E 2485 Test Method for Freeze/Thaw Resistance of Exterior Insulation and Finish Systems (EIFS) and Water Resistive Barrier Coatings

E 2486 Test Method for Impact Resistance of Class PB and PI Exterior Insulation and Finish Systems (EIFS)

G 23 Practice for Operating Light-Exposure Apparatus (Carbon-Arc Type) With and Without Water for Exposure of Nonmetallic Materials (Discontinued 2001)³

G 26 Practice for Operating Light-Exposure Apparatus (Xenon-Arc Type) With and Without Water for Exposure of Nonmetallic Materials (Discontinued 2001)³

G 153 Practice for Operating Enclosed Carbon Arc Light Apparatus for Exposure of Nonmetallic Materials

G 155 Practice for Operating Xenon Arc Light Apparatus for Exposure of Non-Metallic Materials

2.2 NFPA Standards:⁴

ANSI/NFPA 268 Standard Test Method for Determining Ignitability of Exterior Wall Assemblies Using a Radiant Heat Energy Source

ANSI/NFPA 285 Standard Fire Test Method for the Evaluation of Fire Propagation Characteristics of Exterior, Nonload-bearing Wall Assemblies Containing Combustible Components

¹ This test method is under the jurisdiction of ASTM Committee E06 on Performance of Buildings and is the direct responsibility of Subcommittee E06.58 on Exterior Insulation and Finish Systems (EIFS).

Current edition approved Sept. 1, 2007. Published September 2007.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Withdrawn.

⁴ Available from National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02169-7471, <http://www.nfpa.org>.

3. Terminology

3.1 Definitions are in accordance with Terminology E 2110 unless otherwise specified.

3.2 *Definitions of Terms Specific to This Standard:*

3.3 *EIFS-related construction, n*—construction that works in conjunction with the EIFS, but is not part of the EIFS.

3.4 *class PB EIFS, n*—EIFS where the base coat varies in thickness depending upon the number of layers, or thickness of reinforcing mesh. The reinforcing mesh is glass fiber mesh that is encapsulated by the base coat per EIFS manufacturer recommendations. Protective finish coats, of various thicknesses in a variety of textures and colors, are applied over the base coat.

4. Materials and Manufacture

4.1 *Product Description*—The material and specifications shall be as specified by the selected EIFS manufacturer and shall be defined as in Terminology E 2110 except as modified herein.

5. Performance Requirements

5.1 The system and its components shall meet or exceed the performance standards described in 5.2-5.7 of this specification.

5.2 *Performance:*

5.2.1 System performance shall be in conformance with the minimum properties listed in Table 1.

5.3 Component performance shall be in conformance with Table 2.

5.4 *Fire Performance:*

5.4.1 System fire performance shall be in conformance with Table 3 as required.

5.5 Component fire performance shall be in accordance with Table 4.

5.6 Structural performance shall be in conformance with Table 5.

5.7 Impact shall be in conformance with Table 6.

6. Inspection

6.1 Materials supplied by the manufacturer shall be supplied to the site location in original unopened containers with labels intact. Upon arrival, the materials shall be inspected for damage, and the manufacturer notified of any discrepancies. Unsatisfactory materials shall not be used.

7. Packaging and Package Marking

7.1 A description of the method of packaging and field identification of the material shall include the following:

7.1.1 Name and address of the manufacturer.

7.1.1.1 Identification of components,

7.1.1.2 Lot or batch number,

7.1.1.3 Quantity of material in the packaged mix,

7.1.1.4 Storage instructions,

7.1.1.5 Pot life,

7.1.1.6 Expiration date (when applicable), and

7.1.1.7 The name of the accredited inspection agency (when applicable).

8. Keywords

8.1 adhesive; basecoat; Class PB; EIFS; Exterior Insulation and Finish System; system; textured finish; thermal insulation board

TABLE 1 System Performance Tests

Characteristic	Test Method	Minimum Properties
Accelerated weathering	G 153 ^A or G 155 ^{BC}	No deleterious effects ^D after 2000 hours when viewed under 5× magnification.
Freeze/thaw	E 2485 (Formerly EIMA Std. 101.01)	No deleterious effects ^D when viewed under 5× magnification
Salt spray resistance	B 117	No deleterious effects ^D at 300-hour exposure period
Tensile bond adhesion	E 2134 or C 297/C 297M	No failure in the adhesive coat, base coat or finish coat. The insulation board shall fail cohesively except that 25 % adhesive failure is acceptable. For tested values of 103 kPa (15 psi) or greater, adhesive failure up to 100 % is acceptable.
Water penetration	E 331	The exterior wall envelope design shall be considered to resist wind-driven rain where the results of testing indicate that water did not penetrate control joints in the exterior wall envelope, joints at the perimeter of openings or intersections of terminations with dissimilar materials after 2 hours of water application at a pressure differential of 299 Pa (6.24 psf).
Water resistance	D 2247	No deleterious effects ^D at 14- day exposure

^Aformerly specified in Test Method G 23

^BFormerly specified in Test Method G 26

^CDue to differences in spectral power distribution, results from G 155, Cycle 1 and G 153, Cycle 1 cannot be directly compared.

^DNo deleterious effects; no cracking, checking, crazing, erosion, rusting, blistering, peeling, or delamination.

TABLE 2 Component Performance Tests

Characteristic	Test Method	Minimum Properties
Physical properties and requirements for EPS	C 578	Meets TYPE 1
Alkali resistance of reinforcing mesh	E 2098	21 dN/cm (120 pli) retained tensile strength

TABLE 3 System Fire Performance Tests

Characteristic	Test Method	Minimum Properties
Fire endurance Full-scale multi-story fire test	E 119 ANSI/NFPA 285	Maintain fire resistance of known, rated wall assembly 1. Resistance to vertical spread of flame within the core of the panel from one story to the next. 2. Resistance to flame propagation over the exterior face of the system. 3. Resistance to vertical spread of flame over the interior (room side) surface from one story to the next. 4. Resistance to lateral spread of flame from the compartment of fire origin to adjacent spaces
Ignition resistance	ANSI/NFPA 268	No surface ignition when exposed to 12.5 kW/m ² .

TABLE 4 Fire Performance Test

Characteristic	Test Method	Minimum Properties
Surface burning	E 84	Insulation board and reinforced coating system shall each separately have a flame spread of 25 or less, and smoke developed of 450 or less

TABLE 5 Structural Performance Tests

Characteristic	Test Method	Minimum Properties
Wind load	E 330	Report negative and positive wind load values

TABLE 6 Impact Performance Tests

NOTE—The lowest value stated for each level is the minimum value required.

Characteristic	Test Method	Minimum Properties
Impact resistance	E 2486	Standard: 2.83-5.54J (25-49 in-lb) Medium: 5.65-10.1J (50-89 in-lb) High: 10.2-17J (90-150 in-lb) Ultra High: >17J (> 150 in-lb)

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).