



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS K 6251 : 2010

(JRMA/JSA)

**Rubber, vulcanized or
thermoplastics—Determination of
tensile stress-strain properties**

ICS 83.060

Reference number : JIS K 6251 : 2010 (E)

Date of Establishment: 1993-02-01

Date of Revision: 2010-12-20

Date of Public Notice in Official Gazette: 2010-12-20

Investigated by: Japanese Industrial Standards Committee
Standards Board

Technical Committee on Chemical Products

JIS K 6251:2010, First English edition published in 2011-08

Translated and published by: Japanese Standards Association
4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

AT

Contents

	Page
Introduction.....	1
1 Scope.....	1
2 Normative references	1
3 Terms and definitions	2
4 Principle	4
5 General	4
6 Test piece	5
6.1 Dumb-bell-shaped test piece	5
6.2 Ring-shaped test piece	6
6.3 Selection of test pieces	6
7 Testing apparatus	8
8 Number of test pieces	10
9 Sampling and preparation of test pieces	10
9.1 Dumb-bell-shaped test piece	10
9.2 Ring-shaped test piece	10
10 Conditioning of samples and test pieces	10
10.1 Period from vulcanization or moulding to testing	10
10.2 Storage of samples and test pieces	10
10.3 Conditioning of samples	11
10.4 Conditioning of test pieces	11
11 Gauging of dumb-bell test pieces	11
12 Measurement of test pieces	11
12.1 Dumb-bell-shaped test piece	11
12.2 Ring-shaped test piece	11
12.3 Median thickness	12
13 Procedure	12
13.1 Dumb-bell-shaped test piece	12
13.2 Ring-shaped test piece	12
13.3 Measurement for obtaining tensile strength, tensile stress at break and elongation at break	13
13.4 Measurement for obtaining tensile stress at a given elongation	13
13.5 Measurement for obtaining tensile stress at yield and elongation at yield	13

14	Temperature of test.....	13
15	Calculation of results	13
15.1	Dumb-bell-shaped test piece	13
15.2	Ring-shaped test piece	14
16	Expression of results.....	16
17	Test report	16
Annex A (informative)	Precision	17
Annex B (informative)	Analysis of ITP data and dumb-bell shape	21
Annex JA (informative)	Comparison table between JIS and corresponding International Standard	26

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by the Japan Rubber Manufacturers Association (JRMA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently **JIS K 6251**:2004 is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with a patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have technical properties. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying the patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have the said technical properties.

Rubber, vulcanized or thermoplastics— Determination of tensile stress-strain properties

Introduction

This Japanese Industrial Standard has been prepared based on the fourth edition of **ISO 37** published in 2005 and **ISO 37 TECHNICAL CORRIGENDUM 1** published in 2008 with some modifications of the technical contents.

The portions given sidelines or dotted underlines are the matters in which the contents of the original International Standard have been modified. A list of modifications with the explanations is given in Annex JA.

1 Scope

This Standard specifies the determination method of the tensile stress-strain properties of vulcanized rubbers and thermoplastic rubbers.

The properties to be determined shall be the tensile strength, elongation at break, stress at a given elongation, elongation at a given stress, tensile stress at yield and elongation at yield. The measurement of the tensile stress at yield and the strain at yield applies only to vulcanized rubbers and thermoplastic rubbers having the yield.

NOTE : The International Standard corresponding to this Standard and the symbol of degree of correspondence are as follows.

ISO 37:2005 *Rubber, vulcanized or thermoplastic—Determination of tensile stress-strain properties* and TECHNICAL CORRIGENDUM 1:2008 (MOD)

In addition, symbols which denote the degree of correspondence in the contents between the relevant International Standard and **JIS** are IDT (identical), MOD (modified), and NEQ (not equivalent) according to **ISO/IEC Guide 21-1**.

Warning : Persons using this Standard should be familiar with normal laboratory practice. This Standard does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent edition of the standard (including amendments) indicated below shall be applied.

JIS K 6200 *Rubber—Vocabulary*

JIS K 6250 *Rubber—General procedures for preparing and conditioning test pieces for physical test methods*