CORROSION RESISTANCE TABLES

Metals, Nonmetals, Coatings, Mortars, Plastics, Elastomers and Linings, and Fabrics

Fifth Edition, Revised and Expanded



Philip A. Schweitzer, P.E.

PART D, POT-ZIN

CORROSION RESISTANCE TABLES

Part D, POT-ZIN

CORROSION TECHNOLOGY

Editor
Philip A. Schweitzer, P.E.
Consultant
York, Pennsylvania

1. *Corrosion Protection Handbook: Second Edition, Revised and Expanded*, edited by Philip A. Schweitzer
2. *Corrosion Resistant Coatings Technology*, Ichiro Suzuki
3. *Corrosion Resistance of Elastomers*, Philip A. Schweitzer
4. *Corrosion Resistance Tables: Metals, Nonmetals, Coatings, Mortars, Plastics, Elastomers and Linings, and Fabrics: Third Edition, Revised and Expanded (Parts A and B)*, Philip A. Schweitzer
5. *Corrosion-Resistant Piping Systems*, Philip A. Schweitzer
6. *Corrosion Resistance of Zinc and Zinc Alloys: Fundamentals and Applications*, Frank Porter
7. *Corrosion of Ceramics*, Ronald A. McCauley
8. *Corrosion Mechanisms in Theory and Practice*, edited by P. Marcus and J. Oudar
9. *Corrosion Resistance of Stainless Steels*, C. P. Dillon
10. *Corrosion Resistance Tables: Metals, Nonmetals, Coatings, Mortars, Plastics, Elastomers and Linings, and Fabrics: Fourth Edition, Revised and Expanded (Parts A, B, and C)*, Philip A. Schweitzer
11. *Corrosion Engineering Handbook*, edited by Philip A. Schweitzer
12. *Atmospheric Degradation and Corrosion Control*, Philip A. Schweitzer
13. *Mechanical and Corrosion-Resistant Properties of Plastics and Elastomers*, Philip A. Schweitzer
14. *Environmental Degradation of Metals*, U. K. Chatterjee, S. K. Bose, and S. K. Roy
15. *Environmental Effects on Engineered Materials*, edited by Russell H. Jones
16. *Corrosion-Resistant Linings and Coatings*, Philip A. Schweitzer
17. *Corrosion Mechanisms in Theory and Practice: Second Edition, Revised and Expanded*, edited by Philippe Marcus
18. *Electrochemical Techniques in Corrosion Science and Engineering*, Robert G. Kelly, John R. Scully, David W. Shoesmith, and Rudolph G. Buchheit
19. *Metallic Materials: Physical, Mechanical, and Corrosion Properties*, Philip A. Schweitzer
20. *Encyclopedia of Corrosion Technology: Second Edition, Revised and Expanded*, Philip A. Schweitzer
21. *Corrosion Resistance Tables: Metals, Nonmetals, Coatings, Mortars, Plastics, Elastomers and Linings, and Fabrics: Fifth Edition, Revised and Expanded (Parts A, B, C, and D)*, Philip A. Schweitzer

ADDITIONAL VOLUMES IN PREPARATION

CORROSION RESISTANCE TABLES

Metals, Nonmetals, Coatings, Mortars, Plastics, Elastomers and Linings, and Fabrics

Fifth Edition, Revised and Expanded

PART D, POT-ZIN

Philip A. Schweitzer, P.E.
Consultant
York, Pennsylvania, U.S.A.

MARCEL DEKKER

MARCEL DEKKER, INC. NEW YORK • BASEL

Although great care has been taken to provide accurate and current information, neither the author(s) nor the publisher, nor anyone else associated with this publication, shall be liable for any loss, damage, or liability directly or indirectly caused or alleged to be caused by this book. The material contained herein is not intended to provide specific advice or recommendations for any specific situation.

Trademark notice: Product or corporate names may be trademarks or registered trademarks and are used only for identification and explanation without intent to infringe.

Library of Congress Cataloging-in-Publication Data
A catalog record for this book is available from the Library of Congress.

ISBN:

Part A, 0-8247-5673-8
Part B, 0-8247-5674-6
Part C, 0-8247-5675-4
Part D, 0-8247-5676-2

This book is printed on acid-free paper.

Headquarters
Marcel Dekker, Inc.
270 Madison Avenue, New York, NY 10016, U.S.A.
tel: 212-696-9000; fax: 212-685-4540

Distribution and Customer Service
Marcel Dekker, Inc.
Cimarron Road, Monticello, New York 12701, U.S.A.
tel: 800-228-1160; fax: 845-796-1772

Eastern Hemisphere Distribution
Marcel Dekker AG
Hutgasse 4, Postfach 812, CH-4001 Basel, Switzerland
tel: 41-61-260-6300; fax: 41-61-260-6333

World Wide Web
http://www.dekker.com

The publisher offers discounts on this book when ordered in bulk quantities. For more information, write to Special Sales/Professional Marketing at the headquarters address above.

Copyright © 2004 by Marcel Dekker, Inc. All Rights Reserved.

Neither this book nor any part may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, microfilming, and recording, or by any information storage and retrieval system, without permission in writing from the publisher.

Current printing (last digit):

10 9 8 7 6 5 4 3 2 1

PRINTED IN THE UNITED STATES OF AMERICA

Preface

The field of corrosion resistance is one of constant change. Research and development is continuously underway, both involving new materials and expanding the uses of known materials. These advances are particularly important for such areas as chemical processing and pollution control. Increased knowledge of corrosion resistance and the mechanisms of corrosion is a vital factor in this work.

This fifth edition of the corrosion resistance tables has been prepared in an attempt to provide the most current information available. Data on the corrosion resistance for the materials and corrodents covered in the previous editions have been greatly expanded, and data for 83 additional corrodents have been incorporated in this edition.

Philip A. Schweitzer, P.E.

Introduction

For years the chemical engineer has been faced with the problem of selecting the proper material to be used for the construction of processing vessels, storage tanks, valves, piping systems, and whatever else comes into contact with potentially corrosive chemicals. During the early days of the chemical engineering profession, the list of materials from which to choose was relatively small, consisting primarily of various metals and their alloys.

As technology made advances, new alloys were developed as well as synthetic materials such as plastics. Simultaneously, new chemicals came into being, many of which required the newly developed materials of construction for safe handling.

However, the problem of material selection is not limited to the chemical engineer. Many industries that use chemicals in their everyday operations cannot be classified as members of the chemical processing industry, yet they have the same problems of selecting the proper materials of construction to handle these products. This is particularly true in the area of pollution control. Many processes for the elimination of air and/or water pollution involve chemical changes in the pollutants that result in problems of corrosion that were not present before.

The dictionary defines corrosion as "eating or wearing away by slow degrees," a definition that is rather broad and does not restrict the application of the word to the destruction of metals. This is as it should be because of the availability of so many nonmetallic materials of construction.

Most reference sources for the selection of proper materials of construction are devoted to either a specific group of metals or alloys, plastics, rubbers (synthetic and natural), gasketing materials, or packing materials. An individual with the problem of selecting materials of construction must usually make a selection in more than one of the preceding categories, which necessitates going to several sources for the information. It is the purpose of this book to provide one source from which all the components of a system may be selected, including processing vessels, tanks, pumps, piping, valves, gaskets, packing, etc.

These corrosion tables have been prepared with the intention of assisting not only the practicing engineer, but whoever may be charged with the responsibility of selecting the proper materials of construction for a specific application. Any table of this type should be used only as a guide since it is extremely difficult, and at times impossible, to duplicate actual operating conditions. To fully guarantee the suitability of a particular material of construction, corrosion tests should be conducted under actual operating conditions.

In the tables, all the chemicals are assumed to be in the pure state or in concentrated or saturated aqueous solutions, unless otherwise indicated. Concentration percentages used are by weight.

Two types of notation have been employed to indicate the suitability of a specific material of construction—one for metallic materials and one for nonmetallic materials. This is necessary because their mechanisms of corrosion differ.

CORROSION OF METALLICS

The four most common forms of corrosion of metals are

1. General corrosion
2. Galvanic corrosion
3. Stress corrosion cracking
4. Intergranular corrosion

General Corrosion

Metals resist corrosion by the formation of a passive film on the surface, which in a sense is also corrosion but once formed prevents further degradation of the base metal. Most metals form this film after a period of time of exposure to the air. *Passivation* is the name applied to the chemical treatment procedure that helps to form the film more rapidly. For example, exposure of austenitic stainless steels to nitric acid will produce this protective film.

As long as these films remain intact, they protect the base metal from further attack. Certain chemicals attack various films at varying rates. When this occurs, the metal is said to corrode. Such interaction between a chemical and a metal can be determined from the corrosion tables. This type of corrosion is known as general corrosion.

Galvanic Corrosion

Galvanic corrosion occurs when two or more dissimilar metals are in contact, or when metals having the same analysis have different surface conditions and an electrolyte is present.

Under these conditions an electrolytic cell is formed. All metals and alloys have certain "built-in" properties that cause them to react as an anode or a cathode when in contact with dissimilar metals or alloys. Whether a particular material will react as a cathode or an anode can be determined from the relative positions of the materials in the galvanic series. The farther apart two materials are from each other in the galvanic series, with all other factors being equal, the greater the rate of corrosion. The material closest to the anodic end will be the one to corrode. For example, if tin and zinc were in contact, the zinc would corrode, whereas if tin and copper were in contact, the tin would corrode.

The rate of attack is also affected by the relative size of the materials and the specific electrolyte present. A small anode area in contact with a large cathode area will result in a rapid severe attack. Conversely, a large anode area in contact with a small cathode area will lessen the rate of galvanic attack since the same total electromagnetic driving force of corrosion will be spread out over a larger area. The higher the degree of ionization of the electrolyte, the greater the rate of attack.

Galvanic corrosion can be prevented by judicious use of dissimilar metals.

Galvanic series

Anodic (corroded) end	Hastelloy C (active)
Magnesium	Brasses
Magnesium alloys	Copper
Zinc	Bronzes
Aluminum 5052	Cupro-nickel alloys
Aluminum 6061	Monel
Cadmium	Silver solder
Aluminum AA 2017	Nickel (passive)
Iron and carbon steel	Inconel (passive)
Copper steel	Ferritic stainless (passive)
4-6% Chromium steel	Austenitic stainless (passive)

Galvanic series	
Ferritic stainless (active) 400 series	Titanium
Austenitic stainless (active) 18-8 series	Hastelloy C (passive)
Lead-tin solder	Silver
Lead	Graphite
Tin	Gold
Nickel (active)	Platinum
Inconel (active)	*Cathodic (protected) end*

Stress Corrosion Cracking

All metals are subject to stress corrosion cracking, which results from residual or applied stress in the metal. Residual stresses can occur as a result of cold forming or quenching after heat treating. Annealing after fabrication will minimize these stresses. Applied stresses can result from faulty design, vibrations, flexing, and excessive expansion and contraction due to thermal changes.

The particular corrodent will determine the degree of effect. Halogen salts are among the materials that will attack metals most vigorously when stresses are present.

Intergranular Corrosion

Corrosive attack involving intergranular corrosion occurs only at the grain boundaries of austenitic stainless steels. All austenitic stainless steels contain carbon in small amounts. When this material is heated to the sensitizing range (850 to 1650°F), such as in welding, carbon is precipitated out at the grain boundaries in the form of chromium carbide. The chromium has been taken from the grain boundaries, changing the composition and making this area even more susceptible to corrosive attack.

This effect can be minimized by annealing the stainless steel after it has been sensitized. This is done by heating the alloy to 1800°F or higher, depending on the specific alloy, and then quickly cooling it through the sensitizing range to prevent the carbon from precipitating out. Another way to reduce this effect is to limit the carbon content to less than 0.03%. This extra-low-carbon (ELC) stainless steel can be welded without the danger of carbide precipitation.

CORROSION OF NONMETALLICS

Plastic materials are attacked by solvation and chemical reactions. Solvation is the penetration of the plastic by corrosive elements that cause softening, swelling, and ultimate failure. Plastics, in contrast to metals, do not exhibit a useful corrosion rate; they usually either completely resist attack or deteriorate rapidly. Because of this difference in corrosion mechanism, the two types of notation used in the tables were established.

Plastic and elastomeric materials are compounded by the manufacturer. Properties of the materials produced can vary from manufacturer to manufacturer. By compounding, it is possible to improve specific mechanical/physical properties, but usually at the expense of another property. Consequently, materials that have been produced to improve a mechanical property may have had their ability to resist corrosion reduced. Since all plastic or elastomeric materials produced may not have the corrosion resistance indicated in the charts, the manufacturer of the material to be used should be consulted. The same reasoning applies to the physical/mechanical properties required for the application.

A word of caution should also be given regarding temperatures. The table shows only the resistivity to corrosive attack at various temperatures. Although the material may be corrosion-resistant at a specific temperature, this does not mean that the physical/mechanical properties would be satisfactory at these temperatures. These must be investigated at the operating temperature to ensure that the material has the proper mechanical strength for the application.


Using the Tables

The tables are arranged alphabetically according to corrodent. Unless otherwise noted, the corrodent is considered pure in the case of liquids, or a saturated aqueous solution in the case of solids. All percentages shown are by weight.

There are four pages for each corrodent: one for the resistance to metals; one for the resistance to nometallic materials, coatings, and mortars; one for the resistance to plastics; and one for the resistance to elastomers, linings, and fabrics.

TABLE NOTATION

Since corrosion is a function of temperature, the tables indicate the suitability of each material at varying temperatures. Symbols used to designate specific corrosion rates are shown on the bottom of the metals pages. The use of the temperature scale is explained by the following example:



From the sample table, it is seen that in the presence of an 80% solution of acetic acid, monel has a corrosion rate varying with temperature rated as follows:

- From 60 to 120°F, excellent (E): <2 mils penetration/year.
- From 120 to 210°F, good (G): <20 mils penetration/year.
- There are no data for temperatures beyond 210°F.

Type 316 stainless steel has a corrosion rate for the same corrodent varying with temperature rated as follows:

- From 60 to 100°F, excellent (E): <2 mils penetration/year.
- From 100 to 180°F, good (G): <20 mils penetration/year.
- From 180 to 240°F, satisfactory (S): <50 mils penetration/year.
- Above 240°F, unsatisfactory (U): >50 mils penetration/year.

Nonmetallics are only rated as resistant (R) or unsatisfactory (U), because they do not exhibit a useful corrosion rate, as explained previously.

Other Notation

Further information regarding the corrosion of specific materials by certain corrodents is provided by the following symbols. In the tables, the symbols follow the applicable material or corrodent name.

Symbol	Meaning
1	Material is subject to pitting.
2	Material is subject to stress cracking.
3	Material is subject to crevice attack.
4	Not for use with carbonated beverages.
5	Material should be passivated.
6	Alkaline.
7	Acid free.
8	Acid free and passivated.
9	Material is subject to intergranular corrosion.
10	Synthetic veil or surfacing mat should be used.
11	Material will cause stress cracking in many polyethylenes. A stress crack-resistant, high molecular weight polyethylene must be used.
12	Material is subject to stress cracking when wet.
13	Corrodent will be absorbed.
14	Corrodent will permeate.
ALL	Data applies to all concentrations.
ELC	Material is low-carbon grade.
SAT	Solution is saturated.


General Notes

- Incolloy category is applicable to grades 800 and 825 only, unless otherwise specified.
- Inconel category is applicable to grade 600, unless otherwise specified.
- The mortars specified are for use fully immersed or subject to constant flow.
- The coatings specified are for use fully immersed or for wet spills or wet fumes.
- There are many epoxy formulations. Where epoxy is shown as being a satisfactory material of construction, it indicates that there is a suitable formulation. Manufacturers should be consulted for the suitability of their specific formulation.
- See Appendix 3 for plating solution compositions.

READING THE TEMPERATURE SCALE

When using the tables, note that the vertical lines refer to temperatures midway between the temperatures cited (see the sample table below). Thus, aluminum is corroded by pyridine at a rate less than 20 mils/year between 60 and 350°F. Brass, carbon steel, and copper have the same corrosion rate between the temperatures of 60 and 210°F, 120°F, and 80°F, respectively.

When a material is indicated to be unsatisfactory at a specific temperature, it is also unsatisfactory at all temperatures above the one shown. A blank in the chart indicates that no data are available.


PYRIDINE
°C
°F
Metals
15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293
60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560
Admiralty Brass
Aluminum
Aluminum Bronze
Brass
Bronze
Carbon Steel
Columbium (Niobium)
Copper
Hastelloy B/B–2
Hastelloy C/C–276
G
G
G
G

Contents

Preface *iii*
Introduction *v*
Using the Tables *ix*

Part A, ACE–CHR
A
Acetaldehyde 1
Acetamide 5
Acetate Solvents, Crude 9
Acetate Solvents, Pure 13
Acetic Acid 10% 17
Acetic Acid 20% 21
Acetic Acid 50% 25
Acetic Acid 80% 29
Acetic Acid, Glacial 33
Acetic Acid Vapors 37
Acetic Anhydride 41
Acetone 45
Acetone, 50% Water 49
Acetonitrile 53
Acetophenone 57
Acetyl Chloride 61
Acetylene 65
Acetylene Tetrabromide 69
Acid Mine Water 73
Acrylic Acid 77
Acrylonitrile 81
Adipic Acid 85
Air 89
Alkaform Anesthesia 93
Allyl Alcohol 97
Allyl Chloride 101
Alum (Aluminum Potassium Sulfate) 105
Alum Ammonium 109

Alum Ammonium Sulfate	113
Alum Chrome	117
Alum Potassium	121
Aluminum Acetate (Sat.)	125
Aluminum Bromide	129
Aluminum Chloride Aqueous	133
Aluminum Chloride Dry	137
Aluminum Chlorohydroxide (Wet)	141
Aluminum Fluoride (Sat.)	145
Aluminum Hydroxide	149
Aluminum Nitrate (Sat.)	153
Aluminum Oxalate	157
Aluminum Oxychloride	161
Aluminum Phosphate	165
Aluminum Potassium Sulfate	169
Aluminum Sulfate (Sat.)	173
Amino Acids	177
2-Aminoethanol	181
Ammonia (Anhydrous)	185
Ammonia Gas	189
Ammonium Acetate	193
Ammonium Bicarbonate	197
Ammonium Bifluoride	201
Ammonium Bromide 5%	205
Ammonium Carbonate (Sat.)	209
Ammonium Chloride 10%	213
Ammonium Chloride 28%	217
Ammonium Chloride 50%	221
Ammonium Chloride (Sat.)	225
Ammonium Citrate	229
Ammonium Dichromate	233
Ammonium Diphosphate	237
Ammonium Fluoride 10%	241
Ammonium Fluoride 25%	245
Ammonium Fluorosilicate	249
Ammonium Formate	253
Ammonium Hydroxide 10%	257
Ammonium Hydroxide 25%	261
Ammonium Hydroxide (Sat.)	265
Ammonium Metaphosphate	269
Ammonium Nitrate	273
Ammonium Oxalate 10%	277
Ammonium Oxalate 20–30%	281
Ammonium Oxalate	285
Ammonium Persulfate	289
Ammonium Phosphate	293
Ammonium Sulfate 10–40%	297
Ammonium Sulfate (Sat.)	301
Ammonium Sulfide	305
Ammonium Sulfite	309

Ammonium Thiocyanate 313
Amyl Acetate 317
Amyl Alcohol 321
Amyl Chloride 325
Aniline 329
Aniline Chlorohydrate 333
Aniline Hydrochloride 337
Aniline Oil 341
Anthraquinone 345
Anthraquinone Sulfonic Acid 349
Antimony Trichloride 353
Aqua Regia 3:1 357
Argon 361
Aroclor 365
Arsenic Acid 369
Arsenious Acid 373
Asphalt 377
Asphalt Emulsion 381

B

Barium Acetate 385
Barium Carbonate (Sat.) 389
Barium Chloride (Sat.) 393
Barium Cyanide 397
Barium Hydroxide (Sat.) 401
Barium Nitrate 405
Barium Sulfate 409
Barium Sulfide 413
Beer 417
Beet Sugar Liquors 421
Benzaldehyde 425
Benzene, Benzol 429
Benzene Sulfonic Acid 10% 433
Benzene Sulfonic Acid 100% 437
Benzoic Acid 441
Benzonitrile 445
Benzoyl Chloride 449
Benzyl Acetate 453
Benzyl Alcohol 457
Benzyl Chloride 461
Bismuth Carbonate 465
Black Liquor 469
Bleach, 12.5% Active Chlorine 473
Blood 477
Borax 481
Borax Liquors 485
Bordeaux Mixtures 489
Boric Acid 493
Brine Acid 497



Bromic Acid 501
Bromine Gas Dry 505
Bromine Gas Moist 509
Bromine Liquid 513
Bromine Water Dilute 517
Bromine Water (Sat.) 521
Bromobenzene 525
Butadiene (Butylene) 529
Butane 533
Buttermilk 537
Butyl Acetate 541
Butyl Alcohol 545
Butyl Alcohol Primary 549
Butyl Alcohol Secondary 553
Butyl Alcohol Tertiary 557
n-Butylamine 561
Butyl Bromide 565
Butyl Cellosolve 569
Butyl Chloride 573
Butylene (Butadiene) 577
Butyl Ether 581
Butyl Lactate 585
n-Butyl Mercaptan 589
Butyl Phenol 593
Butyl Phthalate 597
Butyl Stearate 601
Butyne Diol 605
Butyraldehyde 609
Butyric Acid 613

C
Cadmium Chloride 617
Cadmium Cyanide 621
Cadmium Sulfate 10% 625
Calcium Acetate 629
Calcium Bicarbonate 633
Calcium Bisulfate 637
Calcium Bisulfide 641
Calcium Bisulfite 645
Calcium Bromide 38% 649
Calcium Carbonate 653
Calcium Chlorate 657
Calcium Chloride Dilute 661
Calcium Chloride (Sat.) 665
Calcium Fluoride 669
Calcium Hydroxide 10% 673
Calcium Hydroxide 20% 677
Calcium Hydroxide 30% 681
Calcium Hydroxide (Sat.) 685

Calcium Hypochlorite 30% 689
Calcium Hypochlorite (Sat.) 693
Calcium Nitrate 697
Calcium Oxide 701
Calcium Sulfate 705
Calcium Sulfide 709
Camphor 713
Cane Sugar Liquors 717
Caprylic Acid 721
Carbitol 725
Carbon Bisulfide (Disulfide) 729
Carbon Dioxide Dry 733
Carbon Dioxide Wet 737
Carbon Disulfide (Bisulfide) 741
Carbon Monoxide 745
Carbon Tetrachloride 749
Carbonated Water 753
Carbonic Acid 757
Castor Oil 761
Caustic Potash (Potassium Hydroxide) 765
Cellosolve 769
Cellulose Acetate 773
China Wood Oil 777
Chloral Hydrate 781
Chloramine Dilute 785
Chloric Acid 10% 789
Chloric Acid 20% 793
Chlorine Dioxide 15% 797
Chlorine Gas Dry 801
Chlorine Gas Wet 805
Chlorine Liquid 809
Chlorine Water (Sat.) 813
Chloroacetic Acid 817
Chloroacetic Acid, 50% Water 821
Chloroacetyl Chloride 825
Chlorobenzene (Phenylchloride) 829
Chlorobenzyl Chloride 833
2-Chloroethanol 837
Chloroform 841
Chlorophenol, 5% Aqueous 845
Chloropicrin 849
Chlorosulfonic Acid 100% 853
Chrome Alum 857
Chromic Acid 10% 861
Chromic Acid 30% 865
Chromic Acid 40% 869

Part B, CHR–IOD
Chromic Acid 50% 873
Chromium Potassium Sulfate 877

Chromyl Chloride 881
Cider 885
Citric Acid 5% 889
Citric Acid 10% 893
Citric Acid 15% 897
Citric Acid (Conc.) 901
Clorox Bleach Solution, 5.5% Chlorine 905
Coal Gas 909
Coal Tar 913
Coco Cola Syrup 917
Coconut Oil 921
Coffee 925
Coke Oven Gas 929
Copper Acetate 933
Copper Carbonate 937
Copper Chloride 941
Copper Cyanide 945
Copper Fluoride 949
Copper Nitrate 953
Copper Sulfate 957
Corn Oil 961
Cottonseed Oil 965
Creosote 969
Cresol 973
Cresylic Acid 50% 977
Cresylic Acid (Conc.) 981
Croton Aldehyde 985
Crude Oil 989
Cumene 993
Cupric Chloride 5% 997
Cupric Chloride 50% 1001
Cupric Cyanide 1005
Cupric Fluoride 1009
Cupric Nitrate 1013
Cupric Sulfate 1017
Cuprous Chloride 1021
Cyanoacetic Acid 1025
Cyanogen Gas 1029
Cyclohexane 1033
Cyclohexanol 1037
Cyclohexanone 1041

D

DDT (Dichlorodiphenyl–Trichloroethane) 1045
Detergents 1049
Detergent Solution, Heavy Duty 1053
Dextrin 1057
Dextrose 1061
Diacetone Alcohol 1065

Diammonium Phosphate 1069
Diamylamine 1073
Diazo Salts 1077
Dibenzyl Ether 1081
Dibutyl Ether 1085
Dibutyl Phthalate 1089
Dichloroacetic Acid 1093
Dichlorobenzene 1097
Dichloroethane (Ethylene Dichloride) 1101
Dichloroethylene 1105
Diesel Fuels 1109
Diethanolamine 1113
Diethylamine 1117
Diethyl Benzene 1121
Diethyl Cellosolve 1125
Diethyl Ether 1129
Diethylene Glycol 1133
Diethylene Triamine 1137
Diglycolic Acid 1141
Dimethylamine 1145
Dimethylamine Aqueous 1149
Dimethyl Aniline 1153
Dimethyl Ether 1157
Dimethyl Formamide 1161
Dimethyl Phthalate 1165
Dimethyl Sulfoxide 1169
Dinitrochlorobenzol, Melted 1173
Dioctyl Phthalate 1177
Dioctyl Sebacate 1181
Dioxane 1185
Dipentene 1189
Diphenyl (Dowtherm) 1193
Diphenyl Oxide 1197
Disodium Phosphate 1201

E

Epichlorhydrin 1205
Esters, General 1209
Ethane 1213
Ethanolamine 1217
Ethers, General 1221
Ethyl Acetate 1225
Ethyl Acetoacetate 1229
Ethyl Acrylate 1233
Ethyl Alcohol 1237
Ethyl Benzene 1241
Ethyl Butyrate 1245
Ethyl Chloride 1249
Ethyl Chloroacetate 1253

Ethyl Ether 1257
Ethyl Formate 1261
2-Ethyl Hexanol 1265
Ethyl Mercaptan 1269
Ethyl Oxalate 1273
Ethylene Bromide 1277
Ethylene Chloride 1281
Ethylene Chlorohydrin 1285
Ethylene, Dry 1289
Ethylene Diamine 1293
Ethylene Dibromide 1297
Ethylene Dichloride (Dichloroethane) 1301
Ethylene Glycol 1305
Ethylene Oxide 1309

F
Fatty Acids 1313
Ferric Acetate 1317
Ferric Chloride 1321
Ferric Chloride 50% in Water 1325
Ferric Hydroxide 1329
Ferric Nitrate 10–50% 1333
Ferric Nitrate (Sat.) 1337
Ferric Sulfate 1341
Ferrous Ammonium Citrate 1345
Ferrous Chloride (Sat.) 1349
Ferrous Hydroxide 1353
Ferrous Nitrate 1357
Ferrous Sulfate 1361
Fish Oil 1365
Fish Solubles 1369
Flue Gas 1373
Fluoboric Acid 1377
Fluorine Gas Dry 1381
Fluorine Gas Moist 1385
Fluosilicic Acid 50% 1389
Fluosilicic Acid 1393
Formaldehyde Dilute 1397
Formaldehyde 35% Solution 1401
Formaldehyde 37% Solution 1405
Formaldehyde 50% Solution 1409
Formic Acid 5% 1413
Formic Acid 10–85% 1417
Formic Acid Anhydrous 1421
Freon F-11 1425
Freon F-12 1429
Freon 17 1433
Freon F-21 1437
Freon F-22 1441

Freon F-113 1445
Fructose 1449
Fruit Juices, Pulp 1453
Fuel Oil 1457
Furfural 1461

G

Gallic Acid 1465
Gas, Manufactured 1469
Gas, Natural 1473
Gasohol 1477
Gasoline, Leaded 1481
Gasoline, Refined 1485
Gasoline, Sour 1489
Gasoline, Unleaded 1493
Gelatin 1497
Gin 1501
Glauber's Salt 1505
Glucose (Corn Syrup) 1509
Glue 1513
Glutamic Acid 1517
Glycerine (Glycerol) 1521
Glycolic Acid 1525
Glycols 1529
Green Liquor 1533

H

Helium 1537
Heptane 1541
Hexamethylene Tetramine 1545
Hexamine 1549
Hexane 1553
Hexanol, Tertiary 1557
Hydraulic Fluid (Petroleum) 1561
Hydraulic Fluid (Synthetic) 1565
Hydrazine 1569
Hydrobromic Acid Dilute 1573
Hydrobromic Acid 20% 1577
Hydrobromic Acid 50% 1581
Hydrochloric Acid Dilute 1585
Hydrochloric Acid 20% 1589
Hydrochloric Acid 35% 1593
Hydrochloric Acid 38% 1597
Hydrochloric Acid 50% 1601
Hydrochloric Acid Fumes 1605
Hydrocyanic Acid 10% 1609
Hydrocyanic Acid (Conc.) 1613
Hydrofluoric Acid Dilute 1617
Hydrofluoric Acid 30% 1621

Hydrofluoric Acid 40% 1625
Hydrofluoric Acid 50% 1629
Hydrofluoric Acid 70% 1633
Hydrofluoric Acid 100% 1637
Hydrofluoric Acid Vapors 1641
Hydrofluosilicic Acid 10–50% 1645
Hydrogen 1649
Hydrogen Chloride Gas Dry 1653
Hydrogen Chloride Gas Moist 1657
Hydrogen Cyanide 1661
Hydrogen Fluoride 1665
Hydrogen Iodide 1669
Hydrogen Peroxide Dilute 1673
Hydrogen Peroxide 30% 1677
Hydrogen Peroxide 50% 1681
Hydrogen Peroxide 90% 1685
Hydrogen Phosphide 1689
Hydrogen Sulfide Aqueous Solution 1693
Hydrogen Sulfide Dry 1697
Hydrogen Sulfide Wet 1701
Hydrogen Sulfite 1705
Hydroiodic Acid (49% + 12% Iodine) 1709
Hydroquinone 1713
Hypochlorous Acid 1717

I
Ink 1721
Iodine 1725
Iodine Solution 10% 1729
Iodine Solution (Sat.) 1733
Iodine in Alcohol 1737
Iodoform 1741

Part C, ISO–POT
Isobutane 1745
Isobutyl Alcohol 1749
Isooctane 1753
Isopropyl Acetate 1757
Isopropyl Alcohol 1761
Isopropyl Ether 1765

J
Jet Fuel JP-4 1769
Jet Fuel JP-5 1773

K
Kerosene 1777
Ketchup 1781

Ketones, General 1785
Kraft Liquor 1789

L
Lacquer Thinner 1793
Lactic Acid 5% 1797
Lactic Acid 10% 1801
Lactic Acid 25% 1805
Lactic Acid 80% 1809
Lactic Acid (Conc.) 1813
Lard Oil 1817
Latex 1821
Lauric Acid 1825
Lauryl Chloride 1829
Lead Acetate 1833
Lead Chloride 1837
Lead Nitrate 1841
Lead Sulfate 1845
Lime Slurry 1849
Lime Sulfur 1853
Linoleic Acid 1857
Linseed Oil 1861
Liqueurs 1865
Lithium Bromide 1869
Lithium Chloride 30% 1873
Lithium Hydroxide 10% 1877
LPG Propane 1881
Lubricating Oil 1885

M
Machine Oil 1889
Magnesium Bisulfate 1893
Magnesium Carbonate 1897
Magnesium Chloride 1901
Magnesium Citrate 1905
Magnesium Hydroxide 1909
Magnesium Nitrate 1913
Magnesium Oxide 1917
Magnesium Sulfate 1921
Maleic Acid 1925
Maleic Anhydride 1929
Malic Acid 1933
Manganese Carbonate 1937
Manganese Chloride 1941
Manganese Sulfate 1945
Mercuric Chloride 1949
Mercuric Cyanide 1953
Mercuric Nitrate 1957

Mercurous Nitrate 1961
Mercury 1965
Methane 1969
Methane Sulfonic Acid 50% 1973
Methyl Acetate 1977
Methyl Acetone 1981
Methyl Acrylate 1985
Methyl Alcohol 1989
Methyl Amine 1993
Methyl Bromide 1997
Methyl Cellosolve 2001
Methyl Chloride 2005
Methyl Chloroform 2009
Methyl Ethyl Ketone 2013
Methyl Formate 2017
Methyl Isobutyl Carbinol 2021
Methyl Isobutyl Ketone 2025
Methyl Methacrylate 2029
Methyl Salicylate 2033
Methyl Sulfate 2037
Methyl Sulfuric Acid 2041
Methylene Chloride 2045
Methylene Chlorobromide 2049
Milk 2053
Mineral Oil 2057
Mineral Spirits 2061
Mixed Acids 2065
Molasses 2069
Molybdic Acid 5% 2073
Monochloroacetic Acid 2077
Monochlorobenzene 2081
Monochlorodifluoromethane 2085
Monoethanolamine 2089
Morpholine 2093
Motor Oil 2097
Muriatic Acid 2101
Mustard 2105

N

Naphtha 2109
Naphthalene 2113
Naphthalenic Acid 2117
Nickel Acetate 2121
Nickel Ammonium Sulfate 2125
Nickel Chloride 2129
Nickel Nitrate 2133
Nickel Salt 2137
Nickel Sulfate 2141

Nicotine 2145
Nicotinic Acid 2149
Nitric Acid 5% 2153
Nitric Acid 10% 2157
Nitric Acid 20% 2161
Nitric Acid 30% 2165
Nitric Acid 40% 2169
Nitric Acid 50% 2173
Nitric Acid 70% 2177
Nitric Acid 100% (Anhydrous) 2181
Nitric Acid Fuming (Red) 2185
Nitric Acid:Sulfuric Acid 50:50 2189
Nitriding Gases 2193
Nitrobenzene 2197
Nitrogen 2201
Nitrogen Dioxide 2205
Nitromethane 2209
Nitrous Acid 5% 2213
Nitrous Acid 10% 2217
Nitrous Acid (Conc.) 2221
Nitrous Oxide 2225

O

Ocenol 2229
Octane 2233
Oil and Fats 2237
Oil, Mineral 2241
Oils, Vegetable 2245
Oleic Acid 2249
Oleum 2253
Olive Oil 2257
Oxalic Acid 5% 2261
Oxalic Acid 10% 2265
Oxalic Acid 50% 2269
Oxalic Acid (Sat.) 2273
Oxygen 2277
Oxygen Gas 2281
Ozone 2285

P

Palmitic Acid 10% 2289
Palmitic Acid 70% 2293
Palmitic Acid (Conc.) 2297
Paper Pulp (Chlorinated) 2301
Paper Pulp (Nonchlorinated) 2305
Paraffin 2309
Peanut Oil 2313
Pentane 2317
Peracetic Acid 40% 2321

Perchloric Acid 10% 2325
Perchloric Acid 70% 2329
Perchloroethylene 2333
Petrolatum 2337
Petroleum Ether 2341
Petroleum Oils, Refined 2345
Petroleum Oils, Sour 2349
Phenol (Carbolic Acid) 2353
Phenol 10% 2357
Phenol Sulfonic Acid 2361
Phenylhydrazine 2365
Phenylhydrazine Hydrochloride 2369
Phosgene Gas 2373
Phosgene Liquid 2377
Phosphoric Acid 5% 2381
Phosphoric Acid 10% 2385
Phosphoric Acid 25–50% 2389
Phosphoric Acid 50–85% 2393
Phosphoric Anhydride (Dry or Moist) 2397
Phosphorus 2401
Phosphorus Oxychloride 2405
Phosphorus Pentachloride 2409
Phosphorus Pentoxide 2413
Phosphorus Red 2417
Phosphorus Trichloride 2421
Phosphorus Yellow 2425
Photographic Solutions 2429
Phthalic Acid 2433
Phthalic Anhydride 2437
Picric Acid 2441
Picric Acid 10% 2445
Pine Oil 2449
Plating Solutions, Brass 2453
Plating Solutions, Cadmium 2457
Plating Solutions, Chrome 25% 2461
Plating Solutions, Chrome 40% 2465
Plating Solutions, Copper (Cyanide) 2469
Plating Solutions, Gold 2473
Plating Solutions, Iron 2477
Plating Solutions, Lead 2481
Plating Solutions, Nickel 2485
Plating Solutions, Rhodium 2489
Plating Solutions, Silver 2493
Plating Solutions, Tin 2497
Plating Solutions, Zinc 2501
Polysulfide Liquor 2505
Polyvinyl Acetate 2509
Potassium Acetate 2513
Potassium Aluminum Sulfate 2517
Potassium Bicarbonate 30% 2521

Potassium Bicarbonate (Sat.) 2525
Potassium Bichromate 2529
Potassium Bisulfate 2533
Potassium Borate 2537
Potassium Bromate 2541
Potassium Bromide 30% 2545
Potassium Bromide (Sat.) 2549
Potassium Carbonate 50% 2553
Potassium Chlorate, Aqueous 30% 2557
Potassium Chloride 30% 2561
Potassium Chromate 30% 2565
Potassium Cyanide 30% 2569
Potassium Dichromate 30% 2573
Potassium Dichromate (Sat.) 2577
Potassium Ferricyanide 30% 2581
Potassium Ferrocyanide 30% 2585
Potassium Fluoride 2589
Potassium Hydroxide 5% 2593
Potassium Hydroxide 27% 2597
Potassium Hydroxide 50% 2601
Potassium Hydroxide 90% 2605
Potassium Hypochloride 2609
Potassium Hypochlorite 2613
Potassium Iodide 70% 2617
Potassium Nitrate 1–5% 2621

Part D, POT–ZIN

Potassium Nitrate 80% 2625
Potassium Nitrite 2629
Potassium Oxalate 20% 2633
Potassium Perborate 2637
Potassium Perchlorate 2641
Potassium Permanganate 10% 2645
Potassium Permanganate 20% 2649
Potassium Peroxide 2653
Potassium Persulfate 2657
Potassium Phosphate 2661
Potassium Sulfate 10% 2665
Potassium Sulfate, Pure 2669
Potassium Sulfide 2673
Potassium Sulfite 2677
Potassium Triphosphate 2681
Propane 2685
Propargyl Alcohol 2689
Propionic Acid 2693
Propyl Acetate 2697
Propyl Alcohol 2701
Propyl Nitrate 2705
Propylene Dichloride 2709

Propylene Glycol 2713
Propylene Oxide 2717
Pyridine 2721
Pyrogallic Acid 2725
Pyrogallol 2729
Pyroligneous Acid 2733

Q

Quinine Bisulfate 2737
Quinine Sulfate 2741
Quinone 2745

R

Rayon Coagulating Bath 2749
Resorcinol 2753
Road Oil 2757
Rosin, Dark 2761
Rosin, Light 2765
Rosin, Molten 2769
Rosin Oil 2773

S

Salenic Acid Aqueous 2777
Salicic Acid 2781
Salicylaldehyde 2785
Salicylic Acid 2789
Sea Water 2793
Selenius Acid, 30% 2797
Shellac 2801
Silicone Oil 2805
Silver Bromide 10% 2809
Silver Chloride 2813
Silver Cyanide 2817
Silver Nitrate 2821
Soaps 2825
Soap Solution 5% 2829
Soap Solutions 2833
Sodium Acetate 2837
Sodium Acid Sulfate 2841
Sodium Aluminate 2845
Sodium Benzoate 2849
Sodium Bicarbonate 20% 2853
Sodium Bichromate Neutral 2857
Sodium Bisulfate 2861
Sodium Bisulfite 2865
Sodium Borate 2869
Sodium Bromide 2873

Sodium Carbonate	2877
Sodium Chlorate	2881
Sodium Chloride	2885
Sodium Chlorite	2889
Sodium Chromate 80%	2893
Sodium Citrate	2897
Sodium Cyanide	2901
Sodium Dichromate	2905
Sodium Ferricyanide	2909
Sodium Ferrocyanide	2913
Sodium Fluoride	2917
Sodium Hydrosulfide	2921
Sodium Hydrosulfite	2925
Sodium Hydroxide 10%	2929
Sodium Hydroxide 15%	2933
Sodium Hydroxide 30%	2937
Sodium Hydroxide 50%	2941
Sodium Hydroxide 70%	2945
Sodium Hydroxide Solution (Conc.)	2949
Sodium Hypochlorite 20%	2953
Sodium Hypochlorite (Conc.)	2957
Sodium Hyposulfite 5%	2961
Sodium Iodide	2965
Sodium Lactate	2969
Sodium Metaphosphate	2973
Sodium Metasilicate	2977
Sodium Nitrate	2981
Sodium Nitrite	2985
Sodium Perborate 10%	2989
Sodium Peroxide 10%	2993
Sodium Phosphate Acid	2997
Sodium Phosphate Alkaline	3001
Sodium Phosphate Neutral	3005
Sodium Silicate	3009
Sodium Sulfate	3013
Sodium Sulfide to 50%	3017
Sodium Sulfite 10%	3021
Sodium Tetraborate	3025
Sodium Thiosulfate (Hypo)	3029
Sour Crude Oil	3033
Soybean Oil	3037
Speculum Plating Solution	3041
Stannic Chloride	3045
Stannous Chloride	3049
Stannous Fluoride	3053
Starch	3057
Steam, High Pressure	3061
Steam, Low Pressure	3065
Steam, Medium Pressure	3069
Stearic Acid	3073

Stoddard's Solvent 3077
Styrene 3081
Succinic Acid 3085
Sugar Solution 3089
Sulfamic Acid 3093
Sulfate Liquors 3097
Sulfite Liquors 3101
Sulfonated Detergents 3105
Sulfur 3109
Sulfur Chloride 3113
Sulfur Dichloride 3117
Sulfur Dioxide Dry 3121
Sulfur Dioxide Wet 3125
Sulfur Oxychloride 3129
Sulfur Trioxide 3133
Sulfuric Acid 10% 3137
Sulfuric Acid 30% 3141
Sulfuric Acid 50% 3145
Sulfuric Acid 60% 3149
Sulfuric Acid 70% 3153
Sulfuric Acid 80% 3157
Sulfuric Acid 90% 3161
Sulfuric Acid 95% 3165
Sulfuric Acid 98% 3169
Sulfuric Acid 100% 3173
Sulfuric Acid 103% 3177
Sulfuric Acid Fuming 3181
Sulfuric Acid Vapors 3185
Sulfuric Anhydride Dry 3189
Sulfurous Acid 3193
Sulfuryl Chloride 3197

T

Tall Oil 3201
Tannic Acid 3205
Tanning Liquors 3209
Tar 3213
Tartaric Acid 3217
Tetrachloroacetic Acid 3221
Tetrachloroethane 3225
Tetrachloroethylene 3229
Tetraethyl Lead 3233
Tetrahydrofuran 3237
Tetralin 3241
Tetramethyl Ammonium Hydroxide 50% 3245
Tetraphosphoric Acid 3249
Thionyl Chloride 3253
Thread Cutting Oil 3257
Tin Chloride 3261

Tin (Molten) 3265
Tin Tetrachloride 3269
Titanium Tetrachloride 3273
Toluene (Toluol) 3277
Toluene-Kerosene 25–75% 3281
Tomato Juice 3285
Toxaphene-Xylene 10–90% 3289
Transformer Oil 3293
Transformer Oil DTE/30 3297
Tributyl Phosphate 3301
Trichloroacetic Acid 3305
Trichloroacetic Acid 2N 3309
Trichloroethane 3313
Trichloroethylene 3317
Trichloropropane 3321
Tricresylphosphate 3325
Triethanolamine 3329
Triethylamine 3333
Triethyl Phosphate 3337
Triethyl Phosphite 3341
Trimethyl Propane 3345
Trisodium Phosphate 3349
Tung Oil 3353
Turpentine 3357

U

Udecyl Alcohol 3361
Uranyl Sulfate 5% 3365
Urea 3369
Urea Ammonium Liquor 3373
Uric Acid (Conc.) 3377
Urine 3381

V

Vanadium Pentaoxide 3385
Varnish 3389
Vegetable Oil 3393
Vinegar 3397
Vinyl Acetate 3401
Vinyl Chloride 3405
Vinyl Chloride (Resin) 3409
Vinylidine Chloride Resin 3413

W


Water, Acid Mine 3417
Water, Demineralized 3421
Water, Distilled 3425
Water, Potable 3429
Water, Salt 3433

Water, Sea 3437
Water, Sewage 3441
Whiskey 3445
White Liquor 3449
Wines 3453

X
Xylene (Xylol) 3457

Z
Zinc Carbonate 3461
Zinc Chloride 3465
Zinc Cyanide 3469
Zinc Hydrosulfite 3473
Zinc Nitrate 3477
Zinc Sulfate 5% 3481
Zinc Sulfate 25% 3485
Zinc Sulfate 50% 3489
Zinc Sulfate (Sat.) 3493

Appendix 1: Chemical Synonyms *A-1-1*
Appendix 2: Cross-Reference of Trade Names to Generic Names *A-2-1*
Appendix 3: Plating Solution Composition *A-3-1*



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028966

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM NITRATE 80%




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM NITRATE 80%



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2	U																										
Hastelloy C/C-276	G																										
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400	G																										
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347	G																										
Type 316/316 L	G																										
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3	G																										
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium	G																										
Zirconium	G																										
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028967

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM NITRITE

	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM NITRITE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


POTASSIUM NITRITE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)																					
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)																					
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM OXALATE 20%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028968

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM OXALATE 20%

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate		R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
Sodium Silicate																						
Potassium Silicate		R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
Silica		R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
Sulfur		R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
Furan Resin		R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM OXALATE 20%

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy	R																					
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)	R																					
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)	R																					
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester	ALL R																					
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM OXALATE 20%

Elastomers* and Linings	°C / °F	15 / 60	26 / 80	38 / 100	49 / 120	60 / 140	71 / 160	82 / 180	93 / 200	104 / 220	116 / 240	127 / 260	138 / 280	149 / 300	160 / 320	171 / 340	182 / 360	193 / 380	204 / 400	216 / 420	227 / 440	238 / 460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)		R	R	R	R	R	R	R	R													
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)		R	R	R	R	R	R	R	R													
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F / °C	60 / 15	80 / 26	100 / 38	120 / 49	140 / 60	160 / 71	180 / 82	200 / 93	220 / 104	240 / 116	260 / 127	280 / 138	300 / 149	320 / 160	340 / 171	360 / 182	380 / 193	400 / 204	420 / 216	440 / 227	460 / 238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028969

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


POTASSIUM PERBORATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERBORATE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERBORATE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028970

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


POTASSIUM PERCHLORATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERCHLORATE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERCHLORATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERMANGANATE 10%

Metals		°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293
		°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560
Admiralty Brass		
Aluminum		E
Aluminum Bronze		
Brass		G
Bronze		G
Carbon Steel		G
Columbium (Niobium)		
Copper		G
Hastelloy B/B-2		U
Hastelloy C/C-276		E G
Hastelloy D		U
Hastelloy G/G-3		
High Silicon Iron		G
Inconel 600/625		G
Incolloy 800/825		
Lead		U
Monel 400		G
Naval Bronze		G
Nickel 200/201		G
Ni-Resist	5%	G
Stainless Steels		
Type 304/347		G
Type 316/316 L		G
Type 400 series		G
Type 904-L		
17-4 PH		G
20 Cb 3		G
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		G
Tantalum		G
Titanium		G
Zirconium		
		°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560
		°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028971

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERMANGANATE 10%




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


POTASSIUM PERMANGANATE 10%



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERMANGANATE 20%




FOR METALS
E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year
S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS
R = Resistant
U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028972
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERMANGANATE 20%




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERMANGANATE 20%




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERMANGANATE 20%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

= < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

= < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

led
m.

Corrosion Resistance Tables: Fifth Edition, Revised and Expanded DOI: 10.1081/5672-X-120028973

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PEROXIDE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate	U																					
Silica	U																					
Sulfur	U																					
Furan Resin	U																					
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PEROXIDE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PEROXIDE

Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)	R	
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)		
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERSULFATE

Metals	°C	°F
Admiralty Brass		
Aluminum		
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper		
Hastelloy B/B-2		
Hastelloy C/C-276 4%	E	
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825		
Galv. Stl.	U	
Monel 400		
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347		
Type 316/316 L	G	
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3		
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		
Tantalum		
Titanium		
Zirconium		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028974


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERSULFATE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PERSULFATE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


POTASSIUM PERSULFATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PHOSPHATE



FOR METALS
E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year
S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS
R = Resistant
U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028975
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PHOSPHATE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PHOSPHATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM PHOSPHATE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)		R																				
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		R																				
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)		U																				
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)		U																				
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)		R																				
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)	Acid	R																				
Nitrile Buna-N (NBR)		U																				
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFATE 10%


Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			E																									
Aluminum			E																									
Aluminum Bronze			E																									
Brass			G																									
Bronze			G																									
Carbon Steel			G																									
Columbium (Niobium)			E																									
Copper	1–5%		G																									
Hastelloy B/B-2			E																									
Hastelloy C/C-276			E																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron			E																									
Inconel 600/625			E	G																								
Incolloy 800/825	1–5%		G																									
Lead			G																									
Monel 400			E																									
Naval Bronze			G																									
Nickel 200/201			E																									
Ni-Resist			G																									
Stainless Steels																												
Type 304/347			E																									
Type 316/316 L			E																									
Type 400 series			G																									
Type 904-L																												
17-4 PH			G																									
20 Cb 3			E																									
E-Bright 26-1																												
Silicon Bronze	1–5%		G																									
Silicon Copper			E																									
Stellite			G																									
Tantalum			E																									
Titanium			E																									
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS
E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year
S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS
R = Resistant
U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028976
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFATE 10%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFATE 10%

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		R																				
Acetal																						
Acrylics		R																				
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)		R																				
CPVC		R																				
E-CTFE (Halar)		R																				
Epoxy		R																				
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)		R																				
Noryl		R																				
Nylon 6		R																				
Nylon 11		R																				
Nylon 66		R																				
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate		R																				
Halogenated		R																				
Hydrogenated Bisphenol A –Bisphenol A		R																				
Isophthalic		R																				
Terephthalate (PET)		R																				
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)		R																				
Polyethersulfone (PES)																						
Polyethylene HMW		R																				
Polyethylene UHMW		R																				
Polymethylpentene																						
Polypropylene (PP)		R																				
Polystyrene		R																				
Polysulfone		R																				
Polyvinylidene Chloride		R																				
PVC Type 1		R																				
PVC Type 2		R																				
PVDF (Kynar)		R																				
Ryton	ALL	R																				
TFE (Teflon)		R																				
Vinyl Ester	ALL	R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


POTASSIUM SULFATE 10%



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFATE, PURE



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028977


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFATE, PURE




Schweitzer/ *Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFATE, PURE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFATE, PURE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028978

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFIDE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/Corrosion Resistance Tables: Fifth Edition, Revised and Expanded
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFIDE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFITE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel		U																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276		E																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Galv. Stl.		U																									
Monel 400		G																									
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		G																									
Type 316/316 L		G																									
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3		G																									
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028979

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFITE


Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM SULFITE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM TRIPHOSPHATE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		U																									
Aluminum Bronze		G																									
Brass																											
Bronze																											
Carbon Steel		G																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L		G																									
Type 400 series		E																									
Type 904-L																											
17-4 PH																											
20 Cb 3		G																									
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028980

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM TRIPHOSPHATE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM TRIPHOSPHATE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC	R	—	—	—	—	—	—	—														
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R	—	—	—	—	—	—	—	—	—	—	—	—	—								
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	*71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

POTASSIUM TRIPHOSPHATE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)	R																					
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)	R																					
Nitrile Buna-N (NBR)	R																					
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028981

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPANE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPANE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G																									
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum		G																									
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028982

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPARGYL ALCOHOL

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		R																				
Silicones																						
Urethanes																						
Vinyls		R																				
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPARGYL ALCOHOL

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		U																				
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC		R																				
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		R																				
Polyethylene UHMW		R																				
Polymethylpentene																						
Polypropylene (PP)		U																				
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1		R																				
PVC Type 2		R																				
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


PROPARGYL ALCOHOL

Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)		
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R	
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)	R	
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)		
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)	U	
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028983

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPIONIC ACID



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS			U																				
Acetal																							
Acrylics																							
Asbestos Reinforced Epoxy																							
Asbestos Reinforced Phenolic																							
Chlorinated Polyether (Penton)																							
CPVC			R																				
E-CTFE (Halar)																							
Epoxy																							
ETFE (Tefzel)			R																				
FEP			R																				
Furan (Furfural Alcohol)			R																				
Noryl																							
Nylon 6			R																				
Nylon 11																							
Nylon 66			R																				
Phenolic			R																				
PFA (Teflon)																							
Polyamide-Imide																							
Polyesters																							
Bisphenol A–fumarate	1%		R																				
Halogenated	1%		R																				
Hydrogenated Bisphenol A –Bisphenol A																							
Isophthalic	1%		R																				
Terephthalate (PET)			R																				
Polyetherimide (ULTEM)																							
Polyetheretherketone (PEEK)																							
Polyethersulfone (PES)																							
Polyethylene HMW																							
Polyethylene UHMW	50%		R																				
Polymethylpentene																							
Polypropylene (PP)			R																				
Polystyrene																							
Polysulfone																							
Polyvinylidene Chloride																							
PVC Type 1			R																				
PVC Type 2			R																				
PVDF (Kynar)			R																				
Ryton																							
TFE (Teflon)			R																				
Vinyl Ester	50%		R																				
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPIONIC ACID

Elastomers* and Linings	°C	°F
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)	R	
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)	R	
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)		
Hard Rubber TO 50%	R	
Soft Rubber	U	
Isoprene (IR)		
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)	U	
Nitrile Buna-N (NBR)	R	
Nordel (EPDM)	R	
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		


°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028984

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


PROPYL ACETATE

Nonmetallic Materials	
Borosilicate Glass	R
Carbon	R
Carbon-Graphite Resin Impregnated	R
Ceramics	
Coatings	
Acrylic	
Asphalt	
Chlorinated Rubber	
Coal Tar	
Coal Tar Epoxy	U
Epoxy General Purpose	
Epoxy Chemical Resistant	
Epoxy Polyamide	U
Oil Base (Alkyd, Epoxy, Urethane)	
Phenolic	
Polyester	U
Polyvinyl Chloride	U
Silicones	
Urethanes	
Vinyls	U
Water Base	
Zinc Rich	
Mortars	
Silicate	
Sodium Silicate	R
Potassium Silicate	
Silica	
Sulfur	U
Furan Resin	R
Polyester	U
Epoxy	U

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYL ACETATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYL ACETATE

Elastomers* and Linings	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	R																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	U																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)	U																				
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYL ALCOHOL

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G																									
Aluminum Bronze		G																									
Brass		G																									
Bronze		G																									
Carbon Steel		G																									
Galv. Stl.		G																									
Copper		G																									
Hastelloy B/B-2		E																									
Hastelloy C/C-276		E																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625		E																									
Incolloy 800/825		E																									
Lead		G																									
Monel 400		G																									
Naval Bronze		E																									
Nickel 200/201		E																									
Ni-Resist		E																									
Stainless Steels																											
Type 304/347		E																									
Type 316/316 L		E																									
Type 400 series		E																									
Type 904-L																											
17-4 PH		G																									
20 Cb 3		E																									
E-Bright 26-1																											
Silicon Bronze		G																									
Silicon Copper		E																									
Stellite		G																									
Tantalum		G																									
Titanium		E																									
Zirconium		E																									
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028985

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYL ALCOHOL



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYL ALCOHOL


Plastics	
ABS	U
Acetal	
Acrylics	
Asbestos Reinforced Epoxy	
Asbestos Reinforced Phenolic	
Chlorinated Polyether (Penton)	R
CPVC	U
E-CTFE (Halar)	R
Epoxy	R
ETFE (Tefzel)	R
FEP	R
Furan (Furfural Alcohol)	
Noryl	R
Nylon 6	U
Nylon 11	U
Nylon 66	U
Phenolic	
PFA (Teflon)	R
Polyamide-Imide	
Polyesters	
Bisphenol A–fumarate	
Halogenated	
Hydrogenated Bisphenol A –Bisphenol A	
Isophthalic	
Terephthalate (PET)	R
Polyetherimide (ULTEM)	
Polyetheretherketone (PEEK)	R
Polyethersulfone (PES)	
Polyethylene HMW	R
Polyethylene UHMW	R
Polymethylpentene	
Polypropylene (PP)	R
Polystyrene	
Polysulfone	R
Polyvinylidene Chloride	R
PVC Type 1	R
PVC Type 2	R
PVDF (Kynar)	R
Ryton	
TFE (Teflon)	R
Vinyl Ester	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYL ALCOHOL



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	°F
Admiralty Brass		
Aluminum		
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper		
Hastelloy B/B-2		
Hastelloy C/C-276		
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825		
Lead		
Monel 400		
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347		
Type 316/316 L	G	
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3	G	
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		
Tantalum		
Titanium		
Zirconium		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028986

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYL NITRATE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYL NITRATE

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP		
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)		
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYL NITRATE

Elastomers* and Linings	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	R																				
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	U																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE DICHLORIDE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel		G																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400		G																									
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		G																									
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028987

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE DICHLORIDE

Nonmetallic Materials	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Borosilicate Glass	R																				
Carbon																					
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride	U																				
Silicones																					
Urethanes																					
Vinyls	U																				
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE DICHLORIDE

Plastics	°C	°F
ABS	U	
Acetal		
Acrylics	U	
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)	R	
CPVC	U	
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	U	
Polyethylene UHMW	U	
Polymethylpentene		
Polypropylene (PP)	U	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride	R	
PVC Type 1	U	
PVC Type 2	U	
PVDF (Kynar)	R	
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE DICHLORIDE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	U																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028988

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE GLYCOL




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE GLYCOL

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		R																				
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC		U																				
E-CTFE (Halar)																						
Epoxy		R								U												
ETFE (Tefzel)																						
FEP		R																				
Furan (Furfural Alcohol)		R																				
Noryl																						
Nylon 6		R																				
Nylon 11																						
Nylon 66		R																				
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate		R																				
Halogenated		R																				
Hydrogenated Bisphenol A –Bisphenol A		R																				
Isophthalic		R																				
Terephthalate (PET)		R																				
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		R																				
Polyethylene UHMW		R																				
Polymethylpentene		R																				
Polypropylene (PP)		R																				
Polystyrene																						
Polysulfone		R																				
Polyvinylidene Chloride																						
PVC Type 1		U																				
PVC Type 2		U																				
PVDF (Kynar)		R																				
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE GLYCOL



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE OXIDE

Metals	°C	°F
Admiralty Brass		
Aluminum		
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel	G	
Columbium (Niobium)		
Copper		
Hastelloy B/B-2		
Hastelloy C/C-276		
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825		
Lead		
Monel 400		
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347 90%	E	
Type 316/316 L 90%	E	
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3	G	
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		
Tantalum	G	
Titanium		
Zirconium		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028989

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE OXIDE

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon																					
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride	U																				
Silicones	U																				
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich	R																				
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE OXIDE

Plastics		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																							
Acetal																							
Acrylics																							
Asbestos Reinforced Epoxy																							
Asbestos Reinforced Phenolic																							
Chlorinated Polyether (Penton)																							
CPVC			U																				
E-CTFE (Halar)			U																				
Epoxy																							
ETFE (Tefzel)			R																				
FEP	14		R																				
Furan (Furfural Alcohol)																							
Noryl																							
Nylon 6																							
Nylon 11																							
Nylon 66																							
Phenolic																							
PFA (Teflon)			R																				
Polyamide-Imide																							
Polyesters																							
Bisphenol A–fumarate																							
Halogenated																							
Hydrogenated Bisphenol A –Bisphenol A																							
Isophthalic																							
Terephthalate (PET)																							
Polyetherimide (ULTEM)																							
Polyetheretherketone (PEEK)																							
Polyethersulfone (PES)																							
Polyethylene HMW			R																				
Polyethylene UHMW																							
Polymethylpentene			R																				
Polypropylene (PP)			R																				
Polystyrene																							
Polysulfone			R																				
Polyvinylidene Chloride			R																				
PVC Type 1			U																				
PVC Type 2			U																				
PVDF (Kynar)			U																				
Ryton																							
TFE (Teflon)	14		R																				
Vinyl Ester			U																				
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PROPYLENE OXIDE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYRIDINE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum			G																									
Aluminum Bronze																												
Brass			G																									
Bronze			G																									
Carbon Steel			G																									
Columbium (Niobium)			E																									
Copper			G																									
Hastelloy B/B-2			G																									
Hastelloy C/C-276	50%		E																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625	1		G																									
Incolloy 800/825																												
Lead			G																									
Monel 400			G																									
Naval Bronze																												
Nickel 200/201			G																									
Ni-Resist																												
Stainless Steels																												
Type 304/347			G																									
Type 316/316 L			G																									
Type 400 series																												
Type 904-L																												
17-4 PH																												
20 Cb 3			G																									
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum			G																									
Titanium			G																									
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028990

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYRIDINE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)	R	
CPVC	U	
E-CTFE (Halar)	U	
Epoxy	U	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)	U	
Noryl	R	U
Nylon 6	R	U
Nylon 11	R	U
Nylon 66	R	U
Phenolic	U	
PFA (Teflon)	R	
Polyamide-Imide	U	
Polyesters		
Bisphenol A–fumarate	U	
Halogenated	U	
Hydrogenated Bisphenol A –Bisphenol A	U	
Isophthalic	U	
Terephthalate (PET)	R	
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	R	
Polyethylene UHMW	R	
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone	U	
Polyvinylidene Chloride		
PVC Type 1	U	
PVC Type 2	U	
PVDF (Kynar)	U	
Ryton	R	
TFE (Teflon)	R	
Vinyl Ester	U	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYRIDINE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	R																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	U																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal	U																				
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)	U																				
Polybutadiene (BR)																					
Polyester (PE)	U																				
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)	U																				
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	°F
Admiralty Brass		
Aluminum	G	
Aluminum Bronze		
Brass	G	
Bronze	G	
Carbon Steel	G	
Columbium (Niobium)		
Copper	E	
Hastelloy B/B-2	G	
Hastelloy C/C-276	G	
Hastelloy D	G	
Hastelloy G/G-3		
High Silicon Iron	G	
Inconel 600/625	G	
Incolloy 800/825	E	
Lead		
Monel 400	G	
Naval Bronze	G	
Nickel 200/201	G	
Ni-Resist	U	
Stainless Steels		
Type 304/347	G	
Type 316/316 L	G	
Type 400 series	G	
Type 904-L		
17-4 PH	G	
20 Cb 3 60%	G	
E-Bright 26-1		
Silicon Bronze	G	
Silicon Copper	E	
Stellite	G	
Tantalum	G	
Titanium	E	
Zirconium		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/Corrosion Resistance Tables: Fifth Edition, Revised and Expanded DOI: 10.1081/5672-X-120028991


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYROGALLIC ACID

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon		R																				
Carbon-Graphite Resin Impregnated		R																				
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYROGALLIC ACID




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYROGALLIC ACID



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028992

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYROGALLOL

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon		R																				
Carbon-Graphite Resin Impregnated		R																				
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)	R	
CPVC		
E-CTFE (Halar)	R	
Epoxy	R	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride	R	
PVC Type 1	R	
PVC Type 2		
PVDF (Kynar)	R	
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYROGALLOL



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals			°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
			°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																													
Aluminum		G																											
Aluminum Bronze																													
Brass																													
Bronze																													
Carbon Steel		U																											
Columbium (Niobium)																													
Copper																													
Hastelloy B/B-2		E																											
Hastelloy C/C-276																													
Hastelloy D																													
Hastelloy G/G-3																													
High Silicon Iron																													
Inconel 600/625																													
Incolloy 800/825																													
Lead																													
Monel 400	10–40%	G																											
Naval Bronze																													
Nickel 200/201																													
Ni-Resist																													
Stainless Steels																													
Type 304/347	10%	E																											
Type 316/316 L	10%	E																											
Type 400 series		E	G																										
Type 904-L																													
17-4 PH																													
20 Cb 3	20%	G																											
E-Bright 26-1																													
Silicon Bronze																													
Silicon Copper																													
Stellite																													
Tantalum																													
Titanium																													
Zirconium																													
			°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
			°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028993

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYROLIGNEOUS ACID

Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Borosilicate Glass		R																				
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYROLIGNEOUS ACID

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)	R																					
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

PYROLIGNEOUS ACID

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)	R																					
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																					
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)	U																					
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)	U																					
Hard Rubber	U																					
Soft Rubber																						
Isoprene (IR)	U																					
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)	U																					
Neoprene GR-M (CR)	U																					
Nitrile Buna-N (NBR)	U																					
Nordel (EPDM)	U																					
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)	U																					
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028994

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

QUINONE BISULFATE

	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)	R																					
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

QUINONE BISULFATE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)																					
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)																					
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028995

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

QUININE SULFÁTE

Nonmetallic Materials
Borosilicate Glass
Carbon
Carbon-Graphite Resin Impregnated
Ceramics
Coatings
Acrylic
Asphalt
Chlorinated Rubber
Coal Tar
Coal Tar Epoxy
Epoxy General Purpose
Epoxy Chemical Resistant
Epoxy Polyamide
Oil Base (Alkyd, Epoxy, Urethane)
Phenolic
Polyester
Polyvinyl Chloride
Silicones
Urethanes
Vinyls
Water Base
Zinc Rich
Mortars
Silicate
Sodium Silicate
Potassium Silicate
Silica
Sulfur
Furan Resin
Polyester
Epoxy

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy	R																					
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)	R																					
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)	R																					
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

QUININE SULFATE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)	R																					
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L	G																										
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3	G																										
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028996

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

QUINONE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)																						
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

QUINONE

Elastomers* and Linings	°C	°F
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)		
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U	
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)	R	
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)	U	
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

RAYON COAGULATING BATH

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum																												
Aluminum Bronze																												
Brass																												
Bronze																												
Carbon Steel																												
Columbium (Niobium)																												
Copper																												
Hastelloy B/B-2			G																									
Hastelloy C/C-276			G																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625																												
Incolloy 800/825																												
Lead																												
Monel 400																												
Naval Bronze																												
Nickel 200/201																												
Ni-Resist																												
Stainless Steels																												
Type 304/347			U																									
Type 316/316 L	1		G																									
Type 400 series																												
Type 904-L																												
17-4 PH																												
20 Cb 3																												
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum																												
Titanium																												
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028997


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

RAYON COAGULATING BATH



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

RAYON COAGULATING BATH

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)	R																					
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028998

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

RESORCINOL

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass		R																				
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	°F
Polycarbonate (PC)	R	U
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl		
Nylon 6	R	
Nylon 11	U	
Nylon 66	R	
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)	R	
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	R	
Polyethylene UHMW	R	
Polymethylpentene	R	
Polypropylene (PP)	R	
Polystyrene		
Polysulfone	U	
Polyvinylidene Chloride		
PVC Type 1	R	
PVC Type 2		
PVDF (Kynar)		
Ryton	R	
TFE (Teflon)	R	
Vinyl Ester	R	

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

RESORCINOL

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)	R																					
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel	G	G	G	G	G																						
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist	G	G	G	G	G																						
Stainless Steels																											
Type 304/347	G	G	G	G	G																						
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028999

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROAD OIL

	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROAD OIL

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)		R																				
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029000

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN, DARK

Nonmetallic Materials	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Borosilicate Glass																					
Carbon	R																				
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride																					
Silicones																					
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP		
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW	R	
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1	U	
PVC Type 2	U	
PVDF (Kynar)		
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN, DARK

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)																					
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)																					
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)																					
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	°F	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
			60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum			G																									
Aluminum Bronze																												
Brass			U																									
Bronze			U																									
Carbon Steel			U																									
Columbium (Niobium)			U																									
Copper			U																									
Hastelloy B/B-2			E																									
Hastelloy C/C-276																												
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625			E																									
Incolloy 800/825																												
Lead																												
Monel 400			G																									
Naval Bronze			U																									
Nickel 200/201			E																									
Ni-Resist																												
Stainless Steels																												
Type 304/347			E			G																						
Type 316			E	G																								
Type 430			G																									
Type 904-L																												
17-4 PH																												
20 Cb 3	60%		E																									
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper			U																									
Stellite			E																									
Tantalum			E																									
Titanium																												
Zirconium																												
	°F		60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C		15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029001

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN, LIGHT

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon		R																				
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Polycarbonate		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP		
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW	R	
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1	U	
PVC Type 2	U	
PVDF (Kynar)		
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN, LIGHT

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)																					
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)																					
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)																					
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass	G																										
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2	E																										
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625	E																										
Incolloy 800/825																											
Lead																											
Monel 400	G																										
Naval Bronze																											
Nickel 200/201	E																										
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316	G																										
Type 400 series																											
Type 317/317 L	G																										
17-4 PH																											
20 Cb 3	G																										
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum	E																										
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029002

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN, MOLTEN

Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated		R																				
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN, MOLTEN

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)	R																					
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN, MOLTEN

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)		R																				
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276	G																										
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400	G																										
Naval Bronze																											
Nickel 200/201																											
Ni-Resist	U																										
Stainless Steels																											
Type 304/347	G																										
Type 316	G																										
Type 400 series																											
Type 317/317 L	G																										
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029003

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN OIL

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN OIL

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

ROSIN OIL

Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)		
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)		
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)		
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)	R	
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALENIC ACID AQUEOUS

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029004


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALENIC ACID AQUEOUS

	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		R																				
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALENIC ACID AQUEOUS



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALENIC ACID AQUEOUS

Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)	R	
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)		
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel		U																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		G																									
Type 316/316 L		G																									
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029005

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SALICIC ACID

Nonmetallic Materials	°C	°F
Borosilicate Glass	R	R
Carbon		
Carbon-Graphite Resin Impregnated		
Ceramics		
Coatings		
Acrylic		
Asphalt		
Chlorinated Rubber		
Coal Tar		
Coal Tar Epoxy		
Epoxy General Purpose		
Epoxy Chemical Resistant		
Epoxy Polyamide		
Oil Base (Alkyd, Epoxy, Urethane)		
Phenolic		
Polyester		
Polyvinyl Chloride	R	R
Silicones		
Urethanes		
Vinyls		
Water Base		
Zinc Rich		
Mortars		
Silicate		
Sodium Silicate		
Potassium Silicate		
Silica		
Sulfur		
Furan Resin		
Polyester		
Epoxy		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALICIC ACID



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALICIC ACID

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)																					
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)	R																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	°F
Admiralty Brass		
Aluminum		
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper		
Hastelloy B/B-2		
Hastelloy C/C-276		
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825		
Lead		
Monel 400		
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347		
Type 316/316 L		
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3		
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		
Tantalum		
Titanium		
Zirconium		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029006

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALICYLALDEHYDE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALICYLALDEHYDE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		U																				
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)		R																				
CPVC		U																				
E-CTFE (Halar)		R	U																			
Epoxy		R																				
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)		R																				
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate		R																				
Halogenated		R																				
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		R																				
Polyethylene UHMW																						
Polymethylpentene		R																				
Polypropylene (PP)		R																				
Polystyrene																						
Polysulfone		U																				
Polyvinylidene Chloride		U																				
PVC Type 1		U																				
PVC Type 2		U																				
PVDF (Kynar)		R					U															
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALICYLALDEHYDE

Elastomers* and Linings	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)	R																					
Ethylene-Propylene Terpolymer (EPT)	R																					
FKM (Viton A)	R																					
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)	R																					
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/Corrosion Resistance Tables: Fifth Edition, Revised and Expanded DOI: 10.1081/5672-X-120029007

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SALICYLIC ACID



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALICYLIC ACID



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SALICYLIC ACID


Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)	R	
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)	R	
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R	
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)	R	
Ethylene-Propylene Terpolymer (EPT)	R	
FKM (Viton A)	R	
Hard Rubber		
Soft Rubber		
Isoprene (IR)	R	
Kalrez (FPM)	R	
Koroseal	R	
Natural Rubber (GRS)	R	
Neoprene GR-M (CR)	R	
Nitrile Buna-N (NBR)	R	U
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton	U	
Felt (Wool)	U	
Rayon Viscose	U	

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SEA WATER



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029008

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SEA WATER




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SEA WATER



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SELENIUS ACID, 30%

Metals	°C	°F
Admiralty Brass		
Aluminum		
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper		
Hastelloy B/B-2		
Hastelloy C/C-276		
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825		
Lead		
Monel 400		
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347		
Type 316/316 L	G	
Type 400 series		
Type 317/317 L	G	
17-4 PH		
20 Cb 3	G	
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		
Tantalum		
Titanium		
Zirconium		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029009

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SELENIUS ACID, 30%

Nonmetallic Materials
Borosilicate Glass
Carbon
Carbon-Graphite Resin Impregnated
Ceramics
Coatings
Acrylic
Asphalt
Chlorinated Rubber
Coal Tar
Coal Tar Epoxy
Epoxy General Purpose
Epoxy Chemical Resistant
Epoxy Polyamide
Oil Base (Alkyd, Epoxy, Urethane)
Phenolic
Polyester
Polyvinyl Chloride
Silicones
Urethanes
Vinyls
Water Base
Zinc Rich
Mortars
Silicate
Sodium Silicate
Potassium Silicate
Silica
Sulfur
Furan Resin
Polyester
Epoxy

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SELENIUS ACID, 30%

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)		R																				
Ryton																						
TFE (Teflon)																						
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SELENIUS ACID, 30%

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)																					
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)																					
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029010

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SHELLAC

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon		R																				
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																					
Acetal																					
Acrylics																					
Asbestos Reinforced Epoxy																					
Asbestos Reinforced Phenolic																					
Chlorinated Polyether (Penton)																					
CPVC																					
E-CTFE (Halar)																					
Epoxy	R																				
ETFE (Tefzel)																					
FEP	R																				
Furan (Furfural Alcohol)																					
Noryl																					
Nylon 6																					
Nylon 11																					
Nylon 66																					
Phenolic																					
PFA (Teflon)																					
Polyamide-Imide																					
Polyesters																					
Bisphenol A–fumarate																					
Halogenated																					
Hydrogenated Bisphenol A																					
–Bisphenol A																					
Isophthalic																					
Terephthalate (PET)																					
Polyetherimide (ULTEM)																					
Polyetheretherketone (PEEK)																					
Polyethersulfone (PES)																					
Polyethylene HMW	R																				
Polyethylene UHMW	U																				
Polymethylpentene																					
Polypropylene (PP)	R																				
Polystyrene																					
Polysulfone																					
Polyvinylidene Chloride																					
PVC Type 1	R																				
PVC Type 2	R																				
PVDF (Kynar)																					
Ryton																					
TFE (Teflon)	R																				
Vinyl Ester																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SHELLAC

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)																					
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)																					
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G																									
Aluminum Bronze		G																									
Brass		E																									
Bronze		G																									
Carbon Steel		G																									
Columbium (Niobium)																											
Copper		E																									
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze		E																									
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		G																									
Type 316/316 L		G																									
Type 400 series		G																									
Type 904-L																											
17-4 PH		G																									
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze		G																									
Silicon Copper																											
Stellite		G																									
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029011

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILICONE OIL

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon		R	—																			
Carbon-Graphite Resin Impregnated		R																				
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones		U																				
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILICONE OIL

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Polycarbonate (PC)		R																				
Polyphenylene Oxide		R																				
Polybutylene Terephthalate		R																				
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC		R																				
E-CTFE (Halar)		R																				
Epoxy		R																				
ETFE (Tefzel)																						
FEP		R																				
Furan (Furfural Alcohol)																						
Noryl		R																				
Nylon 6		R																				
Nylon 11		R																				
Nylon 66		R																				
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic		R																				
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW		R																				
Polymethylpentene																						
Polypropylene (PP)		R																				
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1		R																				
PVC Type 2																						
PVDF (Kynar)		R																				
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILICONE OIL



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass		U																									
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper		U																									
Hastelloy B/B-2		E																									
Hastelloy C/C-276		E																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 825		E																									
Galv. Stl.		U																									
Monel 400		E	G																								
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		U																									
Type 316/316 L		U																									
Type 400 series		U																									
Type 317/317 L		U																									
Type 321		U																									
20 Cb 3		E																									
E-Bright 26-1																											
Silicon Bronze		U																									
Silicon Copper																											
Stellite																											
Tantalum		E																									
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029012

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER BROMIDE 10%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER BROMIDE 10%

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC	R	
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A–Bisphenol A		
Isophthalic	R	
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1	R	
PVC Type 2	R	
PVDF (Kynar)	R	
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER BROMIDE 10%

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)																					
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)																					
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SILVER CHLORIDE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum			U																									
Aluminum Bronze			U																									
Brass			U																									
Bronze			U																									
Carbon Steel			U																									
Columbium (Niobium)																												
Copper			U																									
Hastelloy B/B-2			U																									
Hastelloy C/C-276	10%		G																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625			S																									
Incolloy 825			E																									
Galv. Stl.			U																									
Monel 400			G																									
Naval Bronze			U																									
Nickel 200/201			S																									
Ni-Resist																												
Stainless Steels																												
Type 304/347			U																									
Type 316/316 L			U																									
Type 400 series			U																									
Type 904-L																												
17-4 PH			U																									
20 Cb 3			G																									
E-Bright 26-1																												
Silicon Bronze			U																									
Silicon Copper			U																									
Stellite																												
Tantalum			E																									
Titanium			E																									
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029013

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER CHLORIDE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER CHLORIDE

Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)	R	
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)	R	
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton	U	
Felt (Wool)		
Rayon Viscose		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		U																									
Aluminum Bronze		U																									
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper		U																									
Hastelloy B/B-2		E																									
Hastelloy C/C-276		E																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825		E																									
Lead																											
Monel 400		G																									
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		E																									
Type 316/316 L		E																									
Type 400 series		E																									
Type 904-L																											
17-4 PH																											
20 Cb 3		E																									
E-Bright 26-1																											
Silicon Bronze		U																									
Silicon Copper		U																									
Stellite																											
Tantalum		E																									
Titanium		E																									
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029014

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SILVER CYANIDE

Nonmetallic Materials	°F	°C
Borosilicate Glass		
Carbon	R	R
Carbon-Graphite Resin Impregnated	R	R
Ceramics		
Coatings		
Acrylic		
Asphalt		
Chlorinated Rubber		
Coal Tar		
Coal Tar Epoxy		
Epoxy General Purpose		
Epoxy Chemical Resistant		
Epoxy Polyamide		
Oil Base (Alkyd, Epoxy, Urethane)		
Phenolic		
Polyester		
Polyvinyl Chloride	R	R
Silicones		
Urethanes		
Vinyls	R	R
Water Base		
Zinc Rich		
Mortars		
Silicate		
Sodium Silicate		
Potassium Silicate		
Silica		
Sulfur		
Furan Resin		
Polyester		
Epoxy		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER CYANIDE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER CYANIDE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER NITRATE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum			U																									
Aluminum Bronze			U																									
Brass			U																									
Bronze			U																									
Carbon Steel			U																									
Columbium (Niobium)			E																									
Copper			U																									
Hastelloy B/B-2	10–40%		E																									
Hastelloy C/C-276	10–40%		E																									
Hastelloy D	10–40%		E																									
Hastelloy G/G-3																												
High Silicon Iron			G																									
Inconel 600/625			G																									
Incolloy 800/825			G																									
Lead			U																									
Monel 400			U																									
Naval Bronze			U																									
Nickel 200/201			U																									
Galv. Stl.			U																									
Stainless Steels																												
Type 304/347			G																									
Type 316/316 L			E		G																							
Type 400 series	10–90%		G																									
Type 904-L																												
17-4 PH																												
20 Cb 3			G																									
E-Bright 26-1																												
Silicon Bronze			U																									
Silicon Copper			U																									
Stellite																												
Tantalum	50%		E																									
Titanium	50%		E																									
Zirconium	50%		G																									
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029015

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SILVER NITRATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER NITRATE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SILVER NITRATE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029016

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOAPS




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SOAPS



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOAP SOLUTION 5%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029017

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOAP SOLUTION 5%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOAP SOLUTION 5%


Plastics	
Polybutylene Terephthalate	R
Acetal	R
Acrylics	R
Polycarbonate	R
Polyphenylene Oxide	R
Chlorinated Polyether (Penton)	R
CPVC	R
E-CTFE (Halar)	
Epoxy	R
ETFE (Tefzel)	
FEP	R
Furan (Furfural Alcohol)	
Noryl	R
Nylon 6	R
Nylon 11	R
Nylon 66	R
Phenolic	
PFA (Teflon)	R
Polyamide-Imide	
Polyesters	
Bisphenol A–fumarate	R
Halogenated	R
Hydrogenated Bisphenol A –Bisphenol A	
Isophthalic	R
Terephthalate (PET)	
Polyetherimide (ULTEM)	
Polyetheretherketone (PEEK)	
Polyethersulfone (PES)	
Polyethylene HMW	R
Polyethylene UHMW	R
Polymethylpentene	
Polypropylene (PP)	R
Polystyrene	
Polysulfone	R
Polyvinylidene Chloride	R
PVC Type 1	R
PVC Type 2	R
PVDF (Kynar)	R
Ryton	
TFE (Teflon)	R
Vinyl Ester	R

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOAP SOLUTION 5%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029018

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOAP SOLUTIONS



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOAP SOLUTIONS

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Polybutylene Terephthalate		R																				
Acetal		R																				
Acrylics		R																				
Polycarbonate		R																				
Polyphenylene Oxide		R																				
Chlorinated Polyether (Penton)		R																				
CPVC		R																				
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP		R																				
Furan (Furfural Alcohol)																						
Noryl		R																				
Nylon 6		R																				
Nylon 11		R																				
Nylon 66		R																				
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate	1%	R																				
Halogenated	1%	R																				
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic	1%	R																				
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		R																				
Polyethylene UHMW		R																				
Polymethylpentene																						
Polypropylene (PP)		R																				
Polystyrene																						
Polysulfone		R																				
Polyvinylidene Chloride		R																				
PVC Type 1		R																				
PVC Type 2		R																				
PVDF (Kynar)		R																				
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOAP SOLUTIONS



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass	10%		G																									
Aluminum			E																									
Aluminum Bronze																												
Brass	ALL		G																									
Bronze			G																									
Carbon Steel	10%		U																									
Columbium (Niobium)																												
Copper			G																									
Hastelloy B/B-2	60%		G																									
Hastelloy C/C-276	60%		G																									
Hastelloy D	60%		G																									
Hastelloy G/G-3																												
High Silicon Iron			G																									
Inconel 600/625	60%		G																									
Incolloy 800/825	5%		G																									
Galv. Stl.			U																									
Monel 400	ALL		G																									
Naval Bronze	10–60%		G																									
Nickel 200/201	60%		G																									
Ni-Resist			G																									
Stainless Steels																												
Type 304/347			G																									
Type 316/316 L			G																									
Type 400 series TO	60% 1		G																									
Type 904-L																												
17-4 PH																												
20 Cb 3			G																									
E-Bright 26-1																												
Silicon Bronze			G																									
Silicon Copper	10%		G																									
Stellite																												
Tantalum			E																									
Titanium	SAT		E																									
Zirconium	60%		E																									
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029019


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM ACETATE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM ACETATE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM ACETATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cor



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029020

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM ACID SULFATE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM ACID SULFATE


Plastics		°C	°F
ABS	6.5%	R	R
Acetal			
Acrylics		R	R
Asbestos Reinforced Epoxy		R	R
Asbestos Reinforced Phenolic		R	R
Chlorinated Polyether (Penton)		R	R
CPVC		R	R
E-CTFE (Halar)		R	R
Epoxy		R	R
ETFE (Tefzel)		R	R
FEP		R	R
Furan (Furfural Alcohol)		R	R
Noryl		R	R
Nylon 6		R	R
Nylon 11		R	R
Nylon 66		R	R
Phenolic		R	R
PFA (Teflon)		R	R
Polyamide-Imide			
Polyesters			
Bisphenol A–fumarate		R	R
Halogenated	ALL	R	R
Hydrogenated Bisphenol A –Bisphenol A			
Isophthalic		R	R
Terephthalate (PET)		R	R
Polyetherimide (ULTEM)			
Polyetheretherketone (PEEK)			
Polyethersulfone (PES)			
Polyethylene HMW		R	R
Polyethylene UHMW		R	R
Polymethylpentene			
Polypropylene (PP)		R	R
Polystyrene		R	R
Polysulfone		R	R
Polyvinylidene Chloride		R	R
PVC Type 1		R	R
PVC Type 2		R	R
PVDF (Kynar)		R	R
Ryton	ALL	R	R
TFE (Teflon)		R	R
Vinyl Ester	ALL	R	R

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM ACID SULFATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum			G	—																								
Aluminum Bronze																												
Brass																												
Bronze			U																									
Carbon Steel			G	—	—	—	—																					
Columbium (Niobium)																												
Copper																												
Hastelloy B/B-2	10%		S	—																								
Hastelloy C/C-276			G	—	—	—	—																					
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625																												
Incolloy 800/825																												
Galv. Stl.			U																									
Monel 400			G	—	—	—	—																					
Naval Bronze																												
Nickel 200/201																												
Ni-Resist	TO 10%		G	—																								
Stainless Steels																												
Type 304/347			G	—																								
Type 316/316 L			G	—	—	—	—																					
Type 400 series																												
Type 904-L																												
17-4 PH																												
20 Cb 3			G	—	—	—	—																					
E-Bright 26-1																												
Silicon Bronze			U																									
Silicon Copper																												
Stellite																												
Tantalum	25%		E	—	—	—	—	—	—	—																		
Titanium	25%		E	—	—	—	—	—	—	—																		
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029021

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM ALUMINATE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated		R																				
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM ALUMINATE


Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC	R	
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6	R	
Nylon 11	R	
Nylon 66	R	
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate	R	
Halogenated	U	
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic	U	
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)		
Ryton		
TFE (Teflon)	R	
Vinyl Ester	R	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM ALUMINATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expa*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c

SODIUM BENZOATE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum			G	—																								
Aluminum Bronze																												
Brass																												
Bronze																												
Carbon Steel																												
Columbium (Niobium)																												
Copper			E	—																								
Hastelloy B/B-2			G	—																								
Hastelloy C/C-276			G	—																								
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625			G	—																								
Incolloy 800/825			E	G	—																							
Galv. Stl.	2%		G	—																								
Monel 400			G	—																								
Naval Bronze																												
Nickel 200/201			G	—																								
Ni-Resist																												
Stainless Steels																												
Type 304/347																												
Type 316/316 L																												
Type 400 series																												
Type 904-L																												
17-4 PH																												
20 Cb 3																												
E-Bright 26-1																												
Silicon Bronze			G	—																								
Silicon Copper			E	—																								
Stellite																												
Tantalum			E	—																								
Titanium			E	—																								
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029022

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM BENZOATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BENZOATE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BENZOATE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BICARBONATE 20%

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			G																									
Aluminum			G																									
Aluminum Bronze			G																									
Brass			G																									
Bronze			G																									
Carbon Steel			S																									
Columbium (Niobium)																												
Copper			S																									
Hastelloy B/B-2	10–20%		E																									
Hastelloy C/C-276	10–20%		E																									
Hastelloy D	10–20%		E																									
Hastelloy G/G-3																												
High Silicon Iron			G																									
Inconel 600/625			E																									
Incolloy 800/825			G																									
Lead			G																									
Monel 400			E																									
Naval Bronze			G																									
Nickel 200/201			E																									
Ni-Resist			E																									
Stainless Steels																												
Type 304/347			E																									
Type 316/316 L			E																									
Type 400 series			G																									
Type 904-L																												
17-4 PH			G																									
20 Cb 3			E																									
E-Bright 26-1																												
Silicon Bronze			G																									
Silicon Copper			E																									
Galv. Stl.			U																									
Tantalum	ALL		E																									
Titanium			E																									
Zirconium			E																									
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029023

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BICARBONATE 20%




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BICARBONATE 20%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BICHROMATE NEUTRAL

Metals	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																										
Aluminum	G																									
Aluminum Bronze																										
Brass																										
Bronze																										
Carbon Steel																										
Columbium (Niobium)																										
Copper	G																									
Hastelloy B/B-2	U																									
Hastelloy C/C-276	G																									
Hastelloy D																										
Hastelloy G/G-3																										
High Silicon Iron																										
Inconel 600/625	G																									
Incolloy 800/825	G																									
Lead																										
Monel 400																										
Naval Bronze																										
Nickel 200/201																										
Ni-Resist																										
Stainless Steels																										
Type 304/347	G																									
Type 316/316 L	G																									
Type 400 series	G																									
Type 904-L																										
17-4 PH																										
20 Cb 3	G																									
E-Bright 26-1																										
Silicon Bronze	G																									
Silicon Copper																										
Stellite																										
Tantalum	G																									
Titanium	G																									
Zirconium																										
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029024

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BICHROMATE NEUTRAL

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated		R																				
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate	50%	R																				
Silica	50%	R																				
Sulfur	50%	R																				
Furan Resin	50%	R																				
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BICHROMATE NEUTRAL

Plastics		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																							
Acetal																							
Acrylics																							
Asbestos Reinforced Epoxy																							
Asbestos Reinforced Phenolic																							
Chlorinated Polyether (Penton)																							
CPVC			R																				
E-CTFE (Halar)			R																				
Epoxy																							
ETFE (Tefzel)																							
FEP			R																				
Furan (Furfural Alcohol)			R																				
Noryl																							
Nylon 6	5%		R																				
Nylon 11	5%		R																				
Nylon 66	5%		R																				
Phenolic																							
PFA (Teflon)																							
Polyamide-Imide																							
Polyesters																							
Bisphenol A–fumarate			R																				
Halogenated			R																				
Hydrogenated Bisphenol A –Bisphenol A																							
Isophthalic			R																				
Terephthalate (PET)																							
Polyetherimide (ULTEM)																							
Polyetheretherketone (PEEK)																							
Polyethersulfone (PES)																							
Polyethylene HMW																							
Polyethylene UHMW																							
Polymethylpentene																							
Polypropylene (PP)																							
Polystyrene																							
Polysulfone																							
Polyvinylidene Chloride																							
PVC Type 1			R																				
PVC Type 2																							
PVDF (Kynar)																							
Ryton			R																				
TFE (Teflon)			R																				
Vinyl Ester			R																				
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BICHROMATE NEUTRAL



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BISULFATE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			G																									
Aluminum			U																									
Aluminum Bronze			U																									
Brass	10%		G																									
Bronze			G																									
Carbon Steel			G																									
Columbium (Niobium)	40%		G																									
Copper			S																									
Hastelloy B/B-2	10–30%		G																									
Hastelloy C/C-276	10–30%		G																									
Hastelloy D			G																									
Hastelloy G/G-3																												
High Silicon Iron			G																									
Inconel 600/625	10–30%		G																									
Incolloy 800/825			G																									
Lead			G																									
Monel 400	10–30%		G																									
Naval Bronze	10–20%		G																									
Nickel 200/201	10–50%		G																									
Ni-Resist			U																									
Stainless Steels																												
Type 304/347	10% 1,9		E						U																			
Type 316/316 L	10%		E						U																			
Type 400 series	10%		E																									
Type 904-L																												
17-4 PH																												
20 Cb 3	10–40%		E																									
E-Bright 26-1																												
Silicon Bronze			U																									
Silicon Copper			G																									
Galv. Stl.			U																									
Tantalum	TO 25%		E																									
Titanium	10–30%		E						U																			
Zirconium	10–50%		E																									
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029025

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BISULFATE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BISULFATE

Plastics		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS	6.5%		R																				
KEL-F (CTFE)			R																				
Acrylics			R																				
Asbestos Reinforced Epoxy			R																				
Asbestos Reinforced Phenolic			R																				
Chlorinated Polyether (Penton)			R																				
CPVC			R																				
E-CTFE (Halar)			R																				
Epoxy			R																				
ETFE (Tefzel)			R																				
FEP			R																				
Furan (Furfural Alcohol)			R																				
Noryl			R																				
Nylon 6			R																				
Nylon 11			R																				
Nylon 66			R																				
Phenolic			R																				
PFA (Teflon)			R																				
Polyamide-Imide																							
Polyesters																							
Bisphenol A–fumarate			R																				
Halogenated	ALL		R																				
Hydrogenated Bisphenol A –Bisphenol A																							
Isophthalic			R																				
Terephthalate (PET)			R																				
Polyetherimide (ULTEM)																							
Polyetheretherketone (PEEK)																							
Polyethersulfone (PES)																							
Polyethylene HMW			R																				
Polyethylene UHMW			R																				
Polymethylpentene																							
Polypropylene (PP)			R																				
Polystyrene			R																				
Polysulfone			R																				
Polyvinylidene Chloride			R																				
PVC Type 1			R																				
PVC Type 2			R																				
PVDF (Kynar)			R																				
Ryton	ALL		R																				
TFE (Teflon)			R																				
Vinyl Ester	ALL		R																				
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BISULFATE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BISULFITE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			G																									
Aluminum			U																									
Aluminum Bronze			G																									
Brass			G																									
Bronze			U																									
Carbon Steel			U																									
Columbium (Niobium)																												
Copper			G																									
Hastelloy B/B-2	10–40%		G																									
Hastelloy C/C-276			G																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron			S																									
Inconel 600/625	20%		G																									
Incolloy 800/825																												
Lead			G																									
Monel 400	10–40%		G																									
Naval Bronze			G																									
Nickel 200/201	10–40%		G																									
Ni-Resist																												
Stainless Steels																												
Type 304/347	20% 2		G																									
Type 316/316 L	10–40%		G																									
Type 400 series																												
Type 904-L																												
17-4 PH																												
20 Cb 3	10–40%		G																									
E-Bright 26-1																												
Silicon Bronze			G																									
Silicon Copper			G																									
Stellite																												
Tantalum			G																									
Titanium	10–40%		G																									
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029026


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BISULFITE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BISULFITE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM BISULFITE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BORATE



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/Corrosion Resistance Tables: Fifth Edition, Revised and Expanded DOI: 10.1081/5672-X-120029027

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM BORATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BORATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BORATE




*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SODIUM BROMIDE

Metals		°C	°F
Admiralty Brass			
Aluminum	10%	S	
Aluminum Bronze			
Brass	10%	G	
Bronze	10%	G	
Carbon Steel	10%	S	
Columbium (Niobium)			
Copper	5%	G	
Hastelloy B/B-2	10–50%	G	
Hastelloy C/C-276	10–50%	G	
Hastelloy D	10–50%	G	
Hastelloy G/G-3			
High Silicon Iron			
Inconel 600/625	10–50%	G	
Incolloy 800/825	5%	E	
Galv. Stl.		U	
Monel 400	10–40%	G	
Naval Bronze	10%	G	
Nickel 200/201	10–50%	G	
Ni-Resist		G	
Stainless Steels			
Type 304/347	10%	G	
Type 316/316 L	10–50%	G	
Type 400 series		U	
Type 904-L			
17-4 PH			
20 Cb 3	10–50%	G	
E-Bright 26-1			
Silicon Bronze		G	
Silicon Copper	5%	E	
Stellite			
Tantalum		G	
Titanium		G	
Zirconium		G	



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029028

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM BROMIDE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SODIUM BROMIDE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM BROMIDE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029029

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM CARBONATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM CARBONATE

Plastics	
ABS	25% R
Acetal	R
Acrylics	U
Asbestos Reinforced Epoxy	R
Asbestos Reinforced Phenolic	R
Chlorinated Polyether (Penton)	R
CPVC	R
E-CTFE (Halar)	R
Epoxy	R
ETFE (Tefzel)	R
FEP	R
Furan (Furfural Alcohol)	50% R
Noryl	R
Nylon 6	R
Nylon 11	R
Nylon 66	R
Phenolic	U
PFA (Teflon)	R
Polyamide-Imide	10% R
Polyesters	
Bisphenol A–fumarate	R
Halogenated	10% R
Hydrogenated Bisphenol A –Bisphenol A	10% R
Isophthalic	20% R
Terephthalate (PET)	R
Polyetherimide (ULTEM)	
Polyetheretherketone (PEEK)	R
Polyethersulfone (PES)	R
Polyethylene HMW	R
Polyethylene UHMW	R
Polymethylpentene	R
Polypropylene (PP)	R
Polystyrene	R
Polysulfone	R
Polyvinylidene Chloride	R
PVC Type 1	R
PVC Type 2	R
PVDF (Kynar)	R
Ryton	R
TFE (Teflon)	R
Vinyl Ester	R




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CARBONATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029030


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHLORATE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHLORATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM CHLORATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHLORIDE



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029031


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHLORIDE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHLORIDE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SODIUM CHLORITE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum																												
Aluminum Bronze																												
Brass																												
Bronze																												
Carbon Steel																												
Columbium (Niobium)			U																									
Copper																												
Hastelloy B/B-2																												
Hastelloy C/C-276	10%		G																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625																												
Incolloy 800/825																												
Galv. Stl.			G																									
Monel 400																												
Naval Bronze																												
Nickel 200/201																												
Ni-Resist																												
Stainless Steels																												
Type 304/347	5% 1		G																									
Type 316/316 L	5%		E																									
Type 400 series																												
Type 904-L																												
17-4 PH																												
20 Cb 3																												
E-Bright 26-1			E																									
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum																												
Titanium																												
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029032

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHLORITE



Nonmetallic Materials		
Borosilicate Glass		
Carbon		R
Carbon-Graphite Resin Impregnated		R
Ceramics		
Coatings		
Acrylic		
Asphalt		
Chlorinated Rubber		
Coal Tar		
Coal Tar Epoxy		R
Epoxy General Purpose		
Epoxy Chemical Resistant		
Epoxy Polyamide		R
Oil Base (Alkyd, Epoxy, Urethane)		
Phenolic		
Polyester		R
Polyvinyl Chloride		R
Silicones		
Urethanes		
Vinyls		R
Water Base		
Zinc Rich		
Mortars		
Silicate		
Sodium Silicate	50%	U
Potassium Silicate		
Silica		
Sulfur	50%	U
Furan Resin	50%	U
Polyester	50%	R
Epoxy	50%	U


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHLORITE

Plastics		°C	°F
ABS			
Acetal			
Acrylics			
Asbestos Reinforced Epoxy			
Asbestos Reinforced Phenolic			
Chlorinated Polyether (Penton)	R	15–71	60–160
CPVC	R	15–93	60–200
E-CTFE (Halar)			
Epoxy	25% R	15–71	60–160
ETFE (Tefzel)			
FEP	R	15–238	60–460
Furan (Furfural Alcohol)			
Noryl	20% R	15–60	60–140
Nylon 6			
Nylon 11			
Nylon 66			
Phenolic			
PFA (Teflon)			
Polyamide-Imide			
Polyesters			
Bisphenol A–fumarate	50% R	15–104	60–220
Halogenated	R	15–71	60–160
Hydrogenated Bisphenol A –Bisphenol A			
Isophthalic	U		
Terephthalate (PET)			
Polyetherimide (ULTEM)			
Polyetheretherketone (PEEK)			
Polyethersulfone (PES)			
Polyethylene HMW			
Polyethylene UHMW	50% R	15–38	60–100
Polymethylpentene			
Polypropylene (PP)	U		
Polystyrene			
Polysulfone			
Polyvinylidene Chloride	R	15–49	60–120
PVC Type 1	R	15–60	60–140
PVC Type 2	U		
PVDF (Kynar)	R	15–116	60–240
Ryton	10–50% R	15–71	60–160
TFE (Teflon)	R	15–238	60–460
Vinyl Ester	50% R	15–26	60–80

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHLORITE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHROMATE 80%

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass		E																									
Aluminum																											
Aluminum Bronze		E																									
Brass		E																									
Bronze		E																									
Carbon Steel		G																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2		E																									
Hastelloy C/C-276		E																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Galv. Stl.		U																									
Monel 400		E																									
Naval Bronze		E																									
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L		E																									
Type 400 series		E																									
Type 317/317 L		G																									
17-4 PH		E																									
20 Cb 3		E																									
E-Bright 26-1																											
Silicon Bronze		E																									
Silicon Copper		E																									
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029033

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHROMATE 80%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHROMATE 80%

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC	R	
E-CTFE (Halar)		
Epoxy	U	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl	R	
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate 50%	R	
Halogenated SAT	R	
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic	R	
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone	R	
Polyvinylidene Chloride		
PVC Type 1	R	
PVC Type 2	R	
PVDF (Kynar)	R	
Ryton 50%	R	
TFE (Teflon)	R	
Vinyl Ester 50%	R	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CHROMATE 80%

Elastomers* and Linings	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	R																				
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)	R																				
Nitrile Buna-N (NBR)	R																				
Nordel (EPDM)	R																				
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029034

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CITRATE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CITRATE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)	R																					
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CYANIDE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			U																									
Aluminum			U																									
Aluminum Bronze			U																									
Brass			U																									
Bronze			U																									
Carbon Steel			G																									
Columbium (Niobium)																												
Copper			U																									
Hastelloy B/B-2			G																									
Hastelloy C/C-276			G																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron			G																									
Inconel 600/625			G																									
Incolloy 800/825																												
Lead			U																									
Monel 400			U																									
Naval Bronze			U																									
Nickel 200/201			U																									
Ni-Resist			G																									
Stainless Steels																												
Type 304/347	10% 1		E																									
Type 316/316 L	10%		E																									
Type 400 series 10–20% 1			E																									
Type 904-L																												
17-4 PH			G																									
20 Cb 3	ALL		E																									
E-Bright 26-1																												
Silicon Bronze			U																									
Silicon Copper			U																									
Stellite																												
Tantalum			G																									
Titanium			E																									
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029035

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CYANIDE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


Plastics	
ABS	R
Acetal	10% R
Acrylics	R
Asbestos Reinforced Epoxy	
Asbestos Reinforced Phenolic	
Chlorinated Polyether (Penton)	R
CPVC	R
E-CTFE (Halar)	R
Epoxy	R
ETFE (Tefzel)	R
FEP	R
Furan (Furfural Alcohol)	R
Noryl	R
Nylon 6	R
Nylon 11	R
Nylon 66	R
Phenolic	
PFA (Teflon)	R
Polyamide-Imide	
Polyesters	
Bisphenol A–fumarate	R
Halogenated	50% R U
Hydrogenated Bisphenol A –Bisphenol A	
Isophthalic	R
Terephthalate (PET)	ALL R
Polyetherimide (ULTEM)	
Polyetheretherketone (PEEK)	
Polyethersulfone (PES)	
Polyethylene HMW	R
Polyethylene UHMW	R
Polymethylpentene	
Polypropylene (PP)	R
Polystyrene	
Polysulfone	R
Polyvinylidene Chloride	R
PVC Type 1	R
PVC Type 2	R
PVDF (Kynar)	R
Ryton	R
TFE (Teflon)	R
Vinyl Ester	R

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM CYANIDE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM DICHROMATE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G	—	—	—	—	—	—	—																		
Aluminum Bronze		U																									
Brass		U																									
Bronze		U																									
Carbon Steel		G	—																								
Columbium (Niobium)																											
Copper		U																									
Hastelloy B/B-2		U																									
Hastelloy C/C-276		E	—																								
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Galv. Stl.		U																									
Monel 400																											
Naval Bronze		E	S																								
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		G	—																								
Type 316/316 L		G	—																								
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze		U																									
Silicon Copper																											
Stellite																											
Tantalum		E	—																								
Titanium	SAT	E	—																								
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029036

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM DICHROMATE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM DICHROMATE


Plastics	°C	°F
ABS	R	
Acetal		
Acrylics		
Asbestos Reinforced Epoxy	R	
Asbestos Reinforced Phenolic	R	
Chlorinated Polyether (Penton)	R	
CPVC	R	
E-CTFE (Halar)	R	
Epoxy	R	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl	R	
Nylon 6	U	
Nylon 11	U	
Nylon 66	U	
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate	R	
Halogenated	R	
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic	R	
Terephthalate (PET)	R	
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	R	
Polyethylene UHMW	R	
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride	R	
PVC Type 1	R	
PVC Type 2	R	
PVDF (Kynar)	R	
Ryton	R	
TFE (Teflon)	R	
Vinyl Ester	R	

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM DICHROMATE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029037


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FERRICYANIDE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FERRICYANIDE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FERRICYANIDE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FERROCYANIDE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G																									
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper		G																									
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400		G																									
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L		G																									
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3		G																									
E-Bright 26-1																											
Silicon Bronze		G																									
Silicon Copper																											
Stellite																											
Tantalum		E																									
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029038


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FERROCYANIDE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FERROCYANIDE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FERROCYANIDE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029039


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FLUORIDE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FLUORIDE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM FLUORIDE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROSULFIDE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum																												
Aluminum Bronze																												
Brass																												
Bronze																												
Carbon Steel																												
Columbium (Niobium)																												
Copper																												
Hastelloy B/B-2																												
Hastelloy C/C-276	12%	G																										
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625																												
Incolloy 800/825																												
Lead																												
Monel 400	40%	E																										
Naval Bronze																												
Nickel 200/201	45%	G																										
Ni-Resist																												
Stainless Steels																												
Type 304/347	30–50%	E																										
Type 316	30–50%	G																										
Type 400 series																												
Type 317/317 L	30–50%	G																										
17-4 PH																												
20 Cb 3	40%	E																										
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum																												
Titanium																												
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029040

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROSULFIDE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM HYDROSULFIDE

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP		
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)		
Ryton		
TFE (Teflon)		
Vinyl Ester		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM HYDROSULFIDE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROSULFITE



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028896

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROSULFITE

Nonmetallic Materials	
Borosilicate Glass	
Carbon	
Carbon-Graphite Resin Impregnated	
Ceramics	
Coatings	
Acrylic	
Asphalt	
Chlorinated Rubber	
Coal Tar	
Coal Tar Epoxy	
Epoxy General Purpose	
Epoxy Chemical Resistant	
Epoxy Polyamide	
Oil Base (Alkyd, Epoxy, Urethane)	
Phenolic	
Polyester	
Polyvinyl Chloride	
Silicones	
Urethanes	
Vinyls	10% R
Water Base	
Zinc Rich	
Mortars	
Silicate	
Sodium Silicate	
Potassium Silicate	
Silica	
Sulfur	
Furan Resin	
Polyester	
Epoxy	

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROSULFITE


Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic	R	
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)		
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROSULFITE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028897

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 10%




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM HYDROXIDE 10%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 15%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028898


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 15%




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 15%



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM HYDROXIDE 15%



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 30%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028899


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 30%




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SODIUM HYDROXIDE 30%



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM HYDROXIDE 30%



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SODIUM HYDROXIDE 50%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028900

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 50%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 50%

Plastics	
ABS	R
Acetal	U
Acrylics	R
Asbestos Reinforced Epoxy	R
Asbestos Reinforced Phenolic	U
Chlorinated Polyether (Penton)	R
CPVC	R
E-CTFE (Halar)	R
Epoxy	R
ETFE (Tefzel)	R
FEP	R
Furan (Furfural Alcohol)	U
Noryl	R
Nylon 6	R
Nylon 11	R
Nylon 66	R
Phenolic	U
PFA (Teflon)	R
Polyamide-Imide	U
Polyesters	
Bisphenol A–fumarate	R
Halogenated	U
Hydrogenated Bisphenol A –Bisphenol A	U
Isophthalic	U
Terephthalate (PET)	U
Polyetherimide (ULTEM)	
Polyetheretherketone (PEEK)	R
Polyethersulfone (PES)	R
Polyethylene HMW	R
Polyethylene UHMW	R
Polymethylpentene	R
Polypropylene (PP)	R
Polystyrene	R
Polysulfone	R
Polyvinylidene Chloride	R
PVC Type 1	R
PVC Type 2	R
PVDF (Kynar) 2	R
Ryton	R
TFE (Teflon)	R
Vinyl Ester	R


°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM HYDROXIDE 50%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 70%



Metals

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/Corrosion Resistance Tables: Fifth Edition, Revised and Expanded DOI: 10.1081/5672-X-120028901

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 70%




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE 70%




*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE SOLUTION (CONC.)



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028902

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE SOLUTION (CONC.)




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SODIUM HYDROXIDE SOLUTION (CONC.)

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		R																				
Acetal		U																				
Acrylics		R																				
Asbestos Reinforced Epoxy		R																				
Asbestos Reinforced Phenolic		U																				
Chlorinated Polyether (Penton)		R																				
CPVC		R																				
E-CTFE (Halar)		R																				
Epoxy																						
ETFE (Tefzel)																						
FEP		R																				
Furan (Furfural Alcohol)		U																				
Noryl		U																				
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic		U																				
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic		U																				
Terephthalate (PET)		U																				
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)		R																				
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene		R																				
Polypropylene (PP)		R																				
Polystyrene		R																				
Polysulfone		R																				
Polyvinylidene Chloride		U																				
PVC Type 1		R																				
PVC Type 2		R																				
PVDF (Kynar)	2	R																				
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester		U																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYDROXIDE SOLUTION (CONC.)




*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SODIUM HYPOCHLORITE 20%

Metals	
Admiralty Brass	U
Aluminum	G
Aluminum Bronze	U
Brass	G
Bronze	S
Carbon Steel	U
Columbium (Niobium)	U
Copper	S
Hastelloy B/B-2	U
Hastelloy C/C-276	U
Hastelloy D	
Hastelloy G/G-3	G
High Silicon Iron	G
Inconel 600/625	U
Incolloy 800/825	S
Lead	U
Monel	S
Naval Bronze	U
Nickel	U
Galv. Stl.	U
Stainless Steels	
Type 304/347	U
Type 316/316 L	U
Type 400 series	U
Type 317/317 L	U
Type 321	U
20 Cb 3	S
E-Bright 26-1	G
Silicon Bronze	U
Silicon Copper	U
Stellite	G
Tantalum	G
Titanium	G
Zirconium	E



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028903


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYPOCHLORITE 20%

Nonmetallic Materials	
Borosilicate Glass	R
Carbon	U
Carbon-Graphite Resin Impregnated	U
Ceramics	
Coatings	
Acrylic	
Asphalt	
Chlorinated Rubber	
Coal Tar	
Coal Tar Epoxy	U
Epoxy General Purpose	U
Epoxy Chemical Resistant	U
Epoxy Polyamide	U
Oil Base (Alkyd, Epoxy, Urethane)	
Phenolic	U
Polyester 17%	R
Polyvinyl Chloride	R
Silicones	
Urethanes	U
Vinyls	R
Water Base	
Zinc Rich	
Mortars	
Silicate	U
Sodium Silicate	U
Potassium Silicate	U
Silica	U
Sulfur	U
Furan Resin	U
Polyester	U
Epoxy	U


°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Ex*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekke



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM HYPOCHLORITE 20%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028904

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYPOCHLORITE (CONC.)




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYPOCHLORITE (CONC.)



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SODIUM HYPOSULFITE 5%

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper	G																										
Hastelloy B/B-2	E																										
Hastelloy C/C-276	E																										
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625	E	G																									
Incolloy 800/825	G																										
Lead																											
Monel 400	E	G																									
Naval Bronze																											
Nickel 200/201	E	G																									
Ni-Resist																											
Stainless Steels																											
Type 304/347	U																										
Type 316/316 L	U																										
Type 400 series	G																										
Type 904-L																											
17-4 PH																											
20 Cb 3	E																										
E-Bright 26-1																											
Silicon Bronze	G																										
Silicon Copper																											
Stellite																											
Tantalum	E																										
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028905

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYPOSULFITE 5%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SODIUM HYPOSULFITE 5%


Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A--fumarate TO 20%	R	
Halogenated TO 20%	R	
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic 20%	R	
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	R	
Polyethylene UHMW	R	
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1	R	
PVC Type 2		
PVDF (Kynar)	R	
Ryton		
TFE (Teflon)	R	
Vinyl Ester 20%	R	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM HYPOSULFITE 5%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SODIUM IODIDE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel		G																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum		G																									
Titanium																											
Zirconium TO 60%		E																									
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028906

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM IODIDE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon		R																				
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SODIUM IODIDE


Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)	R	
CPVC		
E-CTFE (Halar)	R	
Epoxy		
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic	R	
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride	R	
PVC Type 1		
PVC Type 2		
PVDF (Kynar)	R	
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM IODIDE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

Metals	°C	°F
Admiralty Brass		
Aluminum	U	
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper	G	
Hastelloy B/B-2	G	
Hastelloy C/C-276	G	
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825	G	
Lead		
Monel 400	G	
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347	G	
Type 316/316 L	G	
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3	G	
E-Bright 26-1		
Silicon Bronze	G	
Silicon Copper		
Stellite		
Tantalum	E	
Titanium		
Zirconium		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028907

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM LACTATE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM LACTATE

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)		
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM LACTATE

Elastomers* and Linings	°C	°F
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)	R	
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)		
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c

SODIUM METAPHOSPHATE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		U																									
Aluminum Bronze		U																									
Brass		S																									
Bronze		G																									
Carbon Steel		U																									
Columbium (Niobium)																											
Copper		G																									
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron		G																									
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400		G																									
Naval Bronze		S																									
Nickel 200/201		G																									
Ni-Resist																											
Stainless Steels																											
Type 304/347		G																									
Type 316/316 L		G																									
Type 400 series		G																									
Type 904-L																											
17-4 PH																											
20 Cb 3		G																									
E-Bright 26-1																											
Silicon Bronze		U																									
Silicon Copper		G																									
Stellite																											
Tantalum		G																									
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028908

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM METAPHOSPHATE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker

SODIUM METAPHOSPHATE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC	R																					
E-CTFE (Halar)	R																					
Epoxy																						
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)	R																					
Noryl																						
Nylon 6	R																					
Nylon 11	R																					
Nylon 66	R																					
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic	R																					
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW	R																					
Polyethylene UHMW	R																					
Polymethylpentene																						
Polypropylene (PP)	R																					
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1	R																					
PVC Type 2																						
PVDF (Kynar)	R																					
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester	R																					
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM METAPHOSPHATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.

SODIUM METASILICATE



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028909

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM METASILICATE


	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Nonmetallic Materials																						
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride	R																					
Silicones																						
Urethanes																						
Vinyls	R																					
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expa*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM METASILICATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.del



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028910

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM NITRATE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dek

SODIUM NITRATE


Plastics	°C	°F
ABS	R	
Acetal 50%	R	
Acrylics	R	
Asbestos Reinforced Epoxy	R	
Asbestos Reinforced Phenolic	R	
Chlorinated Polyether (Penton)	R	
CPVC	R	
E-CTFE (Halar)	R	
Epoxy	R	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl	R	
Nylon 6	R	
Nylon 11	R	
Nylon 66	R	
Phenolic	R	
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate	R	
Halogenated ALL	R	
Hydrogenated Bisphenol A –Bisphenol A	R	
Isophthalic	R	
Terephthalate (PET)	R	
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	R	
Polyethylene UHMW	R	
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene	R	
Polysulfone	R	
Polyvinylidene Chloride	R	
PVC Type 1	R	
PVC Type 2	R	
PVDF (Kynar)	R	
Ryton	R	
TFE (Teflon)	R	
Vinyl Ester	R	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM NITRATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expa*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028911


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM NITRITE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SODIUM NITRITE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM NITRITE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SODIUM PERBORATE 10%

Metals	°C	°F
Admiralty Brass		
Aluminum	G	
Aluminum Bronze	G	
Brass	S	
Bronze	G	
Carbon Steel	G	
Columbium (Niobium)		
Copper	G	
Hastelloy B/B-2	G	
Hastelloy C/C-276	G	
Hastelloy D	G	
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625	G	
Incolloy 800/825		
Lead	U	
Monel 400	G	
Naval Bronze	E	
Nickel 200/201	G	
Ni-Resist	G	
Stainless Steels		
Type 304/347	G	
Type 316/316 L	G	
Type 400 series	G	
Type 904-L		
17-4 PH	G	
20 Cb 3	G	
E-Bright 26-1		
Silicon Bronze	U	
Silicon Copper	G	
Galv. Stl.	G	
Tantalum		
Titanium		
Zirconium		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028912

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PERBORATE 10%



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SODIUM PERBORATE 10%


Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)	R	
CPVC	R	
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6	R	
Nylon 11	R	
Nylon 66	R	
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	R	
Polyethylene UHMW	R	
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1	R	
PVC Type 2		
PVDF (Kynar)	R	
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PERBORATE 10%




*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PEROXIDE 10%

Metals	
Admiralty Brass	U
Aluminum	G
Aluminum Bronze	U
Brass	U
Bronze	U
Carbon Steel	G
Columbium (Niobium)	
Copper	U
Hastelloy B/B-2	G
Hastelloy C/C-276	G
Hastelloy D	G
Hastelloy G/G-3	
High Silicon Iron	G
Inconel 600/625	G
Incolloy 800/825	G
Lead	U
Monel 400	G
Naval Bronze	U
Nickel 200/201	G
Ni-Resist	G
Stainless Steels	
Type 304/347	G
Type 316/316 L	G
Type 400 series	E G
Type 904-L	
17-4 PH	G
20 Cb 3	G
E-Bright 26-1	
Silicon Bronze	U
Silicon Copper	G
Stellite	
Tantalum	S
Titanium	
Zirconium TO 100%	E



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028913


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PEROXIDE 10%




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PEROXIDE 10%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM PEROXIDE 10%



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SODIUM PHOSPHATE ACID



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028914


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PHOSPHATE ACID




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker

SODIUM PHOSPHATE ACID



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PHOSPHATE ACID



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cor

SODIUM PHOSPHATE ALKALINE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			U																									
Aluminum			G																									
Aluminum Bronze			G																									
Brass	ALL		G																									
Bronze			G																									
Carbon Steel			G																									
Columbium (Niobium)																												
Copper			G																									
Hastelloy B/B-2	ALL		G																									
Hastelloy C/C-276	ALL		G																									
Hastelloy D			G																									
Hastelloy G/G-3																												
High Silicon Iron			S																									
Inconel 600/625			G																									
Incolloy 800/825																												
Lead			G																									
Monel 400	ALL		G																									
Naval Bronze			G																									
Nickel 200/201			G																									
Ni-Resist																												
Stainless Steels																												
Type 304/347			G																									
Type 316/316 L	ALL		G																									
Type 400 series			E			G																						
Type 904-L																												
17-4 PH			G																									
20 Cb 3	ALL		G																									
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum			G																									
Titanium			E																									
Zirconium			E																									
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028915

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PHOSPHATE ALKALINE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PHOSPHATE ALKALINE

Plastics		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																							
Acetal																							
Acrylics			R																				
Asbestos Reinforced Epoxy																							
Asbestos Reinforced Phenolic																							
Chlorinated Polyether (Penton)			R																				
CPVC			R																				
E-CTFE (Halar)			R																				
Epoxy			U																				
ETFE (Tefzel)			R																				
FEP			R																				
Furan (Furfural Alcohol)																							
Noryl																							
Nylon 6			R																				
Nylon 11			R																				
Nylon 66			R																				
Phenolic																							
PFA (Teflon)			R																				
Polyamide-Imide																							
Polyesters																							
Bisphenol A–fumarate																							
Halogenated																							
Hydrogenated Bisphenol A –Bisphenol A																							
Isophthalic																							
Terephthalate (PET)																							
Polyetherimide (ULTEM)																							
Polyetheretherketone (PEEK)																							
Polyethersulfone (PES)																							
Polyethylene HMW			R																				
Polyethylene UHMW			R																				
Polymethylpentene																							
Polypropylene (PP)			R																				
Polystyrene																							
Polysulfone																							
Polyvinylidene Chloride			R																				
PVC Type 1			R																				
PVC Type 2																							
PVDF (Kynar)			R																				
Ryton																							
TFE (Teflon)			R																				
Vinyl Ester	10%		R																				
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM PHOSPHATE ALKALINE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.del

SODIUM PHOSPHATE NEUTRAL



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028916

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PHOSPHATE NEUTRAL


Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass	R																				
Carbon	R																				
Carbon-Graphite Resin Impregnated	R																				
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride																					
Silicones	U																				
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM PHOSPHATE NEUTRAL



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			E																									
Aluminum			E																									
Aluminum Bronze			E																									
Brass	ALL		G																									
Bronze			G																									
Carbon Steel			G																									
Columbium (Niobium)			U																									
Copper			S																									
Hastelloy B/B-2	10%		G																									
Hastelloy C/C-276	ALL		G																									
Hastelloy D			G																									
Hastelloy G/G-3																												
High Silicon Iron			G																									
Inconel 600/625			G																									
Incolloy 800/825			E																									
Lead																												
Monel 400	ALL		G																									
Naval Bronze	10–100%		G																									
Nickel 200/201			G																									
Ni-Resist			G																									
Stainless Steels																												
Type 304/347			G																									
Type 316/316 L	ALL		G																									
Type 400 series			E	G																								
Type 904-L																												
17-4 PH			G																									
20 Cb 3	ALL		G																									
E-Bright 26-1																												
Silicon Bronze			U																									
Silicon Copper			G																									
Stellite																												
Tantalum			G																									
Titanium			E																									
Zirconium			E																									
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028917

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM SILICATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.

SODIUM SILICATE


Plastics	°C	°F
ABS	R	
Acetal		
Acrylics	R	
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic	R	
Chlorinated Polyether (Penton)	R	
CPVC	R	
E-CTFE (Halar)	R	
Epoxy	R	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl	R	
Nylon 6	R	
Nylon 11	R	
Nylon 66	R	
Phenolic	R	
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate	R	
Halogenated	R	
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic	U	
Terephthalate (PET)	R	
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	R	
Polyethylene UHMW	R	
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene	R	
Polysulfone	R	
Polyvinylidene Chloride	R	
PVC Type 1	R	
PVC Type 2	R	
PVDF (Kynar)	R	
Ryton ALL	R	
TFE (Teflon)	R	
Vinyl Ester ALL	R	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM SILICATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028918

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM SULFATE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM SULFATE

Plastics		°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238
		°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460
ABS		R
KEL-F (CTFE)		R
Acrylics		R
Asbestos Reinforced Epoxy		R
Asbestos Reinforced Phenolic		R
Chlorinated Polyether (Penton)		R
CPVC		R
E-CTFE (Halar)		R
Epoxy		R
ETFE (Tefzel)		R
FEP		R
Furan (Furfural Alcohol)		R
Noryl		R
Nylon 6		R
Nylon 11		R
Nylon 66		R
Phenolic		R
PFA (Teflon)		R
Polyamide-Imide	10%	R
Polyesters		
Bisphenol A–fumarate		R
Halogenated		R
Hydrogenated Bisphenol A –Bisphenol A		R
Isophthalic		R
Terephthalate (PET)		R
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		R
Polyethylene UHMW		R
Polymethylpentene		
Polypropylene (PP)		R
Polystyrene		
Polysulfone		R
Polyvinylidene Chloride		R
PVC Type 1		R
PVC Type 2		R
PVDF (Kynar)		R
Ryton	ALL	R
TFE (Teflon)		R
Vinyl Ester	ALL	R
		°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460
		°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM SULFATE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SODIUM SULFIDE TO 50%

Metals		°C	°F
Admiralty Brass	G	15–93	60–200
Aluminum	U		
Aluminum Bronze	U		
Brass	U		
Bronze	U		
Carbon Steel	G	15–26	60–80
Columbium (Niobium)	E	15–93	60–200
Copper	U		
Hastelloy B/B-2	G	15–93	60–200
Hastelloy C/C-276	G	15–93	60–200
Hastelloy D	G	15–93	60–200
Hastelloy G/G-3 20%	E	15–49	60–120
High Silicon Iron	G	15–26	60–80
Inconel 600/625	G	15–93	60–200
Incolloy 800/825 SAT	G	15–26	60–80
Lead	S	15–26	60–80
Monel 400	G	15–93	60–200
Naval Bronze	U		
Nickel 200/201	G	15–93	60–200
Ni-Resist	S	15–26	60–80
Stainless Steels			
Type 304/347 1	G	15–93	60–200
Type 316/316 L	G	15–93	60–200
Type 400 series	U		
Type 317/317 L	G	15–93	60–200
Type 321	G		
20 Cb 3	G	15–93	60–200
E-Bright 26-1			
Silicon Bronze	U		
Silicon Copper	U		
Stellite			
Tantalum TO 10%	G	15–93	60–200
Titanium 10%	G	15–93	60–200
Zirconium	U		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120028919

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM SULFIDE TO 50%




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM SULFIDE TO 50%



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c

SODIUM SULFITE 10%

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			G																									
Aluminum			G																									
Aluminum Bronze			U																									
Brass			G																									
Bronze			U																									
Carbon Steel			G																									
Columbium (Niobium)			E																									
Copper			S																									
Hastelloy B/B-2			U																									
Hastelloy C/C-276			G																									
Hastelloy D			U																									
Hastelloy G/G-3																												
High Silicon Iron			U																									
Inconel 600/625			G																									
Incolloy 800/825	5%		E																									
Lead			G																									
Monel 400			G																									
Naval Bronze			G																									
Nickel 200/201			G																									
Ni-Resist			E																									
Stainless Steels																												
Type 304/347			E																									
Type 316/316 L			E																									
Type 400 series			G																									
Type 904-L																												
17-4 PH																												
20 Cb 3			E																									
E-Bright 26-1																												
Silicon Bronze	5%		G																									
Silicon Copper			G																									
Stellite																												
Tantalum	TO SAT		G																									
Titanium	SAT		E																									
Zirconium	TO 33%		E																									
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029041


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM SULFITE 10%




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Ex*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekk

SODIUM SULFITE 10%



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SODIUM SULFITE 10%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cc

SODIUM TETRABORATE



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029042


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM TETRABORATE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekke

SODIUM TETRABORATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM TETRABORATE




*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM THIOSULFATE (HYPO)

Metals	
Admiralty Brass	G
Aluminum	G
Aluminum Bronze	U
Brass	U
Bronze	U
Carbon Steel	U
Columbium (Niobium)	
Copper	U
Hastelloy B/B-2	E
Hastelloy C/C-276	G
Hastelloy D	
Hastelloy G/G-3	
High Silicon Iron	G
Inconel 600/625	E
Incolloy 800/825	
Lead	G
Monel 400	G
Naval Bronze	U
Nickel 200/201	E
Ni-Resist	G
Stainless Steels	
Type 304/347	E
Type 316/316 L	E
Type 400 series	E S
Type 904-L	
17-4 PH	
20 Cb 3	E
E-Bright 26-1	
Silicon Bronze	U
Silicon Copper	U
Galv. Stl.	U
Tantalum TO 25%	E
Titanium 25%	E
Zirconium	



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029043

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM THIOSULFATE (HYPO)




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and E*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekk

SODIUM THIOSULFATE (HYPO)

Plastics		°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238
		°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460
ABS		R
Acetal		R
Acrylics		R
KEL-F (CTFE)		R
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		R
CPVC		R
E-CTFE (Halar)		R
Epoxy		R
ETFE (Tefzel)		R
FEP		R
Furan (Furfural Alcohol)		R
Noryl		R
Nylon 6		R
Nylon 11	TO 15%	R
Nylon 66		R
Phenolic		R
PFA (Teflon)		R
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		R
Halogenated		R
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		R
Terephthalate (PET)		R
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		R
Polyethylene UHMW		R
Polymethylpentene		
Polypropylene (PP)		R
Polystyrene		
Polysulfone		R
Polyvinylidene Chloride		R
PVC Type 1		R
PVC Type 2		R
PVDF (Kynar)		R
Ryton	ALL	R
TFE (Teflon)		R
Vinyl Ester	ALL	R U
		°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460
		°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SODIUM THIOSULFATE (HYPO)



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker

SOUR CRUDE OIL

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum																												
Aluminum Bronze			G																									
Brass																												
Bronze			E																									
Carbon Steel			G																									
Columbium (Niobium)																												
Copper																												
Hastelloy B/B-2			E																									
Hastelloy C/C-276			E																									
Hastelloy D	58%		G																									
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625																												
Incolloy 800/825																												
Lead																												
Monel 400			E																									
Naval Bronze			S																									
Nickel 200/201																												
Ni-Resist																												
Stainless Steels																												
Type 304/347																												
Type 316/316 L			E																									
Type 400 series			G																									
Type 904-L																												
17-4 PH			G																									
20 Cb 3			E																									
E-Bright 26-1																												
Silicon Bronze			G																									
Silicon Copper																												
Stellite			E																									
Tantalum																												
Titanium																												
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029044

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOUR CRUDE OIL



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekke



© 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SOUR CRUDE OIL

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)		U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)		R																				
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		U																				
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)		U																				
Ethylene-Propylene Terpolymer (EPT)		U																				
FKM (Viton A)		R																				
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)		U																				
Kalrez (FPM)		R																				
Koroseal																						
Natural Rubber (GRS)		U																				
Neoprene GR-M (CR)		U																				
Nitrile Buna-N (NBR)		R																				
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)		U																				
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekke

SOYBEAN OIL



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029045

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOYBEAN OIL




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SOYBEAN OIL



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SPECULUM PLATING SOLUTION

Metals	°C	°F
Admiralty Brass		
Aluminum		
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper		
Hastelloy B/B-2		
Hastelloy C/C-276		
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825		
Lead		
Monel 400		
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347		
Type 316/316 L		
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3		
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		
Tantalum		
Titanium		
Zirconium		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029046

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SPECULUM PLATING SOLUTION

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon																					
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride																					
Silicones																					
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expana*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SPECULUM PLATING SOLUTION

Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)		
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)		
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)		
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cor

STANNIC CHLORIDE

Metals		°C	°F
Admiralty Brass			
Aluminum		U	
Aluminum Bronze		U	
Brass		U	
Bronze		U	
Carbon Steel		U	
Columbium (Niobium)			
Copper		U	
Hastelloy B/B-2	10–50%	G	
Hastelloy C/C-276	TO 50%	G	
Hastelloy D			
Hastelloy G/G-3			
High Silicon Iron		U	
Inconel 600/625		U	
Incolloy 800/825		U	
Lead		U	
Monel 400		U	
Naval Bronze		U	
Nickel 200/201		U	
Ni-Resist			
Stainless Steels			
Type 304/347		U	
Type 316/316 L		U	
Type 400 series		U	
Type 317/317 L		U	
17-4 PH		U	
20 Cb 3		U	
E-Bright 26-1			
Silicon Bronze		U	
Silicon Copper		U	
Stellite			
Tantalum		G	
Titanium	20%	E	
Zirconium	24%	E	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029047

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STANNIC CHLORIDE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STANNIC CHLORIDE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

STANNOUS CHLORIDE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum		U																										
Aluminum Bronze		U																										
Brass		U																										
Bronze		U																										
Carbon Steel		U																										
Columbium (Niobium)																												
Copper		U																										
Hastelloy B/B-2	1	G																										
Hastelloy C/C-276		G																										
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron		S																										
Inconel 600/625	DRY	G																										
Incolloy 800/825	5%	E																										
Lead		U																										
Monel 400	DRY	G																										
Naval Bronze		U																										
Nickel 200/201	DRY	G																										
Ni-Resist																												
Stainless Steels																												
Type 304/347		U																										
Type 316/316 L	10%	E																										
Type 400 series		U																										
Type 904-L																												
17-4 PH																												
20 Cb 3	10%	E																										
E-Bright 26-1	10%	G																										
Silicon Bronze		U																										
Silicon Copper	5%	G																										
Stellite																												
Tantalum		G																										
Titanium	SAT	E																										
Zirconium	TO 70%	G																										
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029048

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STANNOUS CHLORIDE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cor

STANNOUS CHLORIDE

Plastics		°C	°F
ABS	R	15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238	60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460
KEL-F (CTFE)	R		
Acrylics	R		
Asbestos Reinforced Epoxy			
Asbestos Reinforced Phenolic			
Chlorinated Polyether (Penton)	R		
CPVC	R		
E-CTFE (Halar)	R		
Epoxy	R		
ETFE (Tefzel)	R		
FEP	R		
Furan (Furfural Alcohol)	R		
Noryl	R		
Nylon 6	U		
Nylon 11 DRY	R		
Nylon 66	U		
Phenolic			
PFA (Teflon)	R		
Polyamide-Imide			
Polyesters			
Bisphenol A–fumarate	R		
Halogenated	R		
Hydrogenated Bisphenol A –Bisphenol A			
Isophthalic	R		
Terephthalate (PET)	R		
Polyetherimide (ULTEM)			
Polyetheretherketone (PEEK)			
Polyethersulfone (PES)			
Polyethylene HMW	R		
Polyethylene UHMW	R		
Polymethylpentene			
Polypropylene (PP)	R		
Polystyrene			
Polysulfone			
Polyvinylidene Chloride	R		
PVC Type 1	R		
PVC Type 2	R		
PVDF (Kynar)	R		
Ryton ALL	R		
TFE (Teflon)	R		
Vinyl Ester ALL	R		
	°F	60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460	
	°C	15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238	

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STANNOUS CHLORIDE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekke

STANNOUS FLUORIDE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L TO 50%	G																										
Type 400 series																											
Type 317/317 L	G																										
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029049

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STANNOUS FLUORIDE

	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STANNOUS FLUORIDE

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)	R	
FEP		
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)		
Ryton		
TFE (Teflon)		
Vinyl Ester		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STANNOUS FLUORIDE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)		R	R	R	R	R	R	R	R													
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029050

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STARCH


Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


STARCH



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cc

STEAM, HIGH PRESSURE



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029053

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STEAM, HIGH PRESSURE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		U																				
Silicones		U																				
Urethanes		U																				
Vinyls		U																				
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STEAM, HIGH PRESSURE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC	U																					
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)	U																					
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride	U																					
PVC Type 1	U																					
PVC Type 2	U																					
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	U																					
Vinyl Ester	U																					
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


STEAM, HIGH PRESSURE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																					
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)	U																					
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)	U																					
Nitrile Buna-N (NBR)	U																					
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)	U																					
SBR Styrene (Buna-S)																						
Silicone Rubbers	U																					
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.del

STEAM, LOW PRESSURE



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029051


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STEAM, LOW PRESSURE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated		R																				
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		U																				
Silicones		U																				
Urethanes																						
Vinyls		U																				
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dek

STEAM, LOW PRESSURE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STEAM, LOW PRESSURE

Elastomers* and Linings	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																					
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)	U																					
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)	U																					
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)	U																					
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)	U																					
Neoprene GR-M (CR)	U																					
Nitrile Buna-N (NBR)	U																					
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)	U																					
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STEAM, MEDIUM PRESSURE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze	G																										
Brass	G																										
Bronze	G																										
Carbon Steel	G																										
Columbium (Niobium)																											
Copper	G																										
Hastelloy B/B-2																											
Hastelloy C/C-276	G																										
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625	E																										
Incolloy 800/825																											
Lead																											
Monel 400	E																										
Naval Bronze	E																										
Nickel 200/201	E																										
Ni-Resist																											
Stainless Steels																											
Type 304/347	G																										
Type 316/316 L	G																										
Type 400 series	G																										
Type 904-L																											
17-4 PH	G																										
20 Cb 3	G																										
E-Bright 26-1																											
Silicon Bronze	G																										
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium	E																										
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029052

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STEAM, MEDIUM PRESSURE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		U																				
Silicones		U																				
Urethanes																						
Vinyls		U																				
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

STEAM, MEDIUM PRESSURE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC	U																					
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)	R																					
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)	R																					
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)	U																					
Polystyrene																						
Polysulfone	U																					
Polyvinylidene Chloride	U																					
PVC Type 1	U																					
PVC Type 2	U																					
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STEAM, MEDIUM PRESSURE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																					
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)	U																					
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)	U																					
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)	U																					
Nitrile Buna-N (NBR)	U																					
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers	U																					
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029054


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STEARIC ACID




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STEARIC ACID



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STODDARD'S SOLVENT

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G																									
Aluminum Bronze																											
Brass		G																									
Bronze		G																									
Carbon Steel		G																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276		E																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400		G																									
Naval Bronze		E	G																								
Nickel 200/201		G																									
Ni-Resist		E																									
Stainless Steels																											
Type 304/347		G																									
Type 316/316 L		G																									
Type 400 series																											
Type 904-L																											
17-4 PH		G																									
20 Cb 3		G																									
E-Bright 26-1																											
Silicon Bronze		G																									
Silicon Copper																											
Stellite		G																									
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029055

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STODDARD'S SOLVENT

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass		R																				
Carbon		R																				
Carbon-Graphite Resin Impregnated		R																				
Ceramics		R																				
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones		U																				
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STODDARD'S SOLVENT


Plastics	°C	°F
ABS	R	
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC	U	
E-CTFE (Halar)	R	
Epoxy	R	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)		
Noryl	U	
Nylon 6	R	
Nylon 11	R	
Nylon 66	R	
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide	R	
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic	R	
Terephthalate (PET)	R	
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	U	
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone	R	
Polyvinylidene Chloride	R	
PVC Type 1	R	
PVC Type 2	U	
PVDF (Kynar)	R	
Ryton		
TFE (Teflon)	R	
Vinyl Ester	R	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STODDARD'S SOLVENT



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expa*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029056

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STYRENE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

STYRENE

Plastics	°C	°F
Polyphenylene Oxide	U	
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC	U	
E-CTFE (Halar)		
Epoxy	R	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate	R	
Halogenated	U	
Hydrogenated Bisphenol A –Bisphenol A	R	
Isophthalic	U	
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)	R	
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride	R	
PVC Type 1	U	
PVC Type 2	U	
PVDF (Kynar)	R	
Ryton	R	
TFE (Teflon)	R	
Vinyl Ester	R	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


STYRENE

Elastomers* and Linings	°C	°F
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)		
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U	
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)	U	
Ethylene-Propylene Terpolymer (EPT)	U	
FKM (Viton A)	R	
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)	U	
Nitrile Buna-N (NBR)	U	
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers	U	
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029057

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SUCCINIC ACID

	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.de



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SUCCINIC ACID

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	R																				
Ethylene-Propylene Terpolymer (EPT)	R																				
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)	R																				
Nordel (EPDM)	R																				
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SUGAR SOLUTION



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029058

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SUGAR SOLUTION

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass		R																				
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		R																				
Silicones																						
Urethanes		U																				
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SUGAR SOLUTION

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC	R																					
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)	R																					
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1	R																					
PVC Type 2	R																					
PVDF (Kynar)	R																					
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SUGAR SOLUTION



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029059

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFAMIC ACID


Nonmetallic Materials		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																							
Carbon																							
Carbon-Graphite Resin Impregnated																							
Ceramics																							
Coatings																							
Acrylic																							
Asphalt																							
Chlorinated Rubber																							
Coal Tar																							
Coal Tar Epoxy			U																				
Epoxy General Purpose																							
Epoxy Chemical Resistant																							
Epoxy Polyamide			U																				
Oil Base (Alkyd, Epoxy, Urethane)																							
Phenolic																							
Polyester	25%		R																				
Polyvinyl Chloride																							
Silicones																							
Urethanes																							
Vinyls	25%		R																				
Water Base																							
Zinc Rich																							
Mortars																							
Silicate																							
Sodium Silicate	25%		R																				
Potassium Silicate																							
Silica																							
Sulfur	25%		U																				
Furan Resin	25%		R																				
Polyester	25%		R																				
Epoxy	25%		U																				
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFAMIC ACID



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029060


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFATE LIQUORS

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFATE LIQUORS




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFATE LIQUORS



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029062

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFITE LIQUORS



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFITE LIQUORS


Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)	R	
CPVC	R	
E-CTFE (Halar)	R	
Epoxy	R	
ETFE (Tefzel)		
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate	R	
Halogenated	R	
Hydrogenated Bisphenol A –Bisphenol A	R	
Isophthalic	R	
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1	R	
PVC Type 2	R	
PVDF (Kynar)	R	
Ryton		
TFE (Teflon)	R	
Vinyl Ester	R	U

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFITE LIQUORS



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum																												
Aluminum Bronze																												
Brass																												
Bronze																												
Carbon Steel																												
Columbium (Niobium)																												
Copper																												
Hastelloy B/B-2																												
Hastelloy C/C-276	50%	E	E	E	E	E	E																					
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625																												
Incolloy 800/825																												
Lead																												
Monel 400																												
Naval Bronze																												
Nickel 200/201																												
Ni-Resist																												
Stainless Steels																												
Type 304/347																												
Type 316/316 L																												
Type 400 series																												
Type 904-L																												
17-4 PH																												
20 Cb 3																												
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum																												
Titanium																												
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029062


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFONATED DETERGENTS



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFONATED DETERGENTS



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SULFONATED DETERGENTS

Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)		
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)		
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)		
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029063

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		U																				
Acetal		U																				
KEL-F (CTFE)		R																				
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)		R																				
CPVC		R																				
E-CTFE (Halar)		R																				
Epoxy		R																				
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)		R																				
Noryl		R																				
Nylon 6		R																				
Nylon 11		R																				
Nylon 66		R																				
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated		R																				
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic		R																				
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		R																				
Polyethylene UHMW		R																				
Polymethylpentene																						
Polypropylene (PP)		R																				
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride		R																				
PVC Type 1		R																				
PVC Type 2		R																				
PVDF (Kynar)		R																				
Ryton		R																				
TFE (Teflon)		R																				
Vinyl Ester		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SULFUR

Elastomers* and Linings	°C	°F
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)	R	
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R	
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)	R	
Ethylene-Propylene Terpolymer (EPT)	U	
FKM (Viton A)	U	
Hard Rubber		
Soft Rubber		
Isoprene (IR)	U	
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)	U	
Neoprene GR-M (CR)	R	
Nitrile Buna-N (NBR)	U	
Nordel (EPDM)	R	
Polybutadiene (BR)		
Polyester (PE)	R	
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers	U	
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029064

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR CHLORIDE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFUR CHLORIDE

Plastics	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
ABS																						
Acetal																						
Acrylics		U																				
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)		U																				
CPVC		R																				
E-CTFE (Halar)		R																				
Epoxy		U																				
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)		R																				
Noryl																						
Nylon 6		R																				
Nylon 11		R																				
Nylon 66		R																				
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate		R																				
Halogenated		U																				
Hydrogenated Bisphenol A																						
–Bisphenol A VAPOR		U																				
Isophthalic		U																				
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		U																				
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)		U																				
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride		U																				
PVC Type 1		R				U																
PVC Type 2																						
PVDF (Kynar)		R																				
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester VAPOR		U																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR CHLORIDE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)	U																				
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum		G	—																								
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029065

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DICHLORIDE

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon																					
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride																					
Silicones																					
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DICHLORIDE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate	U																					
Halogenated	U																					
Hydrogenated Bisphenol A																						
–Bisphenol A VAPOR	U																					
Isophthalic VAPOR	U																					
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)	U																					
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride	U																					
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)	R																					
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester VAPOR	U																					
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DICHLORIDE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DIOXIDE DRY

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass		G																									
Aluminum		G																									
Aluminum Bronze		G																									
Brass		G																									
Bronze		G																									
Carbon Steel		E				G																					
Columbium (Niobium)		E																									
Copper		G																									
Hastelloy B/B-2		U																									
Hastelloy C/C-276		G																									
Hastelloy D		U																									
Hastelloy G/G-3																											
High Silicon Iron		G																									
Inconel 600/625		G																									
Incolloy 800/825		E																									
Lead		G																									
Monel 400		G																									
Naval Bronze		S																									
Nickel 200/201		G																									
Ni-Resist		G																									
Stainless Steels																											
Type 304/347	9	G																									
Type 316/316 L		G																									
Type 400 series		G																									
Type 904-L																											
17-4 PH		G																									
20 Cb 3		G																									
E-Bright 26-1																											
Silicon Bronze		G																									
Silicon Copper		G																									
Stellite		G																									
Tantalum		G																									
Titanium		E																									
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029066

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DIOXIDE DRY



Schweitzer/Corrosion Resistance Tables: Fifth Edition, Revised and Expanded

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DIOXIDE DRY

Plastics	
ABS	R
Acetal	U
Acrylics	R
Asbestos Reinforced Epoxy	R
Asbestos Reinforced Phenolic	R
Chlorinated Polyether (Penton)	R
CPVC	R
E-CTFE (Halar)	R
Epoxy	R
ETFE (Tefzel)	R
FEP	R
Furan (Furfural Alcohol)	R
KEL-F (CTFE)	R
Nylon 6	U
Nylon 11	R
Nylon 66	U
Phenolic	R
PFA (Teflon)	R
Polyamide-Imide	
Polyesters	
Bisphenol A–fumarate	R
Halogenated	R
Hydrogenated Bisphenol A –Bisphenol A	R
Isophthalic	R
Terephthalate (PET)	R
Polyetherimide (ULTEM)	
Polyetheretherketone (PEEK)	R
Polyethersulfone (PES)	U
Polyethylene HMW	R
Polyethylene UHMW	R
Polymethylpentene	
Polypropylene (PP)	R U
Polystyrene	
Polysulfone	
Polyvinylidene Chloride	R
PVC Type 1	R
PVC Type 2	R
PVDF (Kynar)	R
Ryton	R
TFE (Teflon)	R
Vinyl Ester	R

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DIOXIDE DRY

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	R																				
Ethylene-Propylene Terpolymer (EPT)	R																				
FKM (Viton A)	U																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal	R																				
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)	U																				
Polyester (PE)	R																				
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)	U																				
Silicone Rubbers	R																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DIOXIDE WET

Metals		°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass		U																									
Aluminum		U																									
Aluminum Bronze		U																									
Brass		U																									
Bronze		U																									
Carbon Steel		U																									
Columbium (Niobium)		E																									
Copper		U																									
Hastelloy B/B-2		U																									
Hastelloy C/C-276		E							G																		
Hastelloy D		U																									
Hastelloy G/G-3		E																									
High Silicon Iron		S																									
Inconel 600/625		U																									
Incolloy 800/825		G																									
Lead		G																									
Monel 400		U																									
Naval Bronze		G																									
Nickel 200/201		U																									
Ni-Resist																											
Stainless Steels																											
Type 304/347		U																									
Type 316/316 L		G																									
Type 410	1	U																									
Type 904-L																											
17-4 PH		U																									
20 Cb 3		G																									
E-Bright 26-1		E																									
Silicon Bronze		G																									
Silicon Copper		G																									
Stellite																											
Tantalum		G																									
Titanium		U																									
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029067

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DIOXIDE WET




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR DIOXIDE WET



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR OXYCHLORIDE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347	G																										
Type 316/316 L	G																										
Type 400 series																											
Type 317/317 L	G																										
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029068

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR OXYCHLORIDE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFUR OXYCHLORIDE

Plastics	°F	°C
ABS	60–460	15–238
Acetal	60–460	15–238
Acrylics	60–460	15–238
Asbestos Reinforced Epoxy	60–460	15–238
Asbestos Reinforced Phenolic	60–460	15–238
Chlorinated Polyether (Penton)	60–460	15–238
CPVC	60–460	15–238
E-CTFE (Halar)	60–460	15–238
Epoxy	60–460	15–238
ETFE (Tefzel)	60–460	15–238
FEP	60–460	15–238
Furan (Furfural Alcohol)	60–460	15–238
Noryl	60–460	15–238
Nylon 6	60–460	15–238
Nylon 11	60–460	15–238
Nylon 66	60–460	15–238
Phenolic	60–460	15–238
PFA (Teflon)	60–460	15–238
Polyamide-Imide	60–460	15–238
Polyesters	60–460	15–238
Bisphenol A–fumarate	60–460	15–238
Halogenated	60–460	15–238
Hydrogenated Bisphenol A –Bisphenol A	60–460	15–238
Isophthalic	60–460	15–238
Terephthalate (PET)	60–460	15–238
Polyetherimide (ULTEM)	60–460	15–238
Polyetheretherketone (PEEK)	60–460	15–238
Polyethersulfone (PES)	60–460	15–238
Polyethylene HMW	60–460	15–238
Polyethylene UHMW	60–460	15–238
Polymethylpentene	60–460	15–238
Polypropylene (PP)	60–460	15–238
Polystyrene	60–460	15–238
Polysulfone	60–460	15–238
Polyvinylidene Chloride	60–460	15–238
PVC Type 1	60–460	15–238
PVC Type 2	60–460	15–238
PVDF (Kynar)	60–460	15–238
Ryton	60–460	15–238
TFE (Teflon)	60–460	15–238
Vinyl Ester	60–460	15–238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR OXYCHLORIDE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029069

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR TRIOXIDE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUR TRIOXIDE

Plastics		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS			U																				
Acetal																							
Acrylics																							
Asbestos Reinforced Epoxy			R																				
Asbestos Reinforced Phenolic																							
Chlorinated Polyether (Penton)			R																				
CPVC			R																				
E-CTFE (Halar)			R																				
Epoxy			U																				
ETFE (Tefzel)			R																				
FEP	14		R																				
Furan (Furfural Alcohol)			U																				
Noryl																							
Nylon 6			U																				
Nylon 11			U																				
Nylon 66			U																				
Phenolic			R																				
PFA (Teflon)	14		R																				
Polyamide-Imide																							
Polyesters																							
Bisphenol A–fumarate			R																				
Halogenated			R				U																
Hydrogenated Bisphenol A –Bisphenol A																							
Isophthalic			R																				
Terephthalate (PET)			R																				
Polyetherimide (ULTEM)																							
Polyetheretherketone (PEEK)																							
Polyethersulfone (PES)																							
Polyethylene HMW			U																				
Polyethylene UHMW																							
Polymethylpentene																							
Polypropylene (PP)			U																				
Polystyrene																							
Polysulfone																							
Polyvinylidene Chloride			R																				
PVC Type 1			R																				
PVC Type 2			R																				
PVDF (Kynar)			U																				
Ryton																							
TFE (Teflon)	14		R																				
Vinyl Ester			R																				
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SULFUR TRIOXIDE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cc

SULFURIC ACID 10%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029070

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 10%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFURIC ACID 10%

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		R																				
Acetal		U																				
Acrylics		R																				
Asbestos Reinforced Epoxy		R																				
Asbestos Reinforced Phenolic		R																				
Chlorinated Polyether (Penton)		R																				
CPVC		R																				
E-CTFE (Halar)		R																				
Epoxy		R				U																
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)		R																				
Noryl		R																				
Nylon 6		U																				
Nylon 11		R																				
Nylon 66		U																				
Phenolic		R																				
PFA (Teflon)		R																				
Polyamide-Imide		R																				
Polyesters																						
Bisphenol A–fumarate		R																				
Halogenated		R																				
Hydrogenated Bisphenol A –Bisphenol A		R																				
Isophthalic		R																				
Terephthalate (PET)		R																				
Polyetherimide (ULTEM)		R																				
Polyetheretherketone (PEEK)		R																				
Polyethersulfone (PES)		R																				
Polyethylene HMW		R																				
Polyethylene UHMW		R																				
Polymethylpentene		R																				
Polypropylene (PP)		R																				
Polystyrene		R																				
Polysulfone		R																				
Polyvinylidene Chloride		R																				
PVC Type 1		R																				
PVC Type 2		R																				
PVDF (Kynar)		R																				
Ryton		R																				
TFE (Teflon)		R																				
Vinyl Ester		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 10%




*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFURIC ACID 30%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029071

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 30%




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SULFURIC ACID 30%

Plastics		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS	R																						
Acetal	U																						
Acrylics	R																						
Asbestos Reinforced Epoxy	U																						
Asbestos Reinforced Phenolic	R																						
Chlorinated Polyether (Penton)	R																						
CPVC	R																						
E-CTFE (Halar)	R																						
Epoxy	R																						
ETFE (Tefzel)	R																						
FEP	R																						
Furan (Furfural Alcohol)	R																						
Noryl	R																						
Nylon 6	U																						
Nylon 11	U																						
Nylon 66	U																						
Phenolic	R																						
PFA (Teflon)	R																						
Polyamide-Imide	R																						
Polyesters																							
Bisphenol A–fumarate	R																						
Halogenated	R																						
Hydrogenated Bisphenol A –Bisphenol A	R																						
Isophthalic	R																						
Terephthalate (PET)	R																						
Polyetherimide (ULTEM)	R																						
Polyetheretherketone (PEEK)	R																						
KEL-F (CTFE)	R																						
Polyethylene HMW	R																						
Polyethylene UHMW	R																						
Polymethylpentene	R																						
Polypropylene (PP)	R																						
Polystyrene	R																						
Polysulfone	R																						
Polyvinylidene Chloride	R																						
PVC Type 1	R																						
PVC Type 2	R																						
PVDF (Kynar)	R																						
Ryton	R																						
TFE (Teflon)	R																						
Vinyl Ester	R																						
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 30%




*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 50%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029072


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 50%




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 50%



*See also Nylon 11 under PLASTICS.

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 60%

Metals	°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293
	°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560
Admiralty Brass	U
Aluminum	U
Aluminum Bronze	U
Brass	U
Bronze	U
Carbon Steel	U
Columbium (Niobium)	G U
Copper	U
Hastelloy B/B-2	E — G
Hastelloy C/C-276	E — U
Hastelloy D	E — G
Hastelloy G/G-3	
High Silicon Iron	E — G
Inconel 600/625	U
Incolloy 825	G — U
Lead	G
Monel 400	G — S
Naval Bronze	U
Nickel 200/201	S
Alloy Al 6XN	G
Stainless Steels	
Type 304/347	U
Type 316/316 L	U
Type 400 series	U
Type 904-L	G
17-4 PH	U
20 Cb 3	E — S — U
E-Bright 26-1	U
Silicon Bronze	U
Silicon Copper	U
Stellite	U
Tantalum	G
Titanium	U
Zirconium	E — G
	°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560
	°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029073

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 60%



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SULFURIC ACID 60%

Plastics	
ABS	U
Acetal	U
Acrylics	R
Asbestos Reinforced Epoxy	U
Asbestos Reinforced Phenolic	R
Chlorinated Polyether (Penton)	R
CPVC	R
E-CTFE (Halar)	R
Epoxy	R
ETFE (Tefzel)	R
FEP	R
Furan (Furfural Alcohol)	R
Noryl	R
Nylon 6	U
Nylon 11	U
Nylon 66	U
Phenolic	R
PFA (Teflon)	R
KEL-F (CTFE)	R
Polyesters	
Bisphenol A–fumarate	R
Halogenated	R
Hydrogenated Bisphenol A –Bisphenol A	R
Isophthalic	U
Terephthalate (PET)	U
Polyetherimide (ULTEM)	U
Polyetheretherketone (PEEK)	U
Polyethersulfone (PES)	U
Polyethylene HMW	R
Polyethylene UHMW	R
Polymethylpentene	R
Polypropylene (PP)	R
Polystyrene	R
Polysulfone	U
Polyvinylidene Chloride	U
PVC Type 1	R
PVC Type 2	R
PVDF (Kynar)	R
Ryton	R
TFE (Teflon)	R
Vinyl Ester	R

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SULFURIC ACID 60%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SULFURIC ACID 70%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029074

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 70%



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 70%


Plastics	°C	°F
ABS	U	
Acetal	U	
Acrylics	R	
Asbestos Reinforced Epoxy	U	
Asbestos Reinforced Phenolic	R–U	
Chlorinated Polyether (Penton)	R	
CPVC	R	
E-CTFE (Halar)	R	
Epoxy	R–U	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl	R	
Nylon 6	U	
Nylon 11	U	
Nylon 66	U	
Phenolic	R	
PFA (Teflon)	R	
KEL-F (CTFE)	R	
Polyesters		
Bisphenol A–fumarate	R	
Halogenated	R–U	
Hydrogenated Bisphenol A –Bisphenol A	R	
Isophthalic	U	
Terephthalate (PET)	U	
Polyetherimide (ULTEM)	U	
Polyetheretherketone (PEEK)	U	
Polyethersulfone (PES)	U	
Polyethylene HMW	R	
Polyethylene UHMW	R	
Polymethylpentene	R	
Polypropylene (PP)	R	
Polystyrene	R	
Polysulfone	U	
Polyvinylidene Chloride	U	
PVC Type 1	R	
PVC Type 2	R	
PVDF (Kynar)	R	
Ryton	R	
TFE (Teflon)	R	
Vinyl Ester	R	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 70%




*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 80%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029075

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 80%




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SULFURIC ACID 80%



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFURIC ACID 90%



Metals

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029076

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 90%



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 90%


Plastics	
ABS	U
Acetal	U
Acrylics	U
Asbestos Reinforced Epoxy	U
Asbestos Reinforced Phenolic	R–U
Chlorinated Polyether (Penton)	R
CPVC	R
E-CTFE (Halar)	R
Epoxy	U
ETFE (Tefzel)	R
FEP	R
Furan (Furfural Alcohol)	U
Noryl	R
Nylon 6	U
Nylon 11	U
Nylon 66	U
Phenolic	R
PFA (Teflon)	R
KEL-F (CTFE)	R
Polyesters	
Bisphenol A–fumarate	U
Halogenated	U
Hydrogenated Bisphenol A –Bisphenol A	U
Isophthalic	U
Terephthalate (PET)	U
Polyetherimide (ULTEM)	U
Polyetheretherketone (PEEK)	U
Polyethersulfone (PES)	U
Polyethylene HMW	U
Polyethylene UHMW	U
Polymethylpentene	R
Polypropylene (PP)	R
Polystyrene	
Polysulfone	U
Polyvinylidene Chloride	U
PVC Type 1	R
PVC Type 2	U
PVDF (Kynar)	R
Ryton	R
TFE (Teflon)	R
Vinyl Ester	U

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SULFURIC ACID 90%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFURIC ACID 95%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029077

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 95%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 95%

Plastics	
ABS	U
Acetal	U
Acrylics	U
Asbestos Reinforced Epoxy	U
Asbestos Reinforced Phenolic	U
Chlorinated Polyether (Penton)	R
CPVC	R
E-CTFE (Halar)	R
Epoxy	U
ETFE (Tefzel)	R
FEP	R
Furan (Furfural Alcohol)	U
Noryl	R
Nylon 6	U
Nylon 11	U
Nylon 66	U
Phenolic	U
PFA (Teflon)	R
KEL-F (CTFE)	R
Polyesters	
Bisphenol A–fumarate	U
Halogenated	U
Hydrogenated Bisphenol A –Bisphenol A	U
Isophthalic	U
Terephthalate (PET)	U
Polyetherimide (ULTEM)	U
Polyetheretherketone (PEEK)	U
Polyethersulfone (PES)	U
Polyethylene HMW	U
Polyethylene UHMW	U
Polymethylpentene	R
Polypropylene (PP)	R U
Polystyrene	
Polysulfone	U
Polyvinylidene Chloride	U
PVC Type 1	R
PVC Type 2	U
PVDF (Kynar)	R
Ryton	
TFE (Teflon)	R
Vinyl Ester	U

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 95%

Elastomers* and Linings	°C	°F
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)	U	
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)	R	
Chloro-Isobutene-Isoprene (CIIR)	U	
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R	
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)	R	
Ethylene-Propylene-Diene (EPDM)	U	
Ethylene-Propylene Terpolymer (EPT)	U	
FKM (Viton A)	R	
Hard Rubber	U	
Soft Rubber	U	
Isoprene (IR)	U	
Kalrez (FPM)	R	
Koroseal	U	
Natural Rubber (GRS)	U	
Neoprene GR-M (CR)	U	
Nitrile Buna-N (NBR)	U	
Nordel (EPDM)	U	
Polybutadiene (BR)		
Polyester (PE)	U	
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)	U	
Polyurethane (AU)	U	
SBR Styrene (Buna-S)	U	
Silicone Rubbers	U	
Fabrics		
Cotton	U	
Felt (Wool)	U	
Rayon Viscose	U	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFURIC ACID 98%

Metals	°F	°C
Admiralty Brass	U	
Aluminum	U	
Aluminum Bronze	U	
Brass	U	
Bronze	U	
Carbon Steel	S	
Columbium (Niobium)	E	
Copper	U	
Hastelloy B/B-2	G	U
Hastelloy C/C-276	E	G
Hastelloy D	G	U
Hastelloy G/G-3	E	
High Silicon Iron	E	
Inconel 600/625	U	
Incolloy 825	G	U
Lead	E	
Monel 400	U	
Naval Bronze	U	
Nickel 200/201	U	
Type 321	U	
Stainless Steels		
Type 304/347 9	G	
Type 316/316 L 9	G	
Type 400 series	U	
Type 317/317 L	U	
17-4 PH	E	G
20 Cb 3	E	G
E-Bright 26-1	E	
Silicon Bronze	U	
Silicon Copper	U	
Stellite	U	
Tantalum	G	U
Titanium	U	
Zirconium	U	

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 480 500 520 540 560

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 249 260 271 282 293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029078


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 98%

Nonmetallic Materials	
Borosilicate Glass	R
Carbon	U
Carbon-Graphite Resin Impregnated	U
Ceramics	U
Coatings	
Acrylic	U
Asphalt	
Chlorinated Rubber	
Coal Tar	U
Coal Tar Epoxy	U
Epoxy General Purpose	U
Epoxy Chemical Resistant	U
Epoxy Polyamide	U
Oil Base (Alkyd, Epoxy, Urethane)	
Phenolic	U
Polyester	U
Polyvinyl Chloride	U
Silicones	U
Urethanes	U
Vinyls	U
Water Base	
Zinc Rich	
Mortars	
Silicate	U
Sodium Silicate	R
Potassium Silicate	
Silica	
Sulfur	U
Furan Resin	U
Polyester	U
Epoxy	U

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


SULFURIC ACID 98%

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R			U																	
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)	R																				
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R																				
Hard Rubber	U																				
Soft Rubber	U																				
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal	U																				
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)	U																				
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)	U																				
Polyurethane (AU)	U																				
SBR Styrene (Buna-S)	U																				
Silicone Rubbers	U																				
Fabrics																					
Cotton	U																				
Felt (Wool)	U																				
Rayon Viscose	U																				
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 100%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029079


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 100%

Nonmetallic Materials	
Borosilicate Glass	R
Carbon	U
Carbon-Graphite Resin Impregnated	U
Ceramics	U
Coatings	
Acrylic	U
Asphalt	
Chlorinated Rubber	
Coal Tar	U
Coal Tar Epoxy	U
Epoxy General Purpose	U
Epoxy Chemical Resistant	U
Epoxy Polyamide	U
Oil Base (Alkyd, Epoxy, Urethane)	
Phenolic	U
Polyester	U
Polyvinyl Chloride	U
Silicones	U
Urethanes	U
Vinyls	U
Water Base	
Zinc Rich	
Mortars	
Silicate	R
Sodium Silicate	
Potassium Silicate	
Silica	
Sulfur	
Furan Resin	
Polyester	
Epoxy	

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 100%

Elastomers* and Linings	
Acrylate-Butadiene (ABR)	
Butyl GR-1 (IIR)	U
Carboxylic-Acrylonitrile-Butadiene (XNBR)	
Chemraz (FPM)	R
Chloro-Isobutene-Isoprene (CIIR)	U
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U
Ethylene-Acrylic (EA)	
Ethylene-Propylene (EPM)	R
Ethylene-Propylene-Diene (EPDM)	U
Ethylene-Propylene Terpolymer (EPT)	U
FKM (Viton A)	R
Hard Rubber	U
Soft Rubber	U
Isoprene (IR)	U
Kalrez (FPM)	
Koroseal	U
Natural Rubber (GRS)	U
Neoprene GR-M (CR)	U
Nitrile Buna-N (NBR)	U
Nordel (EPDM)	
Polybutadiene (BR)	
Polyester (PE)	U
Polyether-Urethane (EU)	
Polyisoprene (IR)	
Polysulfides (T)	U
Polyurethane (AU)	U
SBR Styrene (Buna-S)	U
Silicone Rubbers	U
Fabrics	
Cotton	U
Felt (Wool)	U
Rayon Viscose	U

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 103%

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron	U																										
Inconel 600/625	U																										
Incolloy 800/825																											
Lead																											
Monel 400	U																										
Naval Bronze																											
Nickel 200/201	U																										
Ni-Resist																											
Stainless Steels																											
Type 304/347	U																										
Type 316/316 L	G																										
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum	U																										
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029080

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 103%

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass		R																				
Carbon		U																				
Carbon-Graphite Resin Impregnated		U																				
Ceramics																						
Coatings																						
Acrylic		U																				
Asphalt																						
Chlorinated Rubber																						
Coal Tar		U																				
Coal Tar Epoxy		U																				
Epoxy General Purpose		U																				
Epoxy Chemical Resistant		U																				
Epoxy Polyamide		U																				
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic		U																				
Polyester		U																				
Polyvinyl Chloride		U																				
Silicones		U																				
Urethanes		U																				
Vinyls		U																				
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFURIC ACID 103%

Plastics	°C	°F
ABS	U	
Acetal	U	
Acrylics	U	
Asbestos Reinforced Epoxy	U	
Asbestos Reinforced Phenolic	U	
Chlorinated Polyether (Penton)	U	
CPVC	U	
E-CTFE (Halar)		
Epoxy	U	
ETFE (Tefzel)		
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6	U	
Nylon 11	U	
Nylon 66	U	
Phenolic	U	
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A	U	
Isophthalic	U	
Terephthalate (PET)	U	
Polyetherimide (ULTEM)	U	
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)	U	
Polyethylene HMW	U	
Polyethylene UHMW	U	
Polymethylpentene	U	
Polypropylene (PP)	U	
Polystyrene	U	
Polysulfone	U	
Polyvinylidene Chloride	U	
PVC Type 1	U	
PVC Type 2	U	
PVDF (Kynar)	U	
Ryton		
TFE (Teflon)	R	
Vinyl Ester	U	

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID 103%

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)	U																				
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)																					
Hard Rubber	U																				
Soft Rubber	U																				
Isoprene (IR)	U																				
Kalrez (FPM)																					
Koroseal	U																				
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)	U																				
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)	U																				
Polyurethane (AU)	U																				
SBR Styrene (Buna-S)	U																				
Silicone Rubbers	U																				
Fabrics																					
Cotton	U																				
Felt (Wool)	U																				
Rayon Viscose	U																				
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID FUMING

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass		U																									
Aluminum		E																									
Aluminum Bronze		U																									
Brass		U																									
Bronze		U																									
Carbon Steel																											
Columbium (Niobium)																											
Copper		U																									
Hastelloy B/B-2		E		G																							
Hastelloy C/C-276		G																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625		U																									
Incolloy 800/825		U																									
Lead																											
Monel 400		U																									
Naval Bronze																											
Nickel 200/201		U																									
Ni-Resist																											
Stainless Steels																											
Type 304/347		E																									
Type 316/316 L		E		G																							
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3		E		G																							
E-Bright 26-1																											
Silicon Bronze		U																									
Silicon Copper		U																									
Stellite																											
Tantalum		U																									
Titanium		U																									
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029081

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID FUMING


Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass		U																				
Carbon		U																				
Carbon-Graphite Resin Impregnated		U																				
Ceramics		U																				
Coatings																						
Acrylic		U																				
Asphalt																						
Chlorinated Rubber																						
Coal Tar		U																				
Coal Tar Epoxy		U																				
Epoxy General Purpose		U																				
Epoxy Chemical Resistant		U																				
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		U																				
Silicones		U																				
Urethanes		U																				
Vinyls		U																				
Water Base																						
Zinc Rich																						
Mortars																						
Silicate		U																				
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID FUMING



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SULFURIC ACID VAPORS

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2		G	G																								
Hastelloy C/C-276		G	G	G	G	G	G	G	G																		
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029082

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID VAPORS

Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID VAPORS

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)																						
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ACID VAPORS

Elastomers* and Linings	°C / °F	15 / 60	26 / 80	38 / 100	49 / 120	60 / 140	71 / 160	82 / 180	93 / 200	104 / 220	116 / 240	127 / 260	138 / 280	149 / 300	160 / 320	171 / 340	182 / 360	193 / 380	204 / 400	216 / 420	227 / 440	238 / 460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F / °C	60 / 15	80 / 26	100 / 38	120 / 49	140 / 60	160 / 71	180 / 82	200 / 93	220 / 104	240 / 116	260 / 127	280 / 138	300 / 149	320 / 160	340 / 171	360 / 182	380 / 193	400 / 204	420 / 216	440 / 227	460 / 238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cor

SULFURIC ANHYDRIDE DRY

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		E																									
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper		G																									
Hastelloy B/B-2		E																									
Hastelloy C/C-276		E																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625		U																									
Incolloy 800/825		U																									
Lead																											
Monel 400		U																									
Naval Bronze																											
Nickel 200/201		U																									
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze		G																									
Silicon Copper																											
Stellite																											
Tantalum		U																									
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029083

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ANHYDRIDE DRY

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

SULFURIC ANHYDRIDE DRY

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)		
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURIC ANHYDRIDE DRY

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029084

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUROUS ACID



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

SULFUROUS ACID


Plastics		
ABS		R
Acetal		U
Acrylics		R
Asbestos Reinforced Epoxy		R
Asbestos Reinforced Phenolic		R
Chlorinated Polyether (Penton)		R
CPVC		R
E-CTFE (Halar)		R
Epoxy	TO 20%	R
ETFE (Tefzel)		R
FEP		R
Furan (Furfural Alcohol)		R
Noryl		
Nylon 6		U
Nylon 11		U
Nylon 66		U
Phenol-Formaldehyde		R
PFA (Teflon)		R
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate	ALL	R
Halogenated	10%	R
Hydrogenated Bisphenol A –Bisphenol A	25%	R
Isophthalic	10%	U
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		R
Polyethylene UHMW		R
Polymethylpentene		
Polypropylene (PP)		R
Polystyrene	10%	R
Polysulfone		R
Polyvinylidene Chloride		R
PVC Type 1		R
PVC Type 2		R
PVDF (Kynar)		R
Ryton	10%	R
TFE (Teflon)		R
Vinyl Ester	10%	R

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFUROUS ACID



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cor



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029085

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURYL CHLORIDE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)	U																					
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic	U																					
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate	U																					
Halogenated	U																					
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic	U																					
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW	U																					
Polyethylene UHMW	U																					
Polymethylpentene																						
Polypropylene (PP)	U																					
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1	U																					
PVC Type 2	U																					
PVDF (Kynar)	U																					
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester	U																					
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

SULFURYL CHLORIDE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	U																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)																					
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120029086

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TALL OIL



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TALL OIL

Elastomers* and Linings	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)		U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		U																				
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)		U																				
Ethylene-Propylene Terpolymer (EPT)		U																				
FKM (Viton A)		R																				
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)		U																				
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)		U																				
Neoprene GR-M (CR)		U																				
Nitrile Buna-N (NBR)		R																				
Nordel (EPDM)		U																				
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			G																									
Aluminum			U																									
Aluminum Bronze			G																									
Brass	Air Free		G																									
Bronze			U																									
Carbon Steel			U																									
Columbium (Niobium)			G																									
Copper			G																									
Hastelloy B/B-2	10%		G																									
Hastelloy C/C-276	10%		G																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron			G																									
Inconel 600/625	ALL		G																									
Incolloy 800/825	ALL		G																									
Lead			U																									
Monel 400	ALL		G																									
Naval Bronze			G																									
Nickel 200/201	ALL		G																									
Ni-Resist																												
Stainless Steels																												
Type 304/347			G																									
Type 316/316 L	ALL		G																									
Type 400 series	10–50%		G																									
Type 904-L																												
17-4 PH			G																									
20 Cb 3	ALL		G																									
E-Bright 26-1																												
Silicon Bronze	ALL		G																									
Silicon Copper			E																									
Galv. Stl.			G																									
Tantalum			G																									
Titanium	10–20%		E																									
Zirconium	10–25%		E																									
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030066

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TANNIC ACID




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TANNIC ACID



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030067


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TANNING LIQUORS




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TANNING LIQUORS



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G	G	G	G	G	G	G																			
Aluminum Bronze		G	G	G	G	G	G	G																			
Brass		G	G	G	G	G	G	G																			
Bronze		G	G	G	G	G	G	G																			
Carbon Steel		G	G	G	G	G	G	G																			
Columbium (Niobium)																											
Copper		G	G	G	G	G	G	G																			
Hastelloy B/B-2																											
Hastelloy C/C-276		G	G	G	G	G	G	G																			
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625		E	E	E	E	E	E	E																			
Incolloy 800/825																											
Lead																											
Monel 400		G	G	G	G	G	G	G																			
Naval Bronze																											
Nickel 200/201		G	G	G	G	G	G	G																			
Ni-Resist		G	G	G	G	G	G	G																			
Stainless Steels																											
Type 304/347		G	G	G	G	G	G	G																			
Type 316/316 L		G	G	G	G	G	G	G																			
Type 400 series		G	G	G	G	G	G	G																			
Type 904-L																											
17-4 PH		G	G	G	G	G	G	G																			
20 Cb 3		G	G	G	G	G	G	G																			
E-Bright 26-1																											
Silicon Bronze		G	G	G	G	G	G	G																			
Silicon Copper		E	E	E	E	E	E	E																			
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030068

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TAR




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TAR



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030069

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TARTARIC ACID




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TARTARIC ACID

Plastics		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS			R																				
Acetal																							
Acrylics																							
Asbestos Reinforced Epoxy																							
Asbestos Reinforced Phenolic																							
Chlorinated Polyether (Penton)			R																				
CPVC			R																				
E-CTFE (Halar)			R																				
Epoxy	11%		R				U																
ETFE (Tefzel)			R																				
FEP			R																				
Furan (Furfural Alcohol)			R																				
Noryl			R																				
Nylon 6			R																				
Nylon 11			R																				
Nylon 66			R																				
Phenolic	50%		R																				
PFA (Teflon)			R																				
Polyamide-Imide																							
Polyesters																							
Bisphenol A–fumarate			R																				
Halogenated	ALL		R																				
Hydrogenated Bisphenol A –Bisphenol A			R																				
Isophthalic			R																				
Terephthalate (PET)			R																				
Polyetherimide (ULTEM)																							
Polyetheretherketone (PEEK)																							
Polyethersulfone (PES)																							
Polyethylene HMW			R																				
Polyethylene UHMW			R																				
Polymethylpentene			R																				
Polypropylene (PP)			R																				
Polystyrene																							
Polysulfone			R																				
Polyvinylidene Chloride			R																				
PVC Type 1			R																				
PVC Type 2			R																				
PVDF (Kynar)			R																				
Ryton	ALL		R																				
TFE (Teflon)			R																				
Vinyl Ester	ALL		R																				
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TARTARIC ACID



*See also Nylon 11 under PLASTICS

Schweitzer/ *Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRACHLOROACETIC ACID

Metals	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																										
Aluminum	U																									
Aluminum Bronze																										
Brass																										
Bronze																										
Carbon Steel	U																									
Columbium (Niobium)	E																									
Copper	G	U																								
Hastelloy B/B-2																										
Hastelloy C/C-276																										
Hastelloy D																										
Hastelloy G/G-3																										
High Silicon Iron																										
Inconel 600/625																										
Incolloy 800/825	U																									
Galv. Stl.	U																									
Monel 400	G																									
Naval Bronze																										
Nickel 200/201																										
Ni-Resist																										
Stainless Steels																										
Type 304/347	U																									
Type 316/316 L	U																									
Type 400 series	U																									
Type 904-L																										
17-4 PH																										
20 Cb 3																										
E-Bright 26-1																										
Silicon Bronze	G	U																								
Silicon Copper																										
Stellite																										
Tantalum																										
Titanium	U																									
Zirconium																										
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS
E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year
S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS
R = Resistant
U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030070
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRACHLOROACETIC ACID

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon																					
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride	U																				
Silicones																					
Urethanes																					
Vinyls	U																				
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expa*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c

TETRACHLOROACETIC ACID



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRACHLOROACETIC ACID

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

TETRACHLOROETHANE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G	U																								
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel		E	G																								
Columbium (Niobium)																											
Copper		S																									
Hastelloy B/B-2																											
Hastelloy C/C-276		E																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze		E	G																								
Nickel 200/201																											
Ni-Resist		G																									
Stainless Steels																											
Type 304/347		E	G																								
Type 316/316 L		E																									
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3		E																									
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium		E																									
Zirconium		E																									
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030071

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRACHLOROETHANE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

TETRACHLOROETHANE

Plastics	°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238 / °F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460
ABS	
Acetal	
Acrylics	
Asbestos Reinforced Epoxy	
Asbestos Reinforced Phenolic	
Chlorinated Polyether (Penton)	
CPVC	U
E-CTFE (Halar)	
Epoxy	R
ETFE (Tefzel)	R
FEP	R
Furan (Furfural Alcohol)	R
Noryl	
Nylon 6	R
Nylon 11	R
Nylon 66	R
Phenolic	R
PFA (Teflon)	
Polyamide-Imide	
Polyesters	
Bisphenol A–fumarate	
Halogenated	
Hydrogenated Bisphenol A –Bisphenol A	
Isophthalic	
Terephthalate (PET)	R
Polyetherimide (ULTEM)	
Polyetheretherketone (PEEK)	
Polyethersulfone (PES)	
Polyethylene HMW	U
Polyethylene UHMW	U
Polymethylpentene	R
Polypropylene (PP)	R U
Polystyrene	
Polysulfone	U
Polyvinylidene Chloride	
PVC Type 1	U
PVC Type 2	U
PVDF (Kynar)	R
Ryton	
TFE (Teflon)	R
Vinyl Ester	R

°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460 / °C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRACHLOROETHANE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)	U																				
Polyurethane (AU)																					
SBR Styrene (Buna-S)	U																				
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)	R																				
Rayon Viscose	R																				
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRACHLOROETHYLENE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum	DRY		G	—	—	—	—	—	—	—																		
Aluminum Bronze																												
Brass	DRY		G	—																								
Bronze	DRY		G	—																								
Carbon Steel																												
Columbium (Niobium)			E	—	—	—	—	—	—	—																		
Copper	DRY		G	—																								
Hastelloy B/B-2																												
Hastelloy C/C-276																												
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron			G	—	—	—	—	—	—	—																		
Inconel 600/625																												
Incolloy 800/825																												
Lead																												
Monel 400																												
Naval Bronze																												
Nickel 200/201																												
Ni-Resist																												
Stainless Steels																												
Type 304/347																												
Type 316/316 L																												
Type 400 series																												
Type 904-L																												
17-4 PH																												
20 Cb 3																												
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum																												
Titanium			E	—	—	—	—	—	—	—	—																	
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030072


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRACHLOROETHYLENE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRACHLOROETHYLENE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRACHLOROETHYLENE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

Metals	°F	°C
Admiralty Brass		
Aluminum	G	
Aluminum Bronze	G	
Brass	G	
Bronze	G	
Carbon Steel	G	
Columbium (Niobium)		
Copper		
Hastelloy B/B-2		
Hastelloy C/C-276		
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625	G	
Incolloy 800/825		
Lead		
Monel 400	G	
Naval Bronze	E	
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347	G	
Type 316/316 L	G	
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3	G	
E-Bright 26-1		
Silicon Bronze	G	
Silicon Copper		
Stellite		
Tantalum		
Titanium		
Zirconium		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030073

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRAETHYL LEAD

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon	R																				
Carbon-Graphite Resin Impregnated	R																				
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride	R																				
Silicones																					
Urethanes																					
Vinyls	R																				
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRAETHYL LEAD

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)	U																				
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expa*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030074

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRAHYDROFURAN



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRAHYDROFURAN

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)	U																				
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R	U																			
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)	U																				
Polybutadiene (BR)																					
Polyester (PE)	R																				
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)	U																				
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cor

Metals	°C	°F
Admiralty Brass		
Aluminum	G	
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper		
Hastelloy B/B-2		
Hastelloy C/C-276		
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825		
Lead		
Monel 400		
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347	G	
Type 316/316 L		
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3		
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		
Tantalum	G	
Titanium		
Zirconium		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030075

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRALIN

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass		R																				
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		U																				
Silicones		U																				
Urethanes																						
Vinyls		U																				
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC	U																					
E-CTFE (Halar)																						
Epoxy	R																					
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl	U																					
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)	R																					
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW	U																					
Polyethylene UHMW	U																					
Polymethylpentene																						
Polypropylene (PP)	R			U																		
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1	U																					
PVC Type 2	U																					
PVDF (Kynar)																						
Ryton	R																					
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRALIN

Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)	U	
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)	R	
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)	U	
Ethylene-Propylene Terpolymer (EPT)	U	
FKM (Viton A)	R	
Hard Rubber		
Soft Rubber		
Isoprene (IR)	U	
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)	U	
Neoprene GR-M (CR)	U	
Nitrile Buna-N (NBR)	U	
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers	U	
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker

TETRAMETHYL AMMONIUM HYDROXIDE 50%

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030076


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRAMETHYL AMMONIUM HYDROXIDE 50%

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

TETRAMETHYL AMMONIUM HYDROXIDE 50%



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRAMETHYL AMMONIUM HYDROXIDE 50%

Elastomers* and Linings	°F / °C	60 / 15	80 / 26	100 / 38	120 / 49	140 / 60	160 / 71	180 / 82	200 / 93	220 / 104	240 / 116	260 / 127	280 / 138	300 / 149	320 / 160	340 / 171	360 / 182	380 / 193	400 / 204	420 / 216	440 / 227	460 / 238
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)		R																				
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F / °C	60 / 15	80 / 26	100 / 38	120 / 49	140 / 60	160 / 71	180 / 82	200 / 93	220 / 104	240 / 116	260 / 127	280 / 138	300 / 149	320 / 160	340 / 171	360 / 182	380 / 193	400 / 204	420 / 216	440 / 227	460 / 238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRAPHOSPHORIC ACID

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		U																									
Aluminum Bronze																											
Brass		S				U																					
Bronze																											
Carbon Steel		U																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2		G																									
Hastelloy C/C-276		G																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625		G																									
Incolloy 800/825																											
Lead																											
Monel 400		S																									
Naval Bronze		U																									
Nickel 200/201		U																									
Ni-Resist																											
Stainless Steels																											
Type 304/347		U																									
Type 316/316 L		U																									
Type 400 series		U																									
Type 904-L																											
17-4 PH																											
20 Cb 3		G																									
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030077

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRAPHOSPHORIC ACID

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

TETRAPHOSPHORIC ACID

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TETRAPHOSPHORIC ACID

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)	R																					
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expa*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.

THIONYL CHLORIDE

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum			U																									
Aluminum Bronze																												
Brass																												
Bronze																												
Carbon Steel			U																									
Columbium (Niobium)																												
Copper																												
Hastelloy B/B-2																												
Hastelloy C/C-276	10%		G																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625																												
Incolloy 800/825																												
Lead			G																									
Monel 400			G																									
Naval Bronze																												
Nickel 200/201			G																									
Ni-Resist																												
Stainless Steels																												
Type 304/347																												
Type 316/316 L			U																									
Type 400 series																												
Type 904-L																												
17-4 PH																												
20 Cb 3																												
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum			G																									
Titanium																												
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030078

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

THIONYL CHLORIDE

Nonmetallic Materials	
Borosilicate Glass	R
Carbon	
Carbon-Graphite Resin Impregnated-Phenolic	R
Ceramics	
Coatings	
Acrylic	
Asphalt	
Chlorinated Rubber	
Coal Tar	
Coal Tar Epoxy	U
Epoxy General Purpose	U
Epoxy Chemical Resistant	U
Epoxy Polyamide	U
Oil Base (Alkyd, Epoxy, Urethane)	
Phenolic	R
Polyester	U
Polyvinyl Chloride	U
Silicones	
Urethanes	
Vinyls	U
Water Base	
Zinc Rich	
Mortars	
Silicate	
Sodium Silicate	U
Potassium Silicate	
Silica	
Sulfur	U
Furan Resin	U
Polyester	U
Epoxy	U

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

THIONYL CHLORIDE

Plastics		°C	°F
ABS		U	
Acetal		U	
Acrylics			
Asbestos Reinforced Epoxy			
Asbestos Reinforced Phenolic			
Chlorinated Polyether (Penton)		U	
CPVC		U	
E-CTFE (Halar)		R	
Epoxy		U	
ETFE (Tefzel)		R	
FEP	14	R	
Furan (Furfural Alcohol)		U	
Noryl			
Nylon 6		U	
Nylon 11		U	
Nylon 66		U	
Phenolic		R	
PFA (Teflon)	14	R	
Polyamide-Imide			
Polyesters			
Bisphenol A–fumarate		U	
Halogenated		U	
Hydrogenated Bisphenol A –Bisphenol A			
Isophthalic		U	
Terephthalate (PET)			
Polyetherimide (ULTEM)			
Polyetheretherketone (PEEK)			
Polyethersulfone (PES)			
Polyethylene HMW		U	
Polyethylene UHMW		U	
Polymethylpentene		U	
Polypropylene (PP)		R	
Polystyrene			
Polysulfone		U	
Polyvinylidene Chloride		U	
PVC Type 1		U	
PVC Type 2		U	
PVDF (Kynar)		U	
Ryton		U	
TFE (Teflon)	14	R	
Vinyl Ester		U	

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

THIONYL CHLORIDE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	U																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel	G																										
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347	G																										
Type 316/316 L	G																										
Type 400 series	G																										
Type 904-L																											
17-4 PH	G																										
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite	U																										
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030079

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

THREAD CUTTING OIL



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.c



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

THREAD CUTTING OIL

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)																					
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)	R																				
Nordel (EPDM)	U																				
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	°F
Admiralty Brass		
Aluminum		
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper		
Hastelloy B/B-2	G	G
Hastelloy C/C-276	G	G
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825		
Lead		
Monel 400		
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347	U	
Type 316/316 L	G	G
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3		
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		
Tantalum	E	
Titanium		
Zirconium		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030080


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TIN CHLORIDE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TIN CHLORIDE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TIN (MOLTEN)

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass		U																									
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper		U																									
Hastelloy B/B-2		E																									
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625		U																									
Incolloy 800/825																											
Lead																											
Monel 400		U																									
Naval Bronze																											
Nickel 200/201		U																									
Ni-Resist																											
Stainless Steels																											
Type 304/347		S																									
Type 316		S																									
Type 430		S																									
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper		U																									
Stellite																											
Tantalum		E												G		S											
Titanium		E																									
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030081

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TIN (MOLTEN)

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated		R																				
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		U																				
Silicones																						
Urethanes																						
Vinyls		U																				
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expandea*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TIN (MOLTEN)

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal		U																				
Acrylics		U																				
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)		U																				
CPVC																						
E-CTFE (Halar)		U																				
Epoxy		U																				
ETFE (Tefzel)		U																				
FEP		U																				
Furan (Furfural Alcohol)		U																				
Noryl		U																				
Nylon 6		U																				
Nylon 11		U																				
Nylon 66		U																				
Phenolic																						
PFA (Teflon)		U																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		U																				
Polyethylene UHMW		U																				
Polymethylpentene																						
Polypropylene (PP)		U																				
Polystyrene																						
Polysulfone		U																				
Polyvinylidene Chloride																						
PVC Type 1		U																				
PVC Type 2		U																				
PVDF (Kynar)		U																				
Ryton																						
TFE (Teflon)		U																				
Vinyl Ester		U																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TIN (MOLTEN)


Elastomers* and Linings	°C	°F
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)		
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)		
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)		
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TIN TETRACHLORIDE



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030082

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TIN TETRACHLORIDE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TIN TETRACHLORIDE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)		R																				
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expan*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030083


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TITANIUM TETRACHLORIDE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TITANIUM TETRACHLORIDE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TITANIUM TETRACHLORIDE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)	U																					
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																					
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)	U																					
Ethylene-Propylene Terpolymer (EPT)	U																					
FKM (Viton A)	R																					
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)	U																					
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)	U																					
Neoprene GR-M (CR)	U																					
Nitrile Buna-N (NBR)	R	U																				
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers	U																					
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030084

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOLUENE (TOLUOL)



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOLUENE (TOLUOL)


Plastics	°C	°F
ABS	U	
Acetal	U	
Acrylics	U	
Asbestos Reinforced Epoxy	R	
Asbestos Reinforced Phenolic	R	
Chlorinated Polyether (Penton)	R	
CPVC	U	
E-CTFE (Halar)	R	
Epoxy	R	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl	U	
Nylon 6	R	
Nylon 11	R	
Nylon 66	R	
Phenolic	R	
PFA (Teflon)	R	
Polyamide-Imide	R	
Polyesters		
Bisphenol A–fumarate	U	
Halogenated	R	
Hydrogenated Bisphenol A –Bisphenol A	R	
Isophthalic	R	
Terephthalate (PET)	R	
Polyetherimide (ULTEM)	R	
Polyetheretherketone (PEEK)	R	
Polyethersulfone (PES)	R	
Polyethylene HMW	U	
Polyethylene UHMW	U	
Polymethylpentene	U	
Polypropylene (PP)	R	
Polystyrene	U	
Polysulfone	U	
Polyvinylidene Chloride	R	
PVC Type 1	U	
PVC Type 2	U	
PVDF (Kynar)	R	
Ryton	R	
TFE (Teflon)	R	
Vinyl Ester	R	

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOLUENE (TOLUOL)




*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOLUENE-KEROSENE 25–75%



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030085

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOLUENE-KEROSENE 25–75%




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


TOLUENE-KEROSENE 25–75%



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030086

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOMATO JUICE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOMATO JUICE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030087

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOXAPHENE-XYLENE 10–90%

Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Borosilicate Glass																						
Carbon	R																					
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy	U																					
Epoxy General Purpose	U																					
Epoxy Chemical Resistant	U																					
Epoxy Polyamide	U																					
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride	U																					
Silicones																						
Urethanes																						
Vinyls	U																					
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur	U																					
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOXAPHENE-XYLENE 10–90%

Plastics	°C	°F
ABS	U	
Acetal		
Acrylics		
Asbestos Reinforced Epoxy	U	
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)	R	U
CPVC	U	
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP	R	
Furan (Furfural Alcohol)	R	
Noryl	U	
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated	R	
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic	U	
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	U	
Polyethylene UHMW	U	
Polymethylpentene		
Polypropylene (PP)	R	U
Polystyrene		
Polysulfone	U	
Polyvinylidene Chloride	R	
PVC Type 1	U	
PVC Type 2	U	
PVDF (Kynar)		
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TOXAPHENE-XYLENE 10–90%

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)	U																				
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R																				
Hard Rubber	U																				
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal	U																				
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)	U																				
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)	U																				
SBR Styrene (Buna-S)	U																				
Silicone Rubbers	U																				
Fabrics																					
Cotton	R																				
Felt (Wool)	R																				
Rayon Viscose	R																				
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G																									
Aluminum Bronze																											
Brass		G																									
Bronze		G																									
Carbon Steel		G																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2		G																									
Hastelloy C/C-276		G																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400		G																									
Naval Bronze		E																									
Nickel 200/201		G																									
Ni-Resist																											
Stainless Steels																											
Type 304/347		G																									
Type 316/316 L		G																									
Type 400 series																											
Type 904-L																											
17-4 PH		G																									
20 Cb 3		G																									
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030088


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRANSFORMER OIL




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

TRANSFORMER OIL



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRANSFORMER OIL



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G																									
Aluminum Bronze																											
Brass																											
Bronze		G																									
Carbon Steel		G																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276		G																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400		G																									
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L		G																									
Type 400 series																											
Type 904-L																											
17-4 PH		G																									
20 Cb 3		G																									
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS
E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year
S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS
R = Resistant
U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030089
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRANSFORMER OIL DTE/30

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co

TRANSFORMER OIL DTE/30

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC	R	
E-CTFE (Halar)	R	
Epoxy		
ETFE (Tefzel)		
FEP		
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)		
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	R	
Polyethylene UHMW	R	
Polymethylpentene		
Polypropylene (PP)	R	
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1	R	
PVC Type 2		
PVDF (Kynar)		
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRANSFORMER OIL DTE/30

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)																					
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)																					
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	R																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	
°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

TRIBUTYL PHOSPHATE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		G	—	—	—																						
Aluminum Bronze																											
Brass																											
Bronze		G	—	—	—																						
Carbon Steel		G	—																								
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2		G	—	—	—																						
Hastelloy C/C-276		G	—	—	—																						
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400		G	—	—	—																						
Naval Bronze																											
Nickel 200/201		G	—	—	—																						
Ni-Resist																											
Stainless Steels																											
Type 304/347		G	—	—	—	—	—	—	—	—	—																
Type 316/316 L		G	—	—	—																						
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3		G	—	—	—																						
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030090

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIBUTYL PHOSPHATE

Nonmetallic Materials	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Borosilicate Glass		R																				
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride		U																				
Silicones		U																				
Urethanes																						
Vinyls		U																				
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

TRIBUTYL PHOSPHATE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		U																				
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)		R																				
CPVC		U																				
E-CTFE (Halar)		R	U																			
Epoxy																						
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6		R																				
Nylon 11																						
Nylon 66		R																				
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate		U																				
Halogenated		U																				
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic		R																				
Terephthalate (PET)		U																				
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		U																				
Polyethylene UHMW		U																				
Polymethylpentene																						
Polypropylene (PP)		R				U																
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride		R																				
PVC Type 1		U																				
PVC Type 2		U																				
PVDF (Kynar)		R				U																
Ryton		R																				
TFE (Teflon)		R																				
Vinyl Ester		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIBUTYL PHOSPHATE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	R	U																			
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	U																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)	U																				
SBR Styrene (Buna-S)																					
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030091

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


TRICHLOROACETIC ACID



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROACETIC ACID



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROACETIC ACID

Elastomers* and Linings	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR) 10%	R																				
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	R	U																			
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	R	U																			
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton	U																				
Felt (Wool)	U																				
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROACETIC ACID 2N

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass		U																									
Aluminum		U																									
Aluminum Bronze		G																									
Brass																											
Bronze																											
Carbon Steel		U																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2		G																									
Hastelloy C/C-276		G																									
Hastelloy D		G																									
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze		G																									
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		U																									
Type 316/316 L		U																									
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze		G																									
Silicon Copper		G																									
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030092


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROACETIC ACID 2N



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

TRICHLOROACETIC ACID 2N



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROACETIC ACID 2N

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	R	U																			
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	U																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	R	U																			
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton	U																				
Felt (Wool)	U																				
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel (DRY)		G																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		E																									
Type 316/316 L		E																									
Type																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030093

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROETHANE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon	R																					
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Polycarbonate		U																				
KEL-F (CTFE)		R																				
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy		R																				
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic		U																				
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		U																				
Polyethylene UHMW		U																				
Polymethylpentene		R																				
Polypropylene (PP)		U																				
Polystyrene																						
Polysulfone		U																				
Polyvinylidene Chloride		R																				
PVC Type 1		U																				
PVC Type 2		U																				
PVDF (Kynar)		R																				
Ryton		R																				
TFE (Teflon)		R																				
Vinyl Ester		U																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROETHANE

Elastomers* and Linings	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	R																				
Hard Rubber	U																				
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)	U																				
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)	U																				
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030094


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROETHYLENE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cor

TRICHLOROETHYLENE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROETHYLENE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)	U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)	U																				
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R																				
Hard Rubber	U																				
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal	U																				
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)	U																				
Polybutadiene (BR)																					
Polyester (PE)	U																				
Polyether-Urethane (EU)	U																				
Polyisoprene (IR)																					
Polysulfides (T)	U																				
Polyurethane (AU)	U																				
SBR Styrene (Buna-S)	U																				
Silicone Rubbers	U																				
Fabrics																					
Cotton	R																				
Felt (Wool)	R																				
Rayon Viscose	R																				
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand.*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.cor



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030097

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROPROPANE

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon																					
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride																					
Silicones																					
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROPROPANE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)																						
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICHLOROPROPANE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)		R																				
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass			U																									
Aluminum																												
Aluminum Bronze																												
Brass																												
Bronze																												
Carbon Steel			E																									
Columbium (Niobium)																												
Copper																												
Hastelloy B/B-2																												
Hastelloy C/C-276	90%		E																									
Hastelloy D																												
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625																												
Incolloy 800/825																												
Lead																												
Monel 400																												
Naval Bronze																												
Nickel 200/201																												
Ni-Resist			E																									
Stainless Steels																												
Type 304/347			G																									
Type 316/316 L			E					G																				
Type 400																												
Type 904-L																												
17-4 PH																												
20 Cb 3			E					G																				
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum																												
Titanium																												
Zirconium																												
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030098

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICRESYLPHOSPHATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expande*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

TRICRESYLPHOSPHATE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy	R																					
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)	R																					
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW	R				U																	
Polymethylpentene																						
Polypropylene (PP)	R																					
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1	U																					
PVC Type 2	U																					
PVDF (Kynar)	U																					
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester	R																					
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRICRESYLPHOSPHATE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	U																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	U																				
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)	U																				
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)	U																				
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030095

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHANOLAMINE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expand*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.co


TRIETHANOLAMINE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		R																				
Acetal		U																				
Acrylics		R																				
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)		R																				
CPVC		R		U																		
E-CTFE (Halar)		R	U																			
Epoxy		R																				
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)		R																				
Noryl		R																				
Nylon 6		R																				
Nylon 11		R																				
Nylon 66		R																				
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate		R																				
Halogenated		R																				
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic		U																				
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		U																				
Polyethylene UHMW		R																				
Polymethylpentene																						
Polypropylene (PP)		R		U																		
Polystyrene																						
Polysulfone		U																				
Polyvinylidene Chloride		R																				
PVC Type 1		U																				
PVC Type 2		U																				
PVDF (Kynar)		R																				
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

كتابخانه

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHANOLAMINE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron	G																										
Inconel 600/625																											
Incolloy 800/825																											
Galv. Stl.	E																										
Monel 400	G																										
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347	G																										
Type 316/316 L	G																										
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3	G																										
E-Bright 26-1																											
Silicon Bronze	G																										
Silicon Copper																											
Stellite																											
Tantalum	E																										
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030096

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHYLAMINE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHYLAMINE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)																					
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)	R																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton	U																				
Felt (Wool)	U																				
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		E	E																								
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel		E	E																								
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel																											
Incolloy																											
Lead																											
Monel																											
Naval Bronze																											
Nickel																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		E	E																								
Type 316		E	E																								
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030099

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHYL PHOSPHATE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHYL PHOSPHATE

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)	U	
CPVC		
E-CTFE (Halar)	R	
Epoxy		
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)		
Ryton	R	
TFE (Teflon)	R	
Vinyl Ester	R	

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHYL PHOSPHATE

Elastomers* and Linings	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)		R	R	R	R	R	R	R	R													
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	%	°F	°C
Admiralty Brass			
Aluminum		E	
Aluminum Bronze			
Brass			
Bronze			
Carbon Steel		G	
Columbium (Niobium)			
Copper			
Hastelloy B/B-2			
Hastelloy C/C-276			
Hastelloy D			
Hastelloy G/G-3			
High Silicon Iron			
Inconel 600/625			
Incolloy 800/825			
Lead			
Monel 400		E	
Naval Bronze			
Nickel 200/201			
Ni-Resist			
Stainless Steels			
Type 304/347	85%	E	
Type 316/316 L		G	
Type 430		E	
Type 904-L			
17-4 PH			
20 Cb 3		E	
E-Bright 26-1			
Silicon Bronze			
Silicon Copper			
Stellite			
Tantalum			
Titanium			
Zirconium			

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030100

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHYL PHOSPHITE

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon																					
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride																					
Silicones																					
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHYL PHOSPHITE

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Polycarbonate	U	
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)	R	15–38
Epoxy		
ETFE (Tefzel)	R	15–93
FEP	R	15–49
Furan (Furfural Alcohol)		
Noryl	U	
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	15–93
Polyamide-Imide	R	15–93
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone	R	15–93
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)		
Ryton	R	15–93
TFE (Teflon)	R	15–93
Vinyl Ester		

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIETHYL PHOSPHITE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030101

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIMETHYL PROPANE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride	R	R	R	R																		
Silicones																						
Urethanes																						
Vinyls	R	R	R	R																		
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIMETHYL PROPANE

Plastics		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS			U																				
Acetal																							
Acrylics																							
Asbestos Reinforced Epoxy																							
Asbestos Reinforced Phenolic																							
Chlorinated Polyether (Penton)			R	—	—	—	—	—	—	—	—	—											
CPVC			R	—	—	—	—																
E-CTFE (Halar)																							
Epoxy																							
ETFE (Tefzel)																							
FEP	14		R	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Furan (Furfural Alcohol)																							
Noryl																							
Nylon 6																							
Nylon 11																							
Nylon 66																							
Phenolic																							
PFA (Teflon)	14		R	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Polyamide-Imide																							
Polyesters																							
Bisphenol A–fumarate																							
Halogenated																							
Hydrogenated Bisphenol A –Bisphenol A																							
Isophthalic																							
Terephthalate (PET)																							
Polyetherimide (ULTEM)																							
Polyetheretherketone (PEEK)																							
Polyethersulfone (PES)																							
Polyethylene HMW																							
Polyethylene UHMW																							
Polymethylpentene																							
Polypropylene (PP)			U																				
Polystyrene																							
Polysulfone																							
Polyvinylidene Chloride			R	—	—	—																	
PVC Type 1			R	—	—	—																	
PVC Type 2			R	—	—	—																	
PVDF (Kynar)			R	—	—	—	—	—	—	—	—	—											
Ryton																							
TFE (Teflon)	14		R	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Vinyl Ester																							
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRIMETHYL PROPANE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																												
Aluminum			U																									
Aluminum Bronze			G																									
Brass			G																									
Bronze																												
Carbon Steel			G																									
Columbium (Niobium)																												
Copper			G																									
Hastelloy B/B-2	10%		E																									
Hastelloy C/C-276	10%		E																									
Hastelloy D	10%		E																									
Hastelloy G/G-3																												
High Silicon Iron																												
Inconel 600/625																												
Incolloy 800/825																												
Lead			U																									
Monel 400			G																									
Naval Bronze			S																									
Nickel 200/201			G																									
Ni-Resist																												
Stainless Steels																												
Type 304/347	10%		E																									
Type 316/316 L	10%		E																									
Type 400 series			G																									
Type 904-L																												
17-4 PH																												
20 Cb 3	10%		E																									
E-Bright 26-1																												
Silicon Bronze																												
Silicon Copper																												
Stellite																												
Tantalum			G																									
Titanium																												
Zirconium	5–20%		G																									
		°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
		°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030102


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRISODIUM PHOSPHATE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRISODIUM PHOSPHATE




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TRISODIUM PHOSPHATE



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030103

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TUNG OIL

	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Nonmetallic Materials																						
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant	R																					
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls	R																					
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy	R																					
ETFE (Tefzel)																						
FEP	R																					
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A																						
–Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1	U																					
PVC Type 2	U																					
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)	R																					
Vinyl Ester	R																					
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TUNG OIL

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)	R																				
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)	U																				
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)	U																				
Neoprene GR-M (CR)	R																				
Nitrile Buna-N (NBR)	R																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)	U																				
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers	U																				
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030104

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TURPENTINE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Plastics	°C	°F
ABS	U	
Acetal	R	
Acrylics	R	
Asbestos Reinforced Epoxy	R	
Asbestos Reinforced Phenolic	R	
Chlorinated Polyether (Penton)	R	
CPVC		
E-CTFE (Halar)	R	
Epoxy	R	
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)		
Noryl	R	
Nylon 6	R	
Nylon 11	R	
Nylon 66	R	
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate	R	
Halogenated	R	
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic	R	
Terephthalate (PET)	R	
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW	U	
Polyethylene UHMW	U	
Polymethylpentene	U	
Polypropylene (PP)	R	U
KEL-F (CTFE)	R	
Polysulfone	R	
Polyvinylidene Chloride	R	
PVC Type 1	R	
PVC Type 2	U	
PVDF (Kynar)	R	
Ryton	R	
TFE (Teflon)	R	
Vinyl Ester	R	

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

TURPENTINE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)		U																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)		R																				
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		R																				
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)		U																				
Ethylene-Propylene Terpolymer (EPT)		U																				
FKM (Viton A)		R																				
Hard Rubber		U																				
Soft Rubber		U																				
Isoprene (IR)		U																				
Kalrez (FPM)		R																				
Koroseal																						
Natural Rubber (GRS)		U																				
Neoprene GR-M (CR)		U																				
Nitrile Buna-N (NBR)		R																				
Nordel (EPDM)		U																				
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)		U																				
Polyisoprene (IR)																						
Polysulfides (T)		R																				
Polyurethane (AU)		U																				
SBR Styrene (Buna-S)		U																				
Silicone Rubbers		U																				
Fabrics																						
Cotton		R																				
Felt (Wool)		R																				
Rayon Viscose		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

UDECYL ALCOHOL

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030105

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

UDECYL ALCOHOL

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

UDECYL ALCOHOL

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Polycarbonate (PC)		R																				
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		R																				
Polyethylene UHMW		R																				
Polymethylpentene		R																				
Polypropylene (PP)		R																				
Polystyrene																						
Polysulfone		U																				
Polyvinylidene Chloride																						
PVC Type 1		R																				
PVC Type 2		R																				
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

UDECYL ALCOHOL

Elastomers and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (PTFE)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

URANYL SULFATE 5%

Metals	°C	°F
Admiralty Brass		
Aluminum		
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper		
Hastelloy B/B-2		
Hastelloy C/C-276		
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625		
Incolloy 800/825		
Lead		
Monel 400		
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347		
Type 316/316 L		
Type 400 series		
Type 904-L		
17-4 PH		
20 Cb 3		
E-Bright 26-1		
Silicon Bronze		
Silicon Copper		
Stellite		
Tantalum		
Titanium		
Zirconium	G	

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030106

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

URANYL SULFATE 5%

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon																					
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride																					
Silicones																					
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	
°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

URANYL SULFATE 5%


Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Asbestos Reinforced Epoxy		
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)		
FEP	R	R
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	R
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)	R	R
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1		
PVC Type 2		
PVDF (Kynar)	R	R
Ryton		
TFE (Teflon)	R	R
Vinyl Ester		

°C: 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

°F: 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

URANYL SULFATE 5%



*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030107

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

UREA



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

UREA

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)		R																				
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		R																				
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)		R																				
Ethylene-Propylene-Diene (EPDM)		R																				
Ethylene-Propylene Terpolymer (EPT)		R																				
FKM (Viton A)		R																				
Hard Rubber		R																				
Soft Rubber																						
Isoprene (IR)		R																				
Kalrez (FPM)																						
Koroseal		R																				
Natural Rubber (GRS)		R																				
Neoprene GR-M (CR)		R																				
Nitrile Buna-N (NBR)		R																				
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

UREA AMMONIUM LIQUOR

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist		G	—																								
Stainless Steels																											
Type 304/347		U																									
Type 316/316 L		G	—																								
Type 400 series																											
Type 317/317 L		G	—																								
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030108

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

UREA AMMONIUM LIQUOR

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


UREA AMMONIUM LIQUOR

Plastics	°C	°F
ABS	15–238	60–460
Acetal	15–238	60–460
Acrylics	15–238	60–460
Asbestos Reinforced Epoxy	15–238	60–460
Asbestos Reinforced Phenolic	15–238	60–460
Chlorinated Polyether (Penton)	15–238	60–460
CPVC	15–238	60–460
E-CTFE (Halar)	15–238	60–460
Epoxy	15–238	60–460
ETFE (Tefzel)	15–238	60–460
FEP	15–238	60–460
Furan (Furfural Alcohol)	15–238	60–460
Noryl	15–238	60–460
Nylon 6	15–238	60–460
Nylon 11	15–238	60–460
Nylon 66	15–238	60–460
Phenolic	15–238	60–460
PFA (Teflon)	15–238	60–460
Polyamide-Imide	15–238	60–460
Polyesters	15–238	60–460
Bisphenol A–fumarate	15–238	60–460
Halogenated	15–238	60–460
Hydrogenated Bisphenol A –Bisphenol A	15–238	60–460
Isophthalic	15–238	60–460
Terephthalate (PET)	15–238	60–460
Polyetherimide (ULTEM)	15–238	60–460
Polyetheretherketone (PEEK)	15–238	60–460
Polyethersulfone (PES)	15–238	60–460
Polyethylene HMW	15–238	60–460
Polyethylene UHMW	15–238	60–460
Polymethylpentene	15–238	60–460
Polypropylene (PP)	15–238	60–460
Polystyrene	15–238	60–460
Polysulfone	15–238	60–460
Polyvinylidene Chloride	15–238	60–460
PVC Type 1	15–238	60–460
PVC Type 2	15–238	60–460
PVDF (Kynar)	15–238	60–460
Ryton	15–238	60–460
TFE (Teflon)	15–238	60–460
Vinyl Ester	15–238	60–460

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

UREA AMMONIUM LIQUOR



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

URIC ACID (CONC.)

Metals	°C	°F
Admiralty Brass		
Aluminum	U	
Aluminum Bronze		
Brass		
Bronze		
Carbon Steel		
Columbium (Niobium)		
Copper	E	
Hastelloy B/B-2	E	
Hastelloy C/C-276	E	
Hastelloy D		
Hastelloy G/G-3		
High Silicon Iron		
Inconel 600/625	E	G
Incolloy 800/825	E	G
Lead		
Monel 400	E	
Naval Bronze		
Nickel 200/201		
Ni-Resist		
Stainless Steels		
Type 304/347	E	
Type 316/316 L	E	
Type 400 series	E	
Type 904-L		
17-4 PH		
20 Cb 3	E	
E-Bright 26-1		
Silicon Bronze	E	
Silicon Copper		
Stellite		
Tantalum		
Titanium	E	
Zirconium		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030109


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

URIC ACID (CONC.)



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

URIC ACID (CONC.)

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)	R																					
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel	G																										
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron	E																										
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347	E																										
Type 316/316 L	E																										
Type 400 series	G																										
Type 904-L																											
17-4 PH	G																										
20 Cb 3	G																										
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030110

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

URINE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

URINE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R																					
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)	R																					
Ethylene-Propylene Terpolymer (EPT)	R																					
FKM (Viton A)	R																					
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)	R																					
Nitrile Buna-N (NBR)	R																					
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VANADIUM PENTAOXIDE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316	G																										
Type 400 series																											
Type 317/317 L	G																										
17-4 PH																											
20 Cb 3	G																										
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030111

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VANADIUM PENTAOXIDE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VANADIUM PENTAOXIDE

Plastics	°C	°F
ABS	15–238	60–460
Acetal	15–238	60–460
Acrylics	15–238	60–460
Asbestos Reinforced Epoxy	15–238	60–460
Asbestos Reinforced Phenolic	15–238	60–460
Chlorinated Polyether (Penton)	15–238	60–460
CPVC	15–238	60–460
E-CTFE (Halar)	15–238	60–460
Epoxy	15–238	60–460
ETFE (Tefzel)	15–238	60–460
FEP	15–238	60–460
Furan (Furfural Alcohol)	15–238	60–460
Noryl	15–238	60–460
Nylon 6	15–238	60–460
Nylon 11	15–238	60–460
Nylon 66	15–238	60–460
Phenolic	15–238	60–460
PFA (Teflon)	15–238	60–460
Polyamide-Imide	15–238	60–460
Polyesters	15–238	60–460
Bisphenol A–fumarate	15–238	60–460
Halogenated	15–238	60–460
Hydrogenated Bisphenol A –Bisphenol A	15–238	60–460
Isophthalic	15–238	60–460
Terephthalate (PET)	15–238	60–460
Polyetherimide (ULTEM)	15–238	60–460
Polyetheretherketone (PEEK)	15–238	60–460
Polyethersulfone (PES)	15–238	60–460
Polyethylene HMW	15–238	60–460
Polyethylene UHMW	15–238	60–460
Polymethylpentene	15–238	60–460
Polypropylene (PP)	15–238	60–460
Polystyrene	15–238	60–460
Polysulfone	15–238	60–460
Polyvinylidene Chloride	15–238	60–460
PVC Type 1	15–238	60–460
PVC Type 2	15–238	60–460
PVDF (Kynar)	15–238	60–460
Ryton	15–238	60–460
TFE (Teflon)	15–238	60–460
Vinyl Ester	15–238	60–460


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VANADIUM PENTAOXIDE

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030112

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VARNISH

Nonmetallic Materials	°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238
	°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460
Borosilicate Glass	R
Carbon	
Carbon-Graphite Resin Impregnated	
Ceramics	
Coatings	
Acrylic	
Asphalt	
Chlorinated Rubber	
Coal Tar	
Coal Tar Epoxy	
Epoxy General Purpose	
Epoxy Chemical Resistant	
Epoxy Polyamide	
Oil Base (Alkyd, Epoxy, Urethane)	
Phenolic	
Polyester	
Polyvinyl Chloride	U
Silicones	U
Urethanes	
Vinyls	U
Water Base	
Zinc Rich	
Mortars	
Silicate	
Sodium Silicate	
Potassium Silicate	
Silica	
Sulfur	
Furan Resin	
Polyester	
Epoxy	
	°F 60 80 100 120 140 160 180 200 220 240 260 280 300 320 340 360 380 400 420 440 460
	°C 15 26 38 49 60 71 82 93 104 116 127 138 149 160 171 182 193 204 216 227 238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


VARNISH

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)	U																					
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)	R																					
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)	R																					
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)	R																					
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers	U																					
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VEGETABLE OIL



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030113

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VEGETABLE OIL




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VEGETABLE OIL



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030114

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINEGAR




Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Exp*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.

VINEGAR

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS		R																				
Acetal		U																				
Acrylics		R																				
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)		R																				
CPVC		R																				
E-CTFE (Halar)		R																				
Epoxy		R				U																
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)		R																				
Noryl		R																				
Nylon 6		R																				
Nylon 11		R																				
Nylon 66		R																				
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate		R																				
Halogenated		R																				
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic		R																				
Terephthalate (PET)		R																				
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		R																				
Polyethylene UHMW		R																				
Polymethylpentene																						
Polypropylene (PP)		R																				
Polystyrene																						
Polysulfone		R																				
Polyvinylidene Chloride		R																				
PVC Type 1		R																				
PVC Type 2		R																				
PVDF (Kynar)		R																				
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINEGAR



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL ACETATE

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum		E																									
Aluminum Bronze																											
Brass		G																									
Bronze		G																									
Carbon Steel		G																									
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276		E																									
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Galv. Stl.		G																									
Monel 400		E																									
Naval Bronze		E	S																								
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347		E																									
Type 316/316 L		E						G																			
Type 400 series																											
Type 904-L																											
17-4 PH																											
20 Cb 3		E																									
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030115


Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL ACETATE



Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL ACETATE



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL ACETATE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)	R																				
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))	R																				
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	R																				
Ethylene-Propylene Terpolymer (EPT)	U																				
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)	R																				
Nitrile Buna-N (NBR)	R	U																			
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)	U																				
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass																											
Aluminum																											
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2	E																										
Hastelloy C/C-276	G																										
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400	E																										
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316	G																										
Type 400 series																											
Type 317/317 L	G																										
17-4 PH																											
20 Cb 3	G																										
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030116

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL CHLORIDE

Nonmetallic Materials	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																						
Carbon																						
Carbon-Graphite Resin Impregnated																						
Ceramics																						
Coatings																						
Acrylic																						
Asphalt																						
Chlorinated Rubber																						
Coal Tar																						
Coal Tar Epoxy																						
Epoxy General Purpose																						
Epoxy Chemical Resistant																						
Epoxy Polyamide																						
Oil Base (Alkyd, Epoxy, Urethane)																						
Phenolic																						
Polyester																						
Polyvinyl Chloride																						
Silicones																						
Urethanes																						
Vinyls																						
Water Base																						
Zinc Rich																						
Mortars																						
Silicate																						
Sodium Silicate																						
Potassium Silicate																						
Silica																						
Sulfur																						
Furan Resin																						
Polyester																						
Epoxy																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL CHLORIDE

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
ABS																						
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)																						
FEP																						
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)																						
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW																						
Polyethylene UHMW																						
Polymethylpentene																						
Polypropylene (PP)																						
Polystyrene																						
Polysulfone																						
Polyvinylidene Chloride																						
PVC Type 1																						
PVC Type 2																						
PVDF (Kynar)																						
Ryton																						
TFE (Teflon)																						
Vinyl Ester																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL CHLORIDE

Elastomers* and Linings	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																					
Butyl GR-1 (IIR)																					
Carboxylic-Acrylonitrile-Butadiene (XNBR)																					
Chemraz (FPM)																					
Chloro-Isobutene-Isoprene (CIIR)																					
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																					
Ethylene-Acrylic (EA)																					
Ethylene-Propylene (EPM)																					
Ethylene-Propylene-Diene (EPDM)	U																				
Ethylene-Propylene Terpolymer (EPT)																					
FKM (Viton A)	R																				
Hard Rubber																					
Soft Rubber																					
Isoprene (IR)																					
Kalrez (FPM)	R																				
Koroseal																					
Natural Rubber (GRS)																					
Neoprene GR-M (CR)																					
Nitrile Buna-N (NBR)	U																				
Nordel (EPDM)																					
Polybutadiene (BR)																					
Polyester (PE)																					
Polyether-Urethane (EU)																					
Polyisoprene (IR)																					
Polysulfides (T)																					
Polyurethane (AU)																					
SBR Styrene (Buna-S)																					
Silicone Rubbers																					
Fabrics																					
Cotton																					
Felt (Wool)																					
Rayon Viscose																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030117

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL CHLORIDE (RESIN)

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon	R																				
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride																					
Silicones																					
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL CHLORIDE (RESIN)

Plastics	°C	°F
ABS		
Acetal		
Acrylics		
Polycarbonate	U	
Asbestos Reinforced Phenolic		
Chlorinated Polyether (Penton)		
CPVC		
E-CTFE (Halar)		
Epoxy		
ETFE (Tefzel)	R	
FEP	R	
Furan (Furfural Alcohol)		
Noryl		
Nylon 6		
Nylon 11		
Nylon 66		
Phenolic		
PFA (Teflon)	R	
Polyamide-Imide		
Polyesters		
Bisphenol A–fumarate		
Halogenated		
Hydrogenated Bisphenol A –Bisphenol A		
Isophthalic		
Terephthalate (PET)		
Polyetherimide (ULTEM)		
Polyetheretherketone (PEEK)		
Polyethersulfone (PES)		
Polyethylene HMW		
Polyethylene UHMW		
Polymethylpentene		
Polypropylene (PP)		
Polystyrene		
Polysulfone		
Polyvinylidene Chloride		
PVC Type 1	U	
PVC Type 2	U	
PVDF (Kynar)	R	
Ryton		
TFE (Teflon)	R	
Vinyl Ester		

°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYL CHLORIDE (RESIN)

Elastomers* and Linings	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Acrylate-Butadiene (ABR)																						
Butyl GR-1 (IIR)																						
Carboxylic-Acrylonitrile-Butadiene (XNBR)																						
Chemraz (FPM)																						
Chloro-Isobutene-Isoprene (CIIR)																						
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))																						
Ethylene-Acrylic (EA)																						
Ethylene-Propylene (EPM)																						
Ethylene-Propylene-Diene (EPDM)																						
Ethylene-Propylene Terpolymer (EPT)																						
FKM (Viton A)																						
Hard Rubber																						
Soft Rubber																						
Isoprene (IR)																						
Kalrez (FPM)																						
Koroseal																						
Natural Rubber (GRS)																						
Neoprene GR-M (CR)																						
Nitrile Buna-N (NBR)																						
Nordel (EPDM)																						
Polybutadiene (BR)																						
Polyester (PE)																						
Polyether-Urethane (EU)																						
Polyisoprene (IR)																						
Polysulfides (T)																						
Polyurethane (AU)																						
SBR Styrene (Buna-S)																						
Silicone Rubbers																						
Fabrics																						
Cotton																						
Felt (Wool)																						
Rayon Viscose																						
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYLIDINE CHLORIDE RESIN

Metals	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
Admiralty Brass		E																									
Aluminum		E																									
Aluminum Bronze																											
Brass																											
Bronze																											
Carbon Steel																											
Columbium (Niobium)																											
Copper																											
Hastelloy B/B-2																											
Hastelloy C/C-276																											
Hastelloy D																											
Hastelloy G/G-3																											
High Silicon Iron																											
Inconel 600/625																											
Incolloy 800/825																											
Lead																											
Monel 400																											
Naval Bronze																											
Nickel 200/201																											
Ni-Resist																											
Stainless Steels																											
Type 304/347																											
Type 316/316 L																											
Type																											
Type 904-L																											
17-4 PH																											
20 Cb 3																											
E-Bright 26-1																											
Silicon Bronze																											
Silicon Copper																											
Stellite																											
Tantalum																											
Titanium																											
Zirconium																											
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238	249	260	271	282	293

FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS

R = Resistant

U = Unsatisfactory

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030118

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYLIDINE CHLORIDE RESIN

Nonmetallic Materials	°C 15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F 60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Borosilicate Glass																					
Carbon																					
Carbon-Graphite Resin Impregnated																					
Ceramics																					
Coatings																					
Acrylic																					
Asphalt																					
Chlorinated Rubber																					
Coal Tar																					
Coal Tar Epoxy																					
Epoxy General Purpose																					
Epoxy Chemical Resistant																					
Epoxy Polyamide																					
Oil Base (Alkyd, Epoxy, Urethane)																					
Phenolic																					
Polyester																					
Polyvinyl Chloride																					
Silicones																					
Urethanes																					
Vinyls																					
Water Base																					
Zinc Rich																					
Mortars																					
Silicate																					
Sodium Silicate																					
Potassium Silicate																					
Silica																					
Sulfur																					
Furan Resin																					
Polyester																					
Epoxy																					
°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

VINYLIDINE CHLORIDE RESIN

Plastics	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
Polycarbonate		U																				
Acetal																						
Acrylics																						
Asbestos Reinforced Epoxy																						
Asbestos Reinforced Phenolic																						
Chlorinated Polyether (Penton)																						
CPVC																						
E-CTFE (Halar)																						
Epoxy																						
ETFE (Tefzel)		R																				
FEP		R																				
Furan (Furfural Alcohol)																						
Noryl																						
Nylon 6																						
Nylon 11																						
Nylon 66																						
Phenolic																						
PFA (Teflon)		R																				
Polyamide-Imide																						
Polyesters																						
Bisphenol A–fumarate																						
Halogenated																						
Hydrogenated Bisphenol A –Bisphenol A																						
Isophthalic																						
Terephthalate (PET)																						
Polyetherimide (ULTEM)																						
Polyetheretherketone (PEEK)																						
Polyethersulfone (PES)																						
Polyethylene HMW		U																				
Polyethylene UHMW		U																				
Polymethylpentene		U																				
Polypropylene (PP)		U																				
Polystyrene																						
Polysulfone		U																				
Polyvinylidene Chloride		U																				
PVC Type 1		U																				
PVC Type 2		U																				
PVDF (Kynar)		R																				
Ryton																						
TFE (Teflon)		R																				
Vinyl Ester		R																				
	°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
	°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.


VINYLIDINE CHLORIDE RESIN

Elastomers* and Linings	°F	°C
Acrylate-Butadiene (ABR)		
Butyl GR-1 (IIR)		
Carboxylic-Acrylonitrile-Butadiene (XNBR)		
Chemraz (FPM)		
Chloro-Isobutene-Isoprene (CIIR)		
Hypalon (Chloro-Sulfonyl-Polyethylene (CSM))		
Ethylene-Acrylic (EA)		
Ethylene-Propylene (EPM)		
Ethylene-Propylene-Diene (EPDM)		
Ethylene-Propylene Terpolymer (EPT)		
FKM (Viton A)		
Hard Rubber		
Soft Rubber		
Isoprene (IR)		
Kalrez (FPM)	R	
Koroseal		
Natural Rubber (GRS)		
Neoprene GR-M (CR)		
Nitrile Buna-N (NBR)		
Nordel (EPDM)		
Polybutadiene (BR)		
Polyester (PE)		
Polyether-Urethane (EU)		
Polyisoprene (IR)		
Polysulfides (T)		
Polyurethane (AU)		
SBR Styrene (Buna-S)		
Silicone Rubbers		
Fabrics		
Cotton		
Felt (Wool)		
Rayon Viscose		

°F	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460
°C	15	26	38	49	60	71	82	93	104	116	127	138	149	160	171	182	193	204	216	227	238

*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



FOR METALS

E = < 2 Mils Penetration/Year; G = < 20 Mils Penetration/Year

S = < 50 Mils Penetration/Year; U = > 50 Mils Penetration/Year

FOR NONMETALLICS


R = Resistant

U = Unsatisfactory


Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded* DOI: 10.1081/5672-X-120030119

Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

WATER, ACID MINE




Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.



Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

WATER, ACID MINE



*See also Nylon 11 under PLASTICS

Schweitzer/*Corrosion Resistance Tables: Fifth Edition, Revised and Expanded*
Copyright © 2004 by Marcel Dekker, Inc. All rights reserved. For more information, go to www.dekker.com.

Appendix 1: Chemical Synonyms

Synonym	Listed under
Acetic acid amine	Acetamide
Acetic acid crude	Pyroligneous acid
Acetic ether	Ethyl acetate
Acetol	Diacetone alcohol
Acetyl benzene	Acetophenone
Acetylene tetrachloride	Tetrachloroethane
Almond oil	Benzaldehyde
Aluminum hydrate	Aluminum hydroxide
Aluminum potassium chrome	Chrome alum
Alum potash	Aluminum potassium sulfate
Amino benzene	Aniline
Ammonium fluoride, acid	Ammonium bifluoride
Antimony chloride	Antimony trichloride
Baking soda	Sodium carbonate
Benzene carbonal	Benzaldehyde
Benzene carboxylic acid	Benzoic acid
Benzine	Petroleum ether
Benzol	Benzene
Benzyl ether	Dibenzyl ether
Boracic acid	Boric acid
Bromo-butane	Butyl bromide
Bromomethane	Methyl bromide
Butanol-1	Butyl alcohol
Butanol-2	Butyl alcohol, secondary
Butanoic acid	Butyric acid
Butanone	Methyl ethyl ketone
Butanthiol-1	Butyl mercaptan
Butter of antimony	Antimony trichloride
Butyl phthalate	Dibutyl phthalate
Calcium disulfide	Calcium bisulfide
Calcium sulfide	Lime sulfur
Carbamide	Urea
Carbolic acid	Phenol
Carbon oxychloride	Phosgene
Carbonyl chloride	Phosgene

Synonym	Listed under
Caustic potash	Potassium hydroxide
Caustic soda	Sodium hydroxide
Chlorinated polyphenol	Aroclor
Chlorobenzene	Monochlorobenzene
1-Chloro-butane	Butyl chloride
Chlorodifluoro-methane	Freon F-22
Chloroethane	Ethyl chloride
Chloroethanoic acid	Chloroacetic acid
Chloromethane	Methyl chloride
Chloropentane	Amyl chloride
3-Chloro-propene-1	Allyl chloride
Chlorotoluene	Benzyl chloride
Chromium trioxide	Chromic acid
Coal tar	Creosote
Corn syrup	Glucose
Cupric acetate	Copper acetate
Cupric carbonate	Copper carbonate
Cupric fluoride	Copper fluoride
Cupric nitrate	Copper nitrate
Cupric sulfate	Copper sulfate
Cuprous chloride	Copper chloride
Diacetone	Diacetone alcohol
Dibromoethane	Ethylene bromide
Dibutyl ether	Butyl ether
Dichloroethane	Ethylene dichloride
Dichloroethene	Dichloroethylene
Dichloromethane	Methylene chloride
Diethyl	Butane
Diethylene dioxide	Dioxane
Diethylene di-imide oxide	Morpholine
Dihydroxy benzene	Resorcinol
Dihydroxy ethane	Glycol, ethyleneglycol
Dimethyl benezene	Xylene
Dimethyl polysiloxane	Silicone oil
Dimethyl sulfate	Methyl sulfate
Diphenyl ether	Diphenyl oxide
Dipropyl	Hexane
Dipropyl ether	Isopropyl ether
Dodecyl chloride	Lauryl chloride
Dowtherm	Diphenyl
Epsom salt	Magnesium sulfate
Ethanal	Acetaldehyde
Ethanamide	Acetamide
Ethanoic acid	Acetic acid
Ethanoic anhydride	Acetic anhydride
Ethanonitrile	Acetonitrile
Ethanol	Ethyl alcohol
Ethanoyl chloride	Acetyl chloride
Ethoxy ethanol	Cellosolve
Ethylene chloride	Ethylene dichloride
Ethyl ether	Diethyl ether
Fluorosilicic acid	Hydrofluorosilicic acid

Synonym	Listed under
Formalin	Formaldehyde
Furfuraldehyde	Furfural
Furfurol	Furfural
Glucose	Dextrose, corn syrup
Glycerol	Glycerine
Glycol	Ethylene glycol
Glycol ether	Diethylene glycol
Glycol methyl ether	Methyl cellosolve
Hexamethylene	Cyclohexane
Hexamethylene tetramine	Hexamine
Hexandioic acid	Adipic acid
Hexose	Dextrose
Hexyl alcohol	Hexanol
Hydrogen iodide	Hydriodic acid
Hydroxy benzoic acid	Salicylic acid
Hypo photographic solution	Sodium thiosulfate
Isopropyl benzene	Cumene
Ligroin	Petroleum ether
Lime	Calcium oxide
Lime sulfur	Calcium sulfide
Lithic acid	Uric acid
Marsh gas	Methane
Methanal	Formaldehyde
Methane sulfonic acid	Methyl sulfonic acid
Methanoic acid	Formic acid
Methanol	Methyl alcohol
Methyl benzene	Toluene
Methyl chloroform	Trichloroethane
Methyl cyanide	Acetonitrile
Methyl ether	Dimethyl ether
Methyl phenol	Cresol
Methyl phenol ketone	Acetophenone
Methyl phthalate	Dimethyl phthalate
Methyl propane-2	Butyl alcohol, tertiary
Methyl sulfonic acid	Methane sulfonic acid
Nitrochloroform	Chloropicrin
Nitrogen oxide, tri-	Nitrous acid
Octanoic acid	Caprylic acid
Oil of mirbane	Nitrobenzene
Oil of wintergreen	Methyl salicylate
Oxalic nitrile	Cyanogen
Phenyl amine	Aniline
Phenyl bromide	Bromobenzene
Phenyl carbinol	Benzyl alcohol
Phenyl chloride	Chlorobenzene
Phenyl cyanide	Benzonitrile
Phenyl ethane	Ethyl benzene
Phosphine	Hydrogen phosphide
Pimelic ketone	Cyclohexanone
Pinene	Dipentene
Polyphenylene sulfide	Ryton
Propanoic acid	Propionic acid

Synonym	Listed under
Propanol	Propyl alcohol
Propanone	Acetone
Propanyl alcohol	Allyl alcohol
Propenoic acid	Acrylic acid
Propyl acetate	Isopropyl acetate
Prussic acid	Hydrocyanic acid
Pyrogallol	Pyrogallic acid
Red oil	Oleic acid
Salammoniac	Ammonium chloride
Sodium borate, tetra	Borax
Sodium phosphate, dibasic	Disodium phosphate
Starch gum	Dextrin
Sugar of lead	Lead acetate
Sulfoanthraquinone	Anthraquinone sulfuric acid
Sulfuric chlorohydrin	Chlosulfonic acid
Tannin	Tannic acid
Tetrachloroethylene	Perchlorethylene
Tetrachloromethane	Carbon tetrachloride
Tetrahydronaphthalene	Tetralin
Toluol	Toluene
Trichloroacetic aldehyde	Chloral hydrate
Trichloromethane	Chloroform
Trihydroxy benzene	Pyrogallic acid
Trihydroxy benzoic acid	Gallic acid
Trinitrophenol	Petrolatum
Vaseline	Picric acid
Vinyl cyanide	Acrylonitrile
Water glass	Sodium silicate

Appendix 2: Cross-Reference of Trade Names to Generic Names

Trade name/designation	Generic name
Adiprene[a]	Urethane (AU)
Bayprene[b]	Polychloroprene (CR)
Baysilone[b]	Silicone rubber (SI)
Baytec[b]	Urethane (AU)
Blue-sil[n]	Silicone rubber (SI)
Buna-85	Polybutadiene (BR)
Buna-CB[b]	Polybutadiene (BR)
Buna-N	Butadiene-acrylonitrile (NBR)
Buna-S	Butadiene-styrene-elastomer (SBR)
Chemraz[j]	Perfluoroelastomers (FPM)
Cohrplastic[o]	Silicone rubber (SI)
Conathane[p]	Urethane (AU)
CSM	Chlorosulfonated polyethylene
Cycolac[ac]	Acrylonitrile-butadiene-styrene (ABS)
Duracryn[a]	Thermoplastic elastomer (TPE)
Dutral[r]	Ethylene-propylene-diene (EPDM)
Flexsorb[q]	Thermoplastic elastomer (TPE)
Fluorel[f]	Fluoroelastomers (FKM)
Foraflon[f]	Polyvinylidene fluoride (PVDF)
Futura-thane[k]	Urethane (AU)
Geolast[r]	Thermoplastic elastomer (TPE)
GR-1	Butyl rubber (IIR)
Green-sil[n]	Silicone rubber (SI)
GR-S	Butadiene-styrene elastomer (SBR)
Halar[i]	ECTFE
Halon-ET[i]	Ethylene-tetrafluorethylene (ETFE)
Hypalon[a]	Chlorosulfonated polyethylene (CSM)
Hytrel[a]	Polyester elastomer (PE)
Kalar[s]	Butyl rubber (IIR)
Kalrez[a]	Perfluoroelastomer (FPM)
Kel-F[f]	Perfluoroelastomer (FPM)
Kodapak[t]	Thermoplastic elastomer (TPE)
Kodar[t]	Polyester elastomer (PE)
Kraton-D[c]	Styrene-butadiene-styrene rubber (SBS)
Kraton-G[c]	Styrene-ethylene-butylene-styrene rubber (SEBS)
Kynar[g]	Polyvinylidene fluoride (PVDF)
Lennite[ad]	Ultra high molecular weight polyethylene (UHMW)
Milkon[af]	Polyphenylene sulfide
NBR	Butadiene-acrylonitrile rubber
Neoprene[a]	Polycloroprene (CR)
Nordel[a]	Ethylene-propylene-diene monomer (EPDM)
Noryl[aa]	Modified phenylene oxide
Nylon[a]	Polyamide

Trade name/designation	Generic name
Nytek[u]	Butadiene-acrylonitrile (NBR) rubber
Parshield[m]	Silicone rubber (SI)
Pellethane[v]	Urethane (AU)
Petbunan[b]	Butadiene-acrylonitrile (NBR) rubber
Plaskon[y]	Polyamide
Propylux[ab]	Polypropylene
Pure-CMC[n]	Urethane (AU)
Rilsan[e]	Polyamide
Royalene[h]	Ethylene-propylene-diene (EPDM) rubber
Ryton[ae]	Polyphenylene sulfide
Santoprene[r]	Thermoplastic elastomer (TPE)
Technoflon[i]	Fluoroelastomer (FKM)
Tefzel[a]	Ethylene-tetrafluorethylene (ETFE)
Texin[b]	Urethane (AU)
Thermalux[ag]	Polysulfone
Thiokol[d]	Polysulfide (ST) (FA)
Ultem[l]	Polyetherimide
Urane[w]	Urethane (AU)
Vamac[a]	Ethylene-acryllic elastomer (EA)
Victrex[z]	Polyether sulfone (PES series)
Victrex[z]	Polyetherether ketone (PEEK series)
Viton[a]	Fluoroelastomer (FKM)
Vydyne[r]	Polyamide
Zurcon[x]	Thermoplastic elastomer (TPE)

Registered trademarks of:
[a] E. I. du Pont.
[b] Mobay Corp.
[c] Shell Chemical Co.
[d] Morton Thiokol Inc.
[e] Atochem Inc.
[f] 3-M Corp.
[g] Pennwalt Corp.
[h] Uniroyal.
[i] Ausimont.
[j] Greene, Tweed & Co. Inc.
[k] Futura Coatings, Inc.
[l] Westlake Plastics Co.
[m] Parker Seal Group.
[n] The Perma-Flip Mold Co.
[o] CHR Industries.
[p] Conap Inc.
[q] Polymer Corp.
[r] Monsanto Co.
[s] Hardman Inc.
[t] Eastman Chemical Products Inc.
[u] Edmont Div. of Becton Dickinson & Co.
[v] Dow Chemical U.S.A.
[w] Krebs Engineers.
[x] U.S. Shamban & Co.
[y] Allied Signal.
[z] ICI Ltd.
[aa] General Electric Co.
[ab] Aristech, Inc.
[ac] Borg Warner Chemical Co.
[ad] Himont U.S.A.
[ae] Phillips Petroleum Co.
[af] Tribol Industries.
[ag] Amoco Performance Products.

Appendix 3: Plating Solution Composition

Brass
3% Copper, 1% zinc, and 5.6% sodium
3% Cyanide
Sodium carbonate

Cadmium cyanide
3% Cadmium oxide
10% Sodium cyanide
1.2% Sodium hydroxide

Chrome 25%
25% CrO_3
12% Sulfuric acid
Water

Chrome 40%
40% CrO_3
12% Sulfuric acid
Water

Copper cyanide
10.5% Copper
14% Sodium cyanide
6% Rochelle salts

Gold
22.8% Potassium ferrocyanide
0.2% Potassium gold cyanide
0.8% Sodium cyanide
Water to make 1 gallon

Iron
45% $FeCl_2$
20% $FeSO_4$

[Iron]
15% $CaCl_2$
11% $(NH_4)_2SO_4$

Lead
8% Lead
0.8% Fluoboric acid
0.4% Boric acid
Water to make 1 gallon

Nickel
11% Nickel sulfate
2% Nickel chloride
1% Boric acid
86% Water

Silver
4% Silver
7% Potassium cyanide
5% Sodium cyanide
2% Potassium carbonate

Tin
7% Tin
18% Stannous fluoborate
9% Fluoboric acid
2% Boric acid

Zinc
9% Zinc cyanide
9% Sodium hydroxide
4% Sodium cyanide

CORROSION RESISTANCE TABLES

Fifth Edition, Revised and Expanded

"...extremely accessible information on comparative material performance...[a] **useful** corrosion guide to anyone involved in the selection of materials." *—Materials & Design*

"...of inestimable value in assisting not only the practicing engineer...but also any general student of science."*—Chemical Industry News*

"...The author has done an **excellent** job in preparing this guide. It is recommended for the specialist and any library."*—Electrochemical Progress*

about the fifth edition . . .

Invested with state-of-the-art research on mechanisms of corrosion and advancements in corrosion resistance, this revised and expanded ***Fifth Edition*** serves as a convenient, single-source tabular guide to materials used in the construction of all system components—from vessels to pumps to gaskets and packing—for specific processes and applications.

The consummate fingertip reference for engineers, students, and industry personnel determining material attributes and operational suitability given exposure to possibly corrosive chemicals.

Authored by one of the most respected names in the field, the ***Fifth Edition*** of ***Corrosion Resistance Tables*** offers tables for 83 additional corrodents covered for the first time...presents new data on previously charted materials and corrodents...organizes tables alphabetically by corrodent for ease of navigation...provides four pages of information per corrodent, grouping tables by resistance to categories of corrosives...and reflects the latest technological developments and research on material usage.

about the author . . .

PHILIP A. SCHWEITZER, P.E. is a consultant in corrosion prevention, materials of construction, and chemical engineering based in York, Pennsylvania. A former Contract Manager for Chem-Pro Corporation, Fairfield, New Jersey, he is the editor of the *Corrosion Engineering Handbook* and the *Corrosion and Corrosion Protection Handbook, Second Edition*; and the author of the *Encyclopedia of Corrosion Technology, Second Edition; Metallic Materials; Corrosion-Resistant Linings and Coatings; Atmospheric Degradation and Corrosion Control; What Every Engineer Should Know About Corrosion; Corrosion Resistance of Elastomers; Corrosion-Resistant Piping Systems*; and *Mechanical and Corrosion-Resistant Properties of Plastics and Elastomers* (all titles, Marcel Dekker, Inc.). He is a licensed engineer in New Jersey, a member of the American Institute of Chemical Engineers, and editor of the *Corrosion Technology* series (Marcel Dekker, Inc.). Mr. Schweitzer received the B.Ch.E. degree (1950) from the Polytechnic University (formerly Polytechnic Institute of Brooklyn), Brooklyn, New York.

Printed in the United States of America



MARCEL DEKKER, INC.
NEW YORK • BASEL

ISBN 0-8247-5676-2



PART D
POT-ZIN

CORROSION RESISTANCE TABLES

Fifth Edition, Revised and Expanded

Schweitzer
66/343

MARCEL
DEKKER