


ANSI/ISA-75.08-1999

Formerly ANSI/ISA-S75.08-1999



Installed Face-to-Face Dimensions for Flanged Clamp or Pinch Valves



**ISA—The Instrumentation,
Systems, and
Automation Society**

Approved 31 August 1999

ANSI/ISA-75.08-1999
Installed Face-to-Face Dimensions for Flanged Clamp or Pinch Valves

ISBN 0-87664-907-X

Copyright © 1999 by the Instrument Society of America. All rights reserved. Printed in the United States of America. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), without the prior written permission of the publisher.

ISA
67 Alexander Drive
P.O. Box 12277
Research Triangle Park, North Carolina 27709

Preface

This preface is included for informational purposes and is not part of ANSI/ISA-75.08-1999.

This standard has been prepared as part of the service of ISA toward a goal of uniformity in the field of instrumentation. To be of real value, this document should not be static, but should be subject to periodic review. Toward this end, the Society welcomes all comments and criticisms, and asks that they be addressed to the Secretary, Standards and Practices Board. ISA, 67 Alexander Drive, P.O. Box 12277, Research Triangle Park, NC 27709, Telephone (919) 549-8411, e-mail: standards@isa.org.

The ISA Standards and Practices Department is aware of the growing need for attention to the metric system of units in general, and the International System of Units (SI) in particular, in the preparation of instrumentation standards. The Department is further aware of the benefits to U.S.A. users of ISA standards of incorporating suitable references to the SI (and the metric system) in their business and professional dealings with other countries. Toward this end, this Department will endeavor to introduce SI-acceptable metric units in all new and revised standards to the greatest extent possible. *The Metric Practice Guide* which has been published by the Institute of Electrical and Electronics Engineers as ANSI/IEEE Std. 268-1982 and future revisions will be the reference guide for definitions, symbols, abbreviations, and conversion factors.

It is the policy of ISA to encourage and welcome the participation of all concerned individuals and interests in the development of ISA standards. Participation in the ISA standards-making process by an individual in no way constitutes endorsement by the employer of that individual, of ISA, or of any of the standards that ISA develops.

The information contained in this preface, footnotes, and appendices is included for information only and is not a part of the standard.

The following people served as members of ISA Subcommittee SP75.08, which prepared this standard:

NAME	COMPANY
H. R. Nickerson, Chairman	Resistoflex Company
G. Borden	Bechtel Power Corporation
C. Clarkson	Clarkson Company
F. Dicosimo	Robbin-Meyers
J. T. Emery	Honeywell, Inc.
B. Howes	Galigher-Ash Valve
R. B. Jones	Dow Chemical Company
M. W. Kaye	M. W. Kellogg Company,
A. Levin	Red Valve Company, Inc.
E. Lincoln	Flow-Con Valve Corporation
O. P. Lovett, Jr.	ISIS Corporation
R. A. Quance	Walsh, Inc.

H. Rich/R. Brodin
H. Schwartz
J. M. Simonsen
R. U. Stanley
W. C. Weidman

Fisher Controls International, Inc.
Flexible Valve Corporation
Valtek, Inc.
Retired
Gilbert/Commonwealth, Inc.

The following people served as members of ISA Committee SP75 during the review of this standard:

NAME	COMPANY
L. R. Driskell, Chairman	Consultant
J. B. Arant	E. I. du Pont de Nemours and Company, Inc.
H. E. Backinger	John F. Kraus & Company
G. Barb	Muesco, Inc.
H. D. Baumann	H. D. Baumann Associates, Ltd.
C. S. Beard*	
N. Belaef	Consultant
G. Borden	Bechtel Power Corporation
R. Brodin/G. F. Stiles**	Fisher Controls International, Inc.
E. H. C. Brown	Dravo Engineers, Inc.
E. J. Cooney	Air Products & Chemicals, Inc.
W. G. Dewart	Rockwell International
J. T. Emery	Honeywell, Inc.
H. J. Fuller	Worcester Controls Corporation
L. Griffith	Consultant
A. J. Hanssen	Fluid Controls Institute, Inc.
F. P. Harthun	Fisher Controls International, Inc.
H. P. Illing	Kieley & Mueller, Inc.
R. B. Jones	Dow Chemical Company
M. W. Kaye	M. W. Kellogg Company
R. Louviere	Creole Engineering
O. P. Lovett, Jr.	ISIS Corporation
A. P. McCauley	Chagrin Valley Controls, Inc.
T. V. Molloy	Pacific Gas & Electric
H. R. Nickerson	Resistoflex Company
J. Ozol	Omaha Public Power Company
R. A. Quance	Walsh Inc.
W. Rahmeyer	Colorado State University
J. N. Reed	Masoneilan/Dresser
G. Richards	Jordan Valve Div., Richards Industries, Inc.

*Deceased

**One vote

J. Rosato
 K. Schoonover, Secretary
 H. Schwartz
 W. L. Scull/J. T. Muller**
 F. O. Seger
 J. M. Simonsen
 H. R. Sonderregger
 N. D. Sprecher
 R. U. Stanley
 R. E. Terhune, Vice-Chairman
 R. F. Tubbs
 W. C. Weidman
 R. L. Widdows
 L. Zinck

Rawson Company
 Con-Tek
 Flexible Valve Corporation
 Leslie Company
 Willis Division, Smith International, Inc.
 Valtek, Inc.
 ITT Grinnell Corporation
 DeZurik
 Retired
 Consultant
 Copes-Vulcan
 Gilbert/Commonwealth, Inc.
 Cashco, Inc.
 Union Carbide Corporation

This standard was approved for publication by the ISA Standards and Practices Board in August 1985.

NAME

COMPANY

N. Conger, Chairman
 P. V. Bhat
 W. Calder III
 R. S. Crowder
 B. Feikle
 H. S. Hopkins
 J. L. Howard
 R. T. Jones
 R. Keller
 O. P. Lovett, Jr.
 E. C. Magison
 A. P. McCauley
 J. W. Mock
 E. M. Nesvig
 R. Prescott
 D. E. Rapley
 C. W. Reimann
 J. Rennie
 W. C. Weidman
 K. Whitman
 P. Bliss***

Fisher Controls Company
 Monsanto Company
 The Foxboro Company
 Ship Star Associates
 OTIS
 Westinghouse Electric Company
 Boeing Aerospace Company
 Philadelphia Electric Company
 The Boeing Company
 ISIS Corporation
 Honeywell, Inc.
 Chagrin Valley Controls, Inc.
 Bechtel Corporation
 ERDCO Engineering Corporation
 Moore Products Company
 Rapley Engineering Services
 National Bureau of Standards
 Factory Mutual Research Corporation
 Gilbert/Commonwealth, Inc.
 Consultant
 Consultant

**One vote
 ***Director Emeritus

B. A. Christensen***
L. N. Combs***
R. L. Galley***
T. J. Harrison***
R. G. Marvin***
W. B. Miller***
G. Platt***
J. R. Williams***

Continental Oil Company
Retired
Consultant
IBM Corporation
Roy G. Marvin Company
Moore Products Company
Retired
Stearns Catalytic Corporation

***Director Emeritus

Contents

1 Scope	9
2 Purpose	9
3 Definitions	9
4 Bibliography	10
5 Dimensional data of installed valves	10
Appendix.....	12

1 Scope

1.1 This standard applies to valves, sizes 1 inch through 8 inches of the clamp or pinch valve design incorporating clamp or pinch elements.

2 Purpose

2.1 The purpose of this standard is to aid users in their piping design by providing installed face-to-face dimensions for control valves, incorporating clamp or pinch elements, which have flanges that mate with ANSI B16.1 Class 125 (PN20) and/or ANSI B16.5 Class 150 (PN20) flanges, without giving special consideration to the manufacturer of the equipment to be used.

2.2 This standard excludes solenoid-actuated valves and direct fluid-actuated valves.

2.3 In the absence of other standards, this standard can be applied to handwheel-operated valves.

3 Definitions

3.1 For definitions of terms used in this standard, see ISA-S75.05-1983, "Control Valve Terminology."

3.2 One-piece-element clamp or pinch valve: A *one-piece-element clamp* or *pinch valve* is a valve consisting of a one-piece flexible element or liner installed in a body with the element or liner extending over the flange faces and acting as gaskets between the valve and connecting piping. See Table 1 for dimensions. "Long style" dimensions are the same as those for flanged-end control valves in ANSI B16.10 and ANSI/ISA-S75.03-1985 except for the 6-inch size. "Short style" dimensions are the same as those for flanged-end gate valves in ANSI B16.10 and MSS SP-72, except for the 6-inch and the 8-inch sizes.

3.3 Two-piece-element clamp or pinch valve: A *two-piece-element clamp* or *pinch valve* is a valve consisting of two flexible elastomeric elements or liners installed between a two-piece flanged body. The flexible elements or liners also extend over the flange faces and act as gaskets between the valve and the connecting piping. See Table 2 for dimensions. No prior standards exist for these two-piece-element valves.

3.4 Face-to-face: Each of the *face-to-face* dimensions in the tables is to be applied to the installed length of the valve after installation into a piping system. The free length face-to-face dimension of a valve before installation into a piping system may be slightly longer than dimensions shown in either Table 1 or Table 2.

4 Bibliography

4.1 American National Standards Institute, Inc. (ANSI) Standard B16.10-1973, "Face-to-Face and End-to-End Dimensions of Ferrous Valves."

4.2 American National Standards Institute, Inc., ANSI/ISA-S75.03-1985, "Face-to-Face Dimensions for Flanged Globe-Style Control Valve Bodies."

4.3 ISA Standard ISA-S75.05-1983, "Control Valve Terminology."

4.4 Manufacturers Standardization Society of the Valve and Fittings Industry, Inc. (MSS), SP-72-1970, "Ball Valves with Flanged or Butt-Welding Ends for General Service."

5 Dimensional data of installed valves

5.1 For face-to-face dimensions for flanged clamp or pinch valves, see Tables 1 and 2.

Table 1 — One-piece-element design

(See Paragraph 3.2)

Nominal Valve Size		Installed Face-to-Face Dimension "A" ^a			
		Long Style		Short Style	
		mm ^{b,c}	inches ^{b,c}	mm ^{b,c}	inches ^{b,c}
25	1	184	7.25	127	5.00
40	1-1/2	222	8.75	165	6.50
50	2	254	10.00	178	7.00
65	2-1/2	276	10.88	190	7.50
80	3	298	11.75	203	8.00
100	4	352	13.88	229	9.00
125	5	381	15.00	—	—
150	6	457	18.00	406	16.00
200	8	543	21.38	483	19.00

^a See Figure 1 for dimension "A"

^b Tolerance for 25 through 125-mm (1 through 5-inch) size valves:
±1.5 mm (±0.06 inches)

^c Tolerance for 150 and 200-mm (6 and 8-inch) size valves:
±3.0 mm (±0.12 inches)

Table 2 — Two-piece-element design

(See Paragraph 3.3)

Nominal Valve Size		Installed Face-to-Face Dimension "A" ^a	
mm	inches	mm ^b	inches ^b
25	1	133	5.25
40	1-1/2	178	7.00
50	2	229	9.00
65	2-1/2	254	10.00
80	3	305	12.00
100	4	381	15.00
150	6	495	19.50
200	8	625	24.63

^a See Figure 1 for dimension "A"

^b Tolerance for all size valves: ± 1.5 mm (± 0.06 inches)




Figure 1 — Installed face-to-face dimension "A"

Appendix

This appendix is not part of the ISA Standard S75.08 but is included to facilitate its use.

Dimensions for metrically sized valves are nominal conversions that are conventionally used in documents by the Manufacturers Standardization Society (MSS) of the Valve and Fitting Industry (MSS-SP86-1981), by the International Organization for Standardization (ISO), and by the International Electrotechnical Commission (IEC).

Developing and promulgating technically sound consensus standards, recommended practices, and technical reports is one of ISA's primary goals. To achieve this goal the Standards and Practices Department relies on the technical expertise and efforts of volunteer committee members, chairmen, and reviewers.

ISA is an American National Standards Institute (ANSI) accredited organization. ISA administers United States Technical Advisory Groups (USTAGs) and provides secretariat support for International Electrotechnical Commission (IEC) and International Organization for Standardization (ISO) committees that develop process measurement and control standards. To obtain additional information on the Society's standards program, please write:

ISA
Attn: Standards Department
67 Alexander Drive
P.O. Box 12277
Research Triangle Park, NC 27709

ISBN: 0-87664-907-X